

Paalsysteem: DPA+

Werknummer: 61220523

Rc;net;d

<-----kN----->					
Sondering	Maaiveld	Paalpunt	Ø360*510	Ø460*610	Ø560*710
<----m tov NAP-----><-----mm----->					
1	3.49	-21.00	526	772	1055
1	3.49	-21.25	549	800	1101
1	3.49	-21.50	579	889	1249
1	3.49	-21.75	676	993	1383
1	3.49	-22.00	709	1147	1446
1	3.49	-22.25	852	1263	1182
1	3.49	-22.50	874	987	1132

2	3.46	-21.00	728	1007	1126
2	3.46	-21.25	797	861	1181
2	3.46	-21.50	635	909	1231
2	3.46	-21.75	656	940	1273
2	3.46	-22.00	681	979	1312
2	3.46	-22.25	702	1014	1359
2	3.46	-22.50	718	1050	1388

3	3.33	-21.00	435	688	976
3	3.33	-21.25	528	852	1270
3	3.33	-21.50	682	1028	1408
3	3.33	-21.75	699	1052	1480
3	3.33	-22.00	732	1095	1454
3	3.33	-22.25	736	1110	1053
3	3.33	-22.50	744	941	939

4	3.32	-21.00	784	1215	1693
4	3.32	-21.25	813	1257	1728
4	3.32	-21.50	845	1292	1643
4	3.32	-21.75	878	1275	909
4	3.32	-22.00	930	1098	927
4	3.32	-22.25	899	696	928
4	3.32	-22.50	551	721	912

5	3.45	-21.75	446	671	947
5	3.45	-22.00	485	724	1007
5	3.45	-22.25	523	776	1075
5	3.45	-22.50	556	816	1121
5	3.45	-22.75	564	818	1065
5	3.45	-23.00	545	867	1048

6	3.49	-22.25**	551	869	1120
6	3.49	-22.50	753	1071	1063
6	3.49	-22.75	803	833	1016
6	3.49	-23.00***	677	789	987

7	3.55	-21.00	692	1015	1389
7	3.55	-21.25	727	1088	1538
7	3.55	-21.50	870	1284	1738
7	3.55	-21.75	920	1344	1809
7	3.55	-22.00	960	1377	1770
7	3.55	-22.25	985	1431	1268
7	3.55	-22.50	1021	1153	1189

** Niet kiezen; ter info.

*** Niet dieper i.v.m. afnemende draagkracht.

Werknummer: 61220523

Rc;net;d

			<-----kN----->		
Sondering	Maaiveld	Paalpunt	Ø360*360	Ø460*460	Ø560*560
<----m tov NAP----->			<-----mm----->		
8	3.51	-21.00**	623	948	952
8	3.51	-21.25	680	866	991
8	3.51	-21.50	642	743	1023
8	3.51	-21.75	572	770	1072
8	3.51	-22.00	543	796	1084
8	3.51	-22.25	551	808	1098
8	3.51	-22.50	557	807	1082
9	3.37	-21.00	613	969	1381
9	3.37	-21.25	670	1040	1469
9	3.37	-21.50	690	1069	1537
9	3.37	-21.75	762	1199	1718
9	3.37	-22.00	835	1294	1864
10	3.52	-21.00	615	940	1333
10	3.52	-21.25	632	962	1358
10	3.52	-21.50	650	982	1386
10	3.52	-21.75	667	1007	1409
10	3.52	-22.00	685	1026	1442
11	3.58	-20.75**	644	947	825
11	3.58	-21.00	684	659	852
11	3.58	-21.25	725	650	883
11	3.58	-21.50	471	674	911
11	3.58	-21.75	482	689	925
11	3.58	-22.00	498	707	950
12	3.55	-20.75**	720	1105	1573
12	3.55	-21.00	844	1257	1367
12	3.55	-21.25	898	1110	1401
12	3.55	-21.50	948	1067	1454
12	3.55	-21.75	779	1093	1484
12	3.55	-22.00	787	1138	1538

Rc;net;d = rekenwaarde netto draagkracht

APRSON version 1.0.0.36

PRJ : u:_aprprj\2022\61220523-2dpa+.prj

XLS : u:_aprxls\2022\61220523-2.xlsx

GEF : u:_aprgef\2022\61220523*.gef

** Niet kiezen; ter info.

Paalsysteem: Vibro

Werknummer: 61220523

Rc;net;d

<-----kN----->						
Sondering	Maaiveld	Paalpunt	Ø380*465	Ø406*495	Ø457*560	Ø559*680
<----m tov NAP-----><-----mm----->						
1	3.49	-21.00	971	1067	1284	1751
1	3.49	-21.25	999	1105	1338	1815
1	3.49	-21.50	1112	1251	1507	2070
1	3.49	-21.75	1225	1366	1661	1845
1	3.49	-22.00	1414	1598	1735	1801
1	3.49	-22.25	1538	1522	1446	1787
1	3.49	-22.50	1210	1229	1396	1751
2	3.46	-21.00	1177	1125	1355	1860
2	3.46	-21.25	1067	1175	1421	1924
2	3.46	-21.50	1121	1232	1482	2017
2	3.46	-21.75	1163	1275	1535	2069
2	3.46	-22.00	1213	1325	1584	2098
3	3.33	-21.00	981	1080	1327	1872
3	3.33	-21.25	1172	1314	1658	2365
3	3.33	-21.50	1372	1504	1815	2503
3	3.33	-21.75	1403	1556	1900	1940
3	3.33	-22.00	1455	1613	1877	1790
4	3.32	-21.00	1579	1746	2125	2693
4	3.32	-21.25	1632	1813	2169	1670
4	3.32	-21.50	1674	1862	2080	1661
4	3.32	-21.75	1662	1771	1270	1670
4	3.32	-22.00	1355	1098	1296	1656
5	3.45	-21.75	835	920	1139	1587
5	3.45	-22.00	896	988	1212	1683
5	3.45	-22.25	954	1056	1293	1654
5	3.45	-22.50	1012	1113	1349	1644
5	3.45	-22.75	1013	1117	1292	1627
5	3.45	-23.00	1066	1117	1280	1614
6	3.49	-22.25**	1085	1224	1362	1598
6	3.49	-22.50	1272	1204	1304	1608
6	3.49	-22.75	1041	1115	1257	1589
7	3.55	-21.00	1251	1376	1667	2278
7	3.55	-21.25	1339	1488	1837	2591
7	3.55	-21.50	1559	1722	2064	2752
7	3.55	-21.75	1634	1781	2149	2035
7	3.55	-22.00	1676	1847	2111	1889
7	3.55	-22.25	1743	1843	1559	1869
7	3.55	-22.50	1393	1346	1476	1836

** Niet kiezen; ter info.

Werknummer: 61220523

Rc;net;d

<-----kN----->						
Sondering	Maaiveld	Paalpunt	Ø380*465	Ø406*495	Ø457*560	Ø559*680
<----m tov NAP-----><-----mm----->						

8	3.51	-21.00**	1136	1112	1149	1591
8	3.51	-21.25	1054	983	1197	1648
8	3.51	-21.50	920	1018	1239	1721
8	3.51	-21.75	964	1063	1299	1775
8	3.51	-22.00	997	1093	1318	1802
8	3.51	-22.25	1004	1107	1339	1816
8	3.51	-22.50	1017	1115	1327	1795

9	3.37	-21.00	1304	1451	1782	2477
9	3.37	-21.25	1389	1548	1884	2589
9	3.37	-21.50	1425	1591	1964	2749
9	3.37	-21.75	1577	1754	2170	2989
9	3.37	-22.00	1686	1879	2337	1892

10	3.52	-20.00	1207	1347	1654	2197
10	3.52	-20.25	1228	1362	1655	2241
10	3.52	-20.50	1245	1367	1681	2308
10	3.52	-20.75	1253	1393	1708	2379
10	3.52	-21.00	1282	1422	1741	2415

11	3.58	-20.50	1104	1222	1231	1364
11	3.58	-20.75	1161	1096	1024	1392
11	3.58	-21.00	823	883	1060	1440
11	3.58	-21.25	833	917	1099	1488
11	3.58	-21.50	866	953	1136	1528
11	3.58	-21.75	885	973	1157	1547
11	3.58	-22.00	912	999	1189	1589

12	3.55	-20.75**	1354	1511	1871	2132
12	3.55	-21.00	1525	1688	1648	2247
12	3.55	-21.25	1326	1421	1691	2325
12	3.55	-21.50	1315	1447	1755	2360
12	3.55	-21.75	1367	1504	1795	2441
12	3.55	-22.00	1407	1552	1860	2343

Rc;net;d = rekenwaarde netto draagkracht

APRSON version 1.0.0.36

PRJ : u:_aprprj\2022\61220523-2vibro.prj

XLS : u:_aprxls\2022\61220523-2.xlsx

GEF : u:_aprgef\2022\61220523*.gef

** Niet kiezen; ter info.