

Model gegevens

Model	: Vergund
Versie	: ISL3a 2025.1
PreSRM versie	: 2.505
Stof:	: PM10 - Fijnstof
Referentiejaar:	: 2025
Terreinhuidheid	: 0,198

Rekenpunt resultaten

Toetspunt	Omschrijving	X	Y	Conc. [$\mu\text{g}/\text{m}^3$]	AG [$\mu\text{g}/\text{m}^3$]	Bron [$\mu\text{g}/\text{m}^3$]	# > 24u limi...	# > AG limie...	Zeezout
1	Stokkelen 43W	151577,00	372229,00	15,4	15,0	0,4	6,0	6,0	1,0
2	Stokkelen 43 recreatieter	151518,00	372280,00	15,6	15,0	0,7	6,0	6,0	1,0
3	Lage Heide 8W	151184,00	372176,00	16,2	15,0	1,2	6,9	6,0	1,0
4	Lage Heide 8T	151160,00	372170,00	16,0	15,0	1,0	6,6	6,0	1,0
5	Lage Heide 6W	151015,00	372014,00	15,3	15,0	0,3	6,1	6,0	1,0
6	Lage Heide 6T	150995,00	372047,00	15,0	14,6	0,3	6,0	6,0	1,0
7	Lage Heide 1W	151097,00	372002,00	15,4	15,0	0,4	6,0	6,0	1,0
8	Lage Heide 1T	151097,00	371988,00	15,1	14,7	0,4	6,0	6,0	1,0
9	Eendbrand 6W	150634,00	372110,00	14,8	14,6	0,1	6,1	6,0	1,0
10	Eendbrand 6T	150658,00	372119,00	14,8	14,6	0,2	6,1	6,0	1,0
11	Voort 10W	150286,00	372414,00	14,7	14,6	0,1	6,0	6,0	1,0
12	Voort 10T	150287,00	372405,00	14,7	14,6	0,1	6,0	6,0	1,0
13	Stokkelen 31aW	151189,00	372754,00	15,6	15,0	0,6	6,1	6,0	1,0
14	Stokkelen 31aT	151163,00	372773,00	15,5	15,0	0,5	6,0	6,0	1,0
15	Stokkelen 33W	151224,00	372732,00	15,7	15,0	0,7	6,1	6,0	1,0
16	Stokkelen 33T	151213,00	372714,00	15,7	15,0	0,8	6,1	6,0	1,0
17	Stokkelen 35aW	151252,00	372683,00	15,9	15,0	1,0	6,1	6,0	1,0
18	Stokkelen 35aT	151233,00	372661,00	16,0	15,0	1,0	6,1	6,0	1,0
19	Stokkelen 35W	151267,00	372675,00	16,0	15,0	1,0	6,2	6,0	1,0
20	Stokkelen 35T	151256,00	372641,00	16,2	15,0	1,2	6,2	6,0	1,0
21	Stokkelen 37W	151382,00	372546,00	17,4	15,0	2,4	6,6	6,0	1,0
22	Stokkelen 37 Lagjenulmte	151296,00	372546,00	17,6	15,0	2,7	6,7	6,0	1,0
23	Stokkelen 52W	151458,00	372554,00	16,5	15,0	1,5	6,1	6,0	1,0
24	Stokkelen 52T	151468,00	372564,00	16,4	15,0	1,4	6,1	6,0	1,0
25	Lage Heide 12W	151530,00	372480,00	16,0	15,0	1,1	6,1	6,0	1,0
26	Lage Heide 12T	151518,00	372473,00	16,1	15,0	1,2	6,1	6,0	1,0
27	Lage Heide 13W	151566,00	372442,00	15,8	15,0	0,8	6,0	6,0	1,0
28	Lage Heide 13T	151573,00	372435,00	15,8	15,0	0,8	6,0	6,0	1,0

Agrarische bronnen

Agrarische bron - 1, Stal 1

X	151279,00	Y	372384,00	Hoogte	2,80	Emis PM10	0,01385718	Int.diam.	0,95
Snelheid	0,40	Gas temp	285,0	Geb.bron	T	Mid X	151305,00	Mid Y	372361,00
Lengte	90,5	Breedte	19,7	Hoogte	4,5	Gebouwhoek	131,0		

Agrarische bron - 2, Stal 2

X	151274,00	Y	372368,00	Hoogte	2,80	Emis PM10	0,01385718	Int.diam.	0,95
Snelheid	0,40	Gas temp	285,0	Geb.bron	T	Mid X	151286,00	Mid Y	372344,00
Lengte	90,5	Breedte	19,7	Hoogte	4,5	Gebouwhoek	131,0		

Agrarische bron - 3, Stal 3

X	151240,00	Y	372350,00	Hoogte	2,80	Emis PM10	0,01385718	Int.diam.	0,95
Snelheid	0,40	Gas temp	285,0	Geb.bron	T	Mid X	151267,00	Mid Y	372327,00
Lengte	90,5	Breedte	19,7	Hoogte	4,5	Gebouwhoek	131,0		

Agrarische bron - 4, Stal 4

X	151272,00	Y	372340,00	Hoogte	2,80	Emis PM10	0,01458650	Int.diam.	1,14
Snelheid	0,40	Gas temp	285,0	Geb.bron	T	Mid X	151248,00	Mid Y	372307,00
Lengte	95,5	Breedte	19,7	Hoogte	5,1	Gebouwhoek	131,0		

Model gegevens

Model	: Beeoogd
Versie	: ISL3a 2025.1
PreSRM versie	: 2.505
Stof:	: PM10 - Fijnstof
Referentiejaar:	: 2025
Terreinhuidheid	: 0,198

Rekenpunt resultaten

Toetspunt	Omschrijving	X	Y	Conc. (µg/m³)	AG (µg/m³)	Bron (µg/m³)	# > 24u limi...	# > AG limi...	Zeerout
1	Stokkelen 43W	151577,00	372229,00	15,3	15,0	0,3	6,0	6,0	1,0
2	Stokkelen 43 recreatieter	151518,00	372280,00	15,4	15,0	0,4	6,0	6,0	1,0
3	Lage Heide 8W	151184,00	372176,00	15,9	15,0	1,0	6,3	6,0	1,0
4	Lage Heide 8T	151160,00	372170,00	15,8	15,0	0,8	6,5	6,0	1,0
5	Lage Heide 6W	151015,00	372014,00	15,2	15,0	0,2	6,0	6,0	1,0
6	Lage Heide 6T	150995,00	372047,00	14,9	14,6	0,2	6,0	6,0	1,0
7	Lage Heide 1W	151097,00	372002,00	15,3	15,0	0,3	6,0	6,0	1,0
8	Lage Heide 1T	151097,00	371988,00	15,0	14,7	0,3	6,0	6,0	1,0
9	Eerdbrand 6W	150634,00	372110,00	14,8	14,6	0,1	6,0	6,0	1,0
10	Eerdbrand 6T	150658,00	372119,00	14,8	14,6	0,1	6,0	6,0	1,0
11	Voort 10W	150286,00	372414,00	14,7	14,6	0,0	6,0	6,0	1,0
12	Voort 10T	150287,00	372405,00	14,7	14,6	0,0	6,0	6,0	1,0
13	Stokkelen 31aW	151189,00	372754,00	15,4	15,0	0,4	6,0	6,0	1,0
14	Stokkelen 31aT	151163,00	372773,00	15,3	15,0	0,4	6,0	6,0	1,0
15	Stokkelen 33W	151224,00	372732,00	15,4	15,0	0,5	6,1	6,0	1,0
16	Stokkelen 33T	151213,00	372714,00	15,5	15,0	0,5	6,1	6,0	1,0
17	Stokkelen 35aW	151252,00	372683,00	15,6	15,0	0,6	6,1	6,0	1,0
18	Stokkelen 35aT	151233,00	372661,00	15,6	15,0	0,7	6,1	6,0	1,0
19	Stokkelen 35W	151267,00	372675,00	15,6	15,0	0,7	6,1	6,0	1,0
20	Stokkelen 35T	151256,00	372641,00	15,8	15,0	0,8	6,1	6,0	1,0
21	Stokkelen 37W	151382,00	372546,00	16,4	15,0	1,5	6,2	6,0	1,0
22	Stokkelen 37 Logieruimte	151296,00	372546,00	16,6	15,0	1,6	6,2	6,0	1,0
23	Stokkelen 52W	151458,00	372554,00	15,9	15,0	0,9	6,0	6,0	1,0
24	Stokkelen 52T	151468,00	372564,00	15,8	15,0	0,9	6,0	6,0	1,0
25	Lage Heide 12W	151530,00	372480,00	15,6	15,0	0,7	6,0	6,0	1,0
26	Lage Heide 12T	151518,00	372473,00	15,7	15,0	0,7	6,0	6,0	1,0
27	Lage Heide 13W	151566,00	372442,00	15,5	15,0	0,5	6,0	6,0	1,0
28	Lage Heide 13T	151573,00	372435,00	15,5	15,0	0,5	6,0	6,0	1,0

Agrarische bronnen

Agrarische bron - 1, Stal 1

X	151286,00	Y	372377,00	Hoogte	2,80	Emis PM10	0,00632764	Int.diam.	0,87
Snelheid	0,40	Gas temp	285,0	Geb.bron	T	Mid X	151305,00	Mid Y	372361,00
Lengte	90,5	Breedte	19,7	Hoogte	4,6	Gebouwhoek	131,0		

Agrarische bron - 2, Stal 2

X	151276,00	Y	372359,00	Hoogte	2,80	Emis PM10	0,00898589	Int.diam.	0,87
Snelheid	0,40	Gas temp	285,0	Geb.bron	T	Mid X	151271,00	Mid Y	372341,00
Lengte	96,5	Breedte	44,7	Hoogte	4,6	Gebouwhoek	131,0		

Agrarische bron - 3, Stal 3

X	151244,00	Y	372348,00	Hoogte	3,10	Emis PM10	0,00898589	Int.diam.	0,87
Snelheid	0,40	Gas temp	285,0	Geb.bron	T	Mid X	151271,00	Mid Y	372341,00
Lengte	96,5	Breedte	44,7	Hoogte	4,6	Gebouwhoek	131,0		

Agrarische bron - 4, Stal 4

X	151232,00	Y	372326,00	Hoogte	2,80	Emis PM10	0,01143655	Int.diam.	0,87
Snelheid	0,40	Gas temp	285,0	Geb.bron	T	Mid X	151233,00	Mid Y	372299,00
Lengte	95,7	Breedte	50,7	Hoogte	5,3	Gebouwhoek	131,0		

Agrarische bron - 5, Stal 6

X	151193,00	Y	372321,00	Hoogte	7,30	Emis PM10	0,01063497	Int.diam.	2,37
Snelheid	4,00	Gas temp	285,0	Geb.bron	T	Mid X	151233,00	Mid Y	372299,00
Lengte	95,7	Breedte	50,7	Hoogte	5,3	Gebouwhoek	131,0		