

BESTEMMINGSPLAN

Herinrichting uiterwaarden Dieden - Demen

Bijlage 15 bij toelichting
PFAS





Bodemonderzoek en actualisatie waterbodemkwaliteitskaart PFAS-verbindingen

Maasuitewaarden Demen-Dieden

Opdrachtgever: K3Delta

Lievense Milieu B.V.

Documentcode:
SOB010398-A.RAP001

KvK
30152124

Telefoon
088 - 9102000

Versie
1.0

Adres
Ringwade 41
3439 LM Nieuwegein

Internet
Lievense.com

Datum
18 december 2019

Colofon

Opdrachtgever

K3Delta
Postbus 200
6660 AE ELST

Contactpersoon opdrachtgever

De heer J. Hijlkema

Contactpersonen Lieveense

Dhr. R.N. van Rijnsoever
Mevr. M.L. Springer

Autorisatie

Documentnummer	Versie	Status
SOB010398-A.RAP001	1.0	Definitief

Opgesteld door	Functie	Datum	Paraaf
Dhr. R.N. van Rijnsoever	Senior adviseur en projecteider SIKB BRL 2003	18-12-2019	
Geverifieerd door	Functie	Datum	Paraaf
Dhr. J.S Spronk	Senior adviseur	18-12-2019	
Akkoord projectleider	Functie	Datum	Paraaf
Dhr. R.N. van Rijnsoever	Senior adviseur en projecteider SIKB BRL 2003	18-12-2019	

Inhoudsopgave

1	Inleiding	1
2	Achtergronden	2
2.1	Locatie-gegevens	2
2.2	Reeds uitgevoerde onderzoeken	3
2.3	PFAS	5
2.4	Onderzoeksopzet	6
3	Uitgevoerd onderzoek	7
3.1	Onderzoeksopzet	7
3.2	Veldonderzoek en laboratoriumonderzoek	7
4	Resultaten	11
4.1	Veldonderzoek	11
4.2	Laboratoriumonderzoek	11
4.2.1	Toepassingsnormen PFAS-verbindingen	11
4.2.2	Analyseresultaten PFAS-verbindingen	13
5	Actualisatie waterbodempkwaliteitskaart voor PFAS-verbindingen	16
5.1	Doelstelling actualiseren waterbodempkwaliteitskaart	16
5.2	Actualisatie waterbodempkwaliteitskaart voor PFAS-verbindingen	16
5.2.1	Actualisatie waterbodempkwaliteitskaart	16
5.2.2	Stap 7: Vaststellen en karakteriseren bodempkwaliteitszones	18
5.2.3	Stap 8: Waterbodempkwaliteitskaart	19
5.2.3.1	Kaart met indeling in gebieden	19
5.2.3.2	Ontgravings- en toepassingskaart	19
5.3	Voorstel beleid bij het voorgenomen grondverzet (waterbodem)	20
5.4	Toekomstige bijstelling van de landelijke (toepassings)normen voor PFAS-houdende waterbodem	21

Overzicht bijlagen

Bijlage 1	Regionale ligging van de onderzoekslocatie
Bijlage 2	Situatietekening onderzoekslocatie
Bijlage 3	Profielbeschrijvingen en veldverslag
Bijlage 4	Analysecertificaten PFAS
Bijlage 5	Begrippenlijst
Bijlage 6	Statistische parameters waterbodempkwaliteitszones
Kaartbijlage 7	Beheergebied en uitgesloten locaties
Kaartbijlage 8	Ontgravings- en toepassingskaart toplaag (0-0,5 m-wb)
Kaartbijlage 9	Ontgravings- en toepassingskaart tussenlaag (0,5-1,0 m-wb)
Kaartbijlage 10	Ontgravings- en toepassingskaart ondergrond (1,0-7,0 m-wb)

1 Inleiding

In opdracht van K3Delta heeft Lieveense Milieu B.V. een PFAS-onderzoek uitgevoerd ter plaatse van de Maasuitewaarden Demen-Dieden. Ook is de voor dit gebied eerder vastgestelde waterbodempkwaliteitskaart¹ voor PFAS-verbindingen geactualiseerd. De regionale ligging van de locatie is weergegeven in bijlage 1.

Onder de noemer 'Meer Maas' heeft Vereniging Natuurmonumenten het initiatief genomen om in de Maasuitewaarden nieuwe riviernatuur te realiseren. Samen met partner Rijkswaterstaat en de baksteenindustrie heeft het initiatief vorm gekregen. Doel is het realiseren van meer riviernatuur door kleiwinning dat leidt tot toename van de hoogwaterveiligheid en de ruimtelijke kwaliteit. Op diverse plaatsen langs de Maas worden plannen uitgewerkt, zoals voor de Maasuitewaarden tussen Dieden, Demen en Neerlangel (hierna Demen-Dieden). K3Delta Gebiedsontwikkeling b.v. trekt in opdracht van Natuurmonumenten en Van de Wetering de gehele uitwerking en (al dan niet) gedeeltelijke uitvoering van het voorgenomen plan.

Ten behoeve van het voorgenomen grondverzet (waterbodem) is begin 2019 een waterbodempkwaliteitskaart opgesteld. Om deze kaart te gebruiken voor het uit te voeren grondverzet (waterbodem) in de uiterwaard zijn aanvullende gegevens voor PFAS noodzakelijk. Deze rapportage beschrijft de uitgevoerde werkzaamheden en analyseresultaten ter aanvulling van de waterbodempkwaliteitskaart.

In hoofdstuk 2 worden de achtergronden van de onderzoekslocatie weergegeven, evenals de resultaten van het eerder uitgevoerde onderzoeken en de daaruit voortvloeiende onderzoeksstrategie. In hoofdstuk 3 worden de uitgevoerde werkzaamheden, de certificering en de kwaliteitsborging besproken. Vervolgens worden in hoofdstuk 4 de onderzoeksresultaten weergegeven. In hoofdstuk 5 wordt de actualisatie van de eerder opgestelde waterbodempkwaliteitskaart besproken. Hoofdstuk 5 kan gebruikt worden ter vervanging van de eerder opgestelde waterbodempkwaliteitskaart en dient door het bevoegde gezag (RWS) bestuurlijk te worden vastgesteld voordat grondverzet (waterbodem) met de dit document als bewijsmiddel voor de kwaliteit van de waterbodem kan worden uitgevoerd.

Voor een uitleg van de in dit rapport gebruikte begrippen wordt verwezen naar bijlage 5.

¹ Rapportage Waterbodempkwaliteitskaart Maasuitewaarden Demen-Dieden (LieveenseCSO; documentcode 17M7013.Wbkk; 17 januari 2019; definitief).

2 Achtergronden

De locatiegegevens en achtergronden zijn reeds beschreven in rapportage 17M7013.RAP.WBO (15 februari 2019 definitief v2) en worden voor zover noodzakelijk hieronder herhaald.

Voor het volledige vooronderzoek wordt naar bovengenoemde rapportage verwezen

2.1 Locatie-gegevens

De onderzoekslocatie betreft de Maasuitwaarden en ligt tussen de Maasdijk en de Maas en strekt zich van west naar oost uit van Dieden tot Neerlangel. Het gehele plangebied betreft uiterwaard gelegen in het winterbed van de Maas: dit wordt beschouwd als waterbodembodem. Het gebied heeft een totale oppervlakte van 110 hectare, het te vergraven gebied heeft een oppervlakte van circa 80 hectare. De Maas zelf behoort niet tot de onderzoekslocatie (zie figuur 1).



Figuur 1: onderzoeksgebied.

Het gebied is in beheer bij het Waterschap Aa en Maas, de oeverzone is eigendom van Rijkswaterstaat. De uiterwaarden zijn in gebruik als agrarisch gebied (bouwland en grasland). De oevers langs de Maas zijn voorzien van stortsteen. Buitendijks zijn geen watergangen of waterstaatkundige werken op de Legger van Aa en Maas opgenomen. Binnendijks liggen de woonkernen van Demen en Dieden.

In het oostelijk deel van het gebied ligt een weg naar de veerpont (Demense Veerstraat, asfalt). Deze weg is geen onderdeel van de onderzoekslocatie vanwege een mogelijk afwijkende kwaliteit. Ook de dijk zelf behoort niet tot het onderzoeksgebied.

Het gebied is niet onderhevig aan sterke sedimentatie of erosie door overstromingen: de uiterwaard overstroomt eens in de 10 jaar (bron: startdocument MeerMaas project Planontwikkeling Demen-Dieden, LievenseCSO, kenmerk 17M7013.RAP001.BW.LD, september 2017).

In bijlage 2 is een situatietekening van de onderzoekslocatie opgenomen.

2.2 Reeds uitgevoerde onderzoeken

Op de locatie hebben in het verleden onder andere de volgende waterbodemonderzoeken plaatsgevonden:

1. Waterbodemonderzoek Maasuitewaarden Demen-Dieden (LievenseCSO; documentcode 17M7013.RAP.WBO; 15 februari 2019 definitief v2).
2. Rapportage Waterbodemkwaliteitskaart Maasuitewaarden Demen-Dieden (LievenseCSO; documentcode 17M7013.Wbkk; 15 februari 2019 definitief).

De belangrijkste bevindingen uit het waterbodemonderzoek uit 2019 zijn hieronder weergegeven:

- Ter plaatse van de onderzoekslocatie bestaat de waterbodem uit een rooflaag (klei) met in de ondergrond klei- en zandlagen en enkele grindlagen.
- Ter plaatse van de onderzoekslocatie varieert de kwaliteit van de waterbodem tussen Altijd toepasbaar en Nooit toepasbaar. De bovengrond is in het algemeen meer verontreinigd dan de ondergrondlagen. Er is geen duidelijk kwaliteitsverschil tussen klei- en zandlagen.
- In enkele monsters worden de interventiewaarden overschreden. Er zijn echter geen verontreinigingsbronnen of zintuiglijke afwijkingen aangetroffen.

In 2019 is een waterbodemkwaliteitskaart opgesteld op basis van de bodemopbouw, geomorfologie en vastgestelde waterbodemkwaliteit. In de waterbodemkwaliteitskaart worden de volgende waterbodemkwaliteitszones onderscheiden:

- Toplaag Oeverzone (0 - 0,5 m-wb);
- Toplaag Riviervlakte (0 - 0,5 m-wb);
- Ondergrond zand (0,5 - 7 m-wb);
- Ondergrond klei (0,5 - 7 m-wb).

Alle zones zijn vastgesteld voor de stoffen uit het C2-pakket. In tabel 2.1 is per waterbodemkwaliteitszone een totaaloverzicht gegeven van de te verwachte ontgravingsklasse en toepassingseis. De toe te passen waterbodem dient minimaal dezelfde kwaliteit te hebben als de ontvangende waterbodem. Toepassen van waterbodem die schoner is, is ook toegestaan.

Tabel 2.1 verwachte ontgravingsklasse en toepassingseis per waterbodempkwaliteitszone

Bodemkwaliteitszone	Verwachte ontgravingsklasse	Toepassingseis
Rivierlakte (0 - 0,5 m-wb)	Klasse B	Klasse B, Klasse A of Altijd toepasbaar
Oevergebied (0 - 0,5 m-wb)	Klasse B	Klasse B , Klasse A of Altijd toepasbaar
Ondergrond klei (0,5 - 7,0 m-wb)	Klasse A	Klasse A of Altijd toepasbaar
Ondergrond zand (0,5 - 7,0 m-wb)	Altijd toepasbaar	Altijd toepasbaar

Hergebruik rooﬂaag

De kleiige rooﬂaag, waterbodempkwaliteitsklasse B, kan zonder aanvullende onderzoeken worden hergebruikt binnen het projectgebied. Deze toplaag zal, ook na realisatie van de natuurontwikkeling, als rooﬂaag worden gebruikt. Het bevoegd gezag Bbk (RWS ZN) zal moeten beoordelen of dergelijk hergebruik past binnen het kader van de ‘op-en-nabij regeling’ uit het Besluit bodempkwaliteit. Wanneer grondverzet voldoet aan de volgende voorwaarden is wellicht geen melding Bbk noodzakelijk: hergebruik zonder bewerking, op of nabij dezelfde plaats en onder dezelfde condities.

Afvoer van keramische klei

Klei geschikt voor de keramische industrie wordt afgevoerd naar een industriële verwerker. Er is geen sprake van grondverzet in het kader van het Besluit bodempkwaliteit. De waterbodempkwaliteitskaart wordt gebruikt om te voldoen aan de algemene zorgplicht (Wbb en Wm) en om de kwaliteit aan te verwerker te kunnen tonen. Daarnaast kan de waterbodempkwaliteitskaart gebruikt worden bij de transportbonnen wanneer de klei wordt vervoerd.

Hergebruik van klei

De klei binnen het projectgebied kan ook binnen het gebied worden gebruikt. Dit kan ook de buitendijkse zijde van de dijkbekleding zijn (zolang die onderdeel is van de waterbodem). De kwaliteit van de klei is klasse A. Dat betekent dat deze klei binnen het gebied van de waterbodempkwaliteitskaart kan worden toegepast danwel hergebruikt op andere kleilagen (ook op de rooﬂaag).

Hergebruik van zand

Binnen de natuurontwikkeling komt niet veel zand vrij. Overtollig ontgraven zand wordt binnen het gebied hergebruikt. Het zand is schoon en kan overal binnen het gebied worden gebruikt of toegepast. Het is aan het bevoegd gezag om te beoordelen of er sprake is van hergebruik (geen melding Bbk) of toepassing (wel melding Bbk). Het zand kan ook worden afgevoerd. Voor de toepassing van zand op andere locaties zal de ontvangende partij moeten beoordelen of zij de waterbodempkwaliteitskaart als bewijsmiddel accepteren.

Verdachte locaties en uitzonderingen

De waterbodempkwaliteitskaart is niet geldig voor ophogingen, dempingen of verhardingen. Grondverzet kan daarom niet worden gemeld met deze waterbodempkwaliteitskaart als milieuhygiënische verklaring.

Tijdens het verzamelen van data (veld- en analyseresultaten) zijn in enkele monsters sterk verhoogde gehalten aangetroffen. De analyse van de gegevens voor de waterbodempkwaliteitskaart toont echter aan dat er **geen puntverontreinigingen** in het gebied zijn aangetoond. Verder onderzoek naar deze hogere gehalten is dan ook niet noodzakelijk.

2.3 PFAS

Poly- en perfluoralkylstoffen (PFAS) zijn chemische stoffen die van nature niet in het milieu voorkomen. Deze stofgroep bestaat uit ruim 6000 stoffen. Hiertoe behoren onder meer de stoffen perfluorooctaanzuur (PFOA), perfluorooctaansulfonaat (PFOS) en HFPO-DA (GenX). PFAS zijn stoffen die door mensen zijn gemaakt vanwege hun specifieke eigenschappen, zoals brandwerendheid en vuil- en waterafstotendheid. Zij worden al decennia gebruikt in industriële en andere processen en in vele producten. Ze worden toegepast in allerlei alledaagse toepassingen, zoals verf, blusschuim, pannen, kleding en cosmetica. Kenmerkend voor deze stoffen is dat ze persistent, mobiel en nauwelijks biologisch afbreekbaar zijn. Van sommige PFAS is al aangetoond dat ze toxisch zijn. De stoffen PFOS en PFOA behoren tot de zogenaamde Zeer Zorgwekkende Stoffen (ZZS). PFAS kunnen door de aanwezigheid van een puntbron of door luchtdepositie in de bodem terechtgekomen zijn.

Beleid, risicogrenzen en grondverzet (eventueel waterbodemp)

Op 8 juli 2019 is een tijdelijk handelingskader in werking getreden voor hergebruik van PFAS-houdende grond en baggerspecie². De initiatiefnemers van grondverzet (eventueel waterbodemp) moeten, tot duidelijk is of er onbelaste gebieden zijn in Nederland, in het kader van de zorgplicht het gehalte aan PFAS meten in te verzetten grond en waterbodemp, die uit land- en waterbodemp wordt ontgraven. Tot dat een (gemeentelijke) achtergrondwaarde is bepaald, mag geen PFAS-houdende grond en baggerspecie worden toegepast. Op 29 november 2019 is het tijdelijk handelingskader geactualiseerd. Met de kennis die tot deze datum is opgedaan, zijn met de actualisatie van het tijdelijk handelingskader enkele voorlopige toepassingsnormen voor PFAS-houdende grond en baggerspecie boven de bepalingsgrens vastgesteld.

Rijkswaterstaat Bodem+ heeft op 12 juli 2019 een advieslijst met PFAS-verbindingen gepubliceerd die moet worden aangehouden als onderzoek naar PFAS wordt gedaan. Er hoeft alleen op GenX onderzocht te worden als sprake is van een directe bron of lozing van GenX. Ter plaatse van onderhavige locatie zijn voor zover bekend geen bekende bronnen van GenX aanwezig.

Om de afvoer van waterbodemp naar een verwerker mogelijk te maken, dient de aanwezigheid van PFAS in de waterbodemp nagegaan te worden. Hierbij dient te worden opgemerkt dat op de locatie voor zover geen specifieke bronnen voor PFAS aanwezig zijn. De aanwezigheid van PFAS in de waterbodemp door atmosferische depositie kan echter niet worden uitgesloten.

² Tijdelijke handelingskader voor hergebruik van PFAS-houdende grond en baggerspecie, kenmerk IENW/BSK-2019/131399, 8 juli 2019.

2.4 Onderzoeksopzet

In het algemeen stelt de Richtlijn bodemkwaliteitskaarten³ de volgende minimale eisen aan het aantal en de spreiding van analysegegevens per deelgebied:

- Per deelgebied zijn voor alle stoffen ten minste 20 meetgegevens beschikbaar.
- De analysegegevens liggen voldoende verspreid over het deelgebied:
 - o Voor aaneengesloten deelgebieden bij een systematische indeling in 20 vakken zijn in tenminste 10 vakken één of meer analysegegevens beschikbaar.
 - o Voor elk niet-aaneengesloten deel van een deelgebied zijn ten minste 3 meetgegevens beschikbaar.

Voor de PFAS-verbindingen wordt aangesloten bij de laatste informatie hierover vanuit Bodem+ (zie daarvoor de veelgestelde vragen over het Besluit bodemkwaliteit, Grond en baggerspecie – PFAS). Hieruit blijkt dat gebruik gemaakt kan worden van de systematiek die in de Richtlijn bodemkwaliteitskaarten is uitgewerkt voor kobalt, molybdeen en PCB. Met deze systematiek kan onder voorwaarden volstaan worden met minimaal 30 meetgegevens per bodemlaag in het gehele beheergebied in plaats van het minimale aantal meetgegevens dat normaal gesproken per bodemkwaliteitszone (20) en per niet-aaneengesloten bodemkwaliteitszone geldt.

Analyseresultaten van PFAS-verbindingen worden alleen gecorrigeerd voor standaardbodem als het organisch stofgehalte hoger is dan 10%. Voor het bodemonderzoek naar PFAS-verbindingen worden de bodemlagen (1) vanaf de bovenzijde van de waterbodem tot 0,5 meter diepte en (2) vanaf 0,5 meter tot 1,0 meter diepte onderscheiden. De bodemlaag dieper dan 1,0 meter wordt vooralsnog als onverdacht voor PFAS beschouwd.

Opgemerkt dient te worden dat de onderzoeksopzet voorafgaand aan de werkzaamheden is voorgelegd aan en op 12 september 2019 goedgekeurd door Rijkswaterstaat (bevoegd gezag waterbodem).

In de navolgende hoofdstukken worden de uitgevoerde werkzaamheden en de onderzoeksresultaten besproken.

³ Richtlijn bodemkwaliteitskaarten, Ministerie van VROM, Ministerie van Verkeer en Waterstaat, 3 september 2007 en latere wijzigingen.

3 Uitgevoerd onderzoek

3.1 Onderzoeksofzet

Op basis van de vastgestelde onderzoeksstrategie is het volgende onderzoeksprogramma uitgevoerd:

Tabel 3.1 Onderzoeksprogramma

Deelgebied	Boring	Analyses
Oeverzone	20x	40x PFAS (zonder GenX ¹) en organisch stofgehalte (20x 0,0-0,5 m-wb; 20x 0,5-1,0 m-wb)
Rivierzone	20x	40x PFAS (zonder GenX ¹) en organisch stofgehalte (20x 0,0-0,5 m-wb; 20x 0,5-1,0 m-wb)
Totaal	40x	80x PFAS (zonder GenX¹) en organisch stofgehalte

Toelichting tabel:

m-wb: meter beneden bovenzijde waterbodem

PFAS: Poly- en PerFluor Alkylstoffen

¹: Rijkswaterstaat beschouwt het plangebied als niet-verdacht voor GenX

3.2 Veldonderzoek en laboratoriumonderzoek

Lievense Milieu B.V. te Nieuwegein is door Normec Certification gecertificeerd voor de ISO 9001- en 14001-normen, VCA** en in het kader van de Regeling Kwalibo is Lievense Milieu B.V. te Nieuwegein gecertificeerd voor de BRL SIKB 1000, 2000 en 6000. Ten slotte is Lievense Milieu B.V. te Nieuwegein door Normec Certification ook gecertificeerd voor de CO₂-prestatieladder trede 5 en voor het uitvoeren van asbestinventarisaties conform de Arbeidsomstandighedenregeling bijlage XIIIa.

Lievense Milieu B.V. heeft het veldwerk voor dit project uitbesteed aan Poelsema Veldwerkbureau. Poelsema Veldwerkbureau is door Normec Certification gecertificeerd voor de ISO 9001-norm, VCA* en in het kader van de Regeling Kwalibo voor de BRL SIKB 1000, 2000, 2100 en 6000.

De veldwerkzaamheden zijn uitgevoerd op 28 en 29 oktober 2019 door Poelsema Veldwerkbureau onder het BRL SIKB 2000-certificaat (protocol 2003) door de erkende veldwerker J. ten Klooster. Alle veld- en analysewerkzaamheden ten behoeve van PFAS zijn tevens uitgevoerd conform het 'Handelingskader Poly- en PerFluor Alkyl Stoffen (PFAS)' ⁴. Hierbij wordt voornamelijk aandacht besteed aan het voorkomen van contaminatie tijdens bemonstering.

⁴ Bemonsteringsprotocol PFAS-verbindingen in grond- en grondwater, opgesteld door het expertisecentrum PFAS, juli 2019.

Aangezien de onderzoekslocatie geen eigendom is van Lievense Milieu B.V., Poelsema Veldwerkbureau of daaraan gelieerde ondernemingen, is voldaan aan de eisen van onafhankelijkheid uit de BRL SIKB 2000.

Tijdens de uitvoering van het veldwerk zijn geen kritieke afwijkingen opgetreden van de protocollen beschreven in de BRL SIKB 2000.

De verrichte meetpunten zijn ingemeten met behulp van GPS en op de tekening van bijlage 2 weergegeven.

De chemische analyses voor PFAS zijn uitgevoerd door het IEC 17025-geaccrediteerde en AS3000-erkende laboratorium SYNLAB Analytics & Services B.V. te Rotterdam.

De monsters in dit onderzoek zijn zover van toepassing geanalyseerd conform de AS3000 (zie de analysecertificaten in de bijlage).

De selectie van de bodemonsters voor analyse heeft plaatsgevonden op basis van zintuiglijke waarnemingen en herkomst. De geanalyseerde monsters en de samenstelling daarvan zijn weergegeven in tabel 3.2.

Tabel 3.2 Analyseprogramma

Analyse-Monster	Traject (m-wb)	Deelmonsters	Bodem-soort	Zintuiglijke waarnemingen	Analysepakket
OZ-01-1	0,00 - 0,50	OZ-01 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-01-2	0,50 - 1,00	OZ-01 (0,50 - 1,00)	Zand	-	PFAS (excl. GenX) + org. stof
OZ-02-1	0,00 - 0,50	OZ-02 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-02-2	0,50 - 0,90	OZ-02 (0,50 - 0,90)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-03-1	0,00 - 0,50	OZ-03 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-03-2	0,50 - 1,00	OZ-03 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-04-1	0,00 - 0,40	OZ-04 (0,00 - 0,40)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-04-2	0,40 - 0,90	OZ-04 (0,40 - 0,90)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-05-1	0,00 - 0,40	OZ-05 (0,00 - 0,40)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-05-2	0,40 - 0,80	OZ-05 (0,40 - 0,80)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-06-1	0,00 - 0,50	OZ-06 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-06-2	0,50 - 1,00	OZ-06 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-07-1	0,00 - 0,50	OZ-07 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-07-2	0,50 - 0,95	OZ-07 (0,50 - 0,95)	Zand	-	PFAS (excl. GenX) + org. stof
OZ-08-1	0,00 - 0,50	OZ-08 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-08-3	0,65 - 1,00	OZ-08 (0,65 - 1,00)	Zand	-	PFAS (excl. GenX) + org. stof
OZ-09-1	0,00 - 0,50	OZ-09 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-09-2	0,50 - 0,90	OZ-09 (0,50 - 0,90)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-10-1	0,00 - 0,50	OZ-10 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-10-2	0,50 - 0,90	OZ-10 (0,50 - 0,90)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-11-1	0,00 - 0,30	OZ-11 (0,00 - 0,30)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-11-3	0,80 - 1,15	OZ-11 (0,80 - 1,15)	Zand	-	PFAS (excl. GenX) + org. stof

Analyse-Monster	Traject (m-wb)	Deelmonsters	Bodem-soort	Zintuiglijke waarnemingen	Analysepakket
OZ-12-1	0,00 - 0,40	OZ-12 (0,00 - 0,40)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-12-3	0,85 - 1,00	OZ-12 (0,85 - 1,00)	Zand	-	PFAS (excl. GenX) + org. stof
OZ-13-1	0,00 - 0,50	OZ-13 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-13-2	0,50 - 1,00	OZ-13 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-14-1	0,00 - 0,50	OZ-14 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-14-2	0,50 - 1,00	OZ-14 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-15-1	0,00 - 0,50	OZ-15 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-15-2	0,50 - 1,00	OZ-15 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-16-1	0,00 - 0,50	OZ-16 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-16-2	0,50 - 1,00	OZ-16 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-17-1	0,00 - 0,50	OZ-17 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-17-2	0,50 - 1,00	OZ-17 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-18-1	0,00 - 0,50	OZ-18 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-18-2	0,50 - 1,00	OZ-18 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-19-1	0,00 - 0,50	OZ-19 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-19-2	0,50 - 1,00	OZ-19 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-20-1	0,00 - 0,50	OZ-20 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
OZ-20-2	0,50 - 1,00	OZ-20 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
RV-01-1	0,00 - 0,50	RV-01 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
RV-01-2	0,50 - 0,90	RV-01 (0,50 - 0,90)	Klei	-	PFAS (excl. GenX) + org. stof
RV-02-1	0,00 - 0,50	RV-02 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
RV-02-2	0,50 - 1,00	RV-02 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
RV-03-1	0,00 - 0,50	RV-03 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
RV-03-2	0,50 - 1,00	RV-03 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
RV-04-1	0,00 - 0,50	RV-04 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
RV-04-2	0,50 - 1,00	RV-04 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
RV-05-1	0,00 - 0,50	RV-05 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
RV-05-2	0,50 - 1,00	RV-05 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
RV-06-1	0,00 - 0,50	RV-06 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
RV-06-2	0,50 - 1,00	RV-06 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
RV-07-1	0,00 - 0,50	RV-07 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
RV-07-2	0,50 - 1,00	RV-07 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
RV-08-1	0,00 - 0,40	RV-08 (0,00 - 0,40)	Klei	-	PFAS (excl. GenX) + org. stof
RV-08-2	0,40 - 0,90	RV-08 (0,40 - 0,90)	Klei	-	PFAS (excl. GenX) + org. stof
RV-09-1	0,00 - 0,45	RV-09 (0,00 - 0,45)	Klei	-	PFAS (excl. GenX) + org. stof
RV-09-2	0,45 - 0,95	RV-09 (0,45 - 0,95)	Klei	-	PFAS (excl. GenX) + org. stof
RV-10-1	0,00 - 0,30	RV-10 (0,00 - 0,30)	Klei	-	PFAS (excl. GenX) + org. stof
RV-10-3	0,50 - 1,00	RV-10 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
RV-11-1	0,00 - 0,30	RV-11 (0,00 - 0,30)	Klei	-	PFAS (excl. GenX) + org. stof
RV-11-3	0,50 - 1,00	RV-11 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
RV-12-1	0,00 - 0,50	RV-12 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
RV-12-2	0,50 - 1,00	RV-12 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof

Analyse-Monster	Traject (m-wb)	Deelmonsters	Bodem-soort	Zintuiglijke waarnemingen	Analysepakket
RV-13-1	0,00 - 0,50	RV-13 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
RV-13-2	0,50 - 1,00	RV-13 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
RV-14-1	0,00 - 0,50	RV-14 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
RV-14-2	0,50 - 1,00	RV-14 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
RV-15-1	0,00 - 0,50	RV-15 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
RV-15-2	0,50 - 1,00	RV-15 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
RV-16-1	0,00 - 0,20	RV-16 (0,00 - 0,20)	Klei	-	PFAS (excl. GenX) + org. stof
RV-16-3	0,50 - 1,00	RV-16 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
RV-17-1	0,00 - 0,50	RV-17 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
RV-17-2	0,50 - 1,00	RV-17 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
RV-18-1	0,00 - 0,50	RV-18 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
RV-18-2	0,50 - 1,00	RV-18 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
RV-19-1	0,00 - 0,50	RV-19 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
RV-19-2	0,50 - 1,00	RV-19 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof
RV-20-1	0,00 - 0,50	RV-20 (0,00 - 0,50)	Klei	-	PFAS (excl. GenX) + org. stof
RV-20-2	0,50 - 1,00	RV-20 (0,50 - 1,00)	Klei	-	PFAS (excl. GenX) + org. stof

- = zintuiglijk geen afwijkingen

4 Resultaten

4.1 Veldonderzoek

Het opgeboorde en opgegraven materiaal is beoordeeld op kleur, textuur, bijmenging en eventuele bijzonderheden. De profielbeschrijvingen en het veldverslag zijn opgenomen in bijlage 3.

In het opgeboorde materiaal zijn geen bodemvreemde materialen aangetroffen. Ook zijn geen asbestverdachte materialen aangetroffen.

4.2 Laboratoriumonderzoek

4.2.1 Toepassingsnormen PFAS-verbindingen

In het geactualiseerde tijdelijk handelingskader van 29 november 2019 worden voor toepassen van grond en baggerspecie de volgende categorieën en landelijke toepassingsnormen onderscheiden:

Tabel 4.1 Landelijke toepassingsnormen voor het toepassen van grond en baggerspecie (in µg/kg d.s.)

Categorie	Toepassingssituatie		Toepassingsnorm (in µg/kg ds) ^{(4) (5)}
Op landbodem			
4.1	Grond en baggerspecie toepassen boven grondwatervniveau ⁽¹⁾		
	Bodemkwaliteitsklasse	Bodemfunctie	
	Wonen of industrie	Wonen of industrie	PFOS = 3 PFOA = 7 GenX = 3 andere PFAS = 3
	Landbouw/natuur	Wonen of industrie	PFAS = 0,8 PFOS = 0,9
	Landbouw/natuur, wonen of industrie	Landbouw/natuur	PFAS = 0,8 PFOS = 0,9
4.2	Baggerspecie toepassen boven grondwatervniveau ⁽¹⁾ , als bedoeld in artikel 35, onder f, Bbk (verspreiden van baggerspecie op aangrenzend perceel of waterbodem)		PFOS = 3 PFOA = 7 GenX = 3 andere PFAS = 3
4.3	Grond en baggerspecie grootschalig toepassen boven grondwatervniveau ⁽¹⁾		PFOS = 3 PFOA = 7 GenX = 3 andere PFAS = 3
4.4	Grond en baggerspecie toepassen in grondwaterbeschermingsgebieden		Bepalingsgrens = 0,1

Categorie	Toepassingssituatie	Toepassingsnorm (in µg/kg ds) ^{(4) (5)}
4.5	Grond en baggerspecie toepassen onder grondwaterniveau ⁽²⁾ , met inbegrip van grootschalig toepassen	PFAS = 0,8 PFOS = 0,9
In oppervlaktewater		
4.6	Grond toepassen	Bepalingsgrens = 0,1
4.7	Baggerspecie toepassen in hetzelfde oppervlaktewaterlichaam of aansluitende (sedimentdelende) stroomafwaarts gelegen oppervlaktewaterlichamen als bedoeld in artikel 35, onder g, BBK (verspreiden van baggerspecie in zoet of zout oppervlaktewater)	Toepasbaar, wel meten en toetsen op uitschieters
4.8.1	Baggerspecie toepassen in hetzelfde oppervlaktewaterlichaam in ophogingen in waterbouwkundige constructies, uitgezonderd de diepe plas, als bedoeld in artikel 35, onder d, Bbk	Toepasbaar, wel meten en toetsen op uitschieters.
4.8.2	Baggerspecie toepassen in een ander oppervlaktewaterlichaam in ophogingen in waterbouwkundige constructies, uitgezonderd de diepe plas, als bedoeld in artikel 35, onder d, Bbk	Bepalingsgrens = 0,1
4.9.1	Baggerspecie toepassen in niet-vrijliggende diepe plassen die in open verbinding staan met een rijkswater, voor zover is voldaan aan de volgende voorwaarde: in de nabijheid van de diepe plas is geen kwetsbaar object gelegen, als bedoeld op p. 26 van de 'Handreiking voor het herinrichten van diepe plassen' ⁽³⁾	PFAS = 0,8 PFOS = 3,7
4.9.2	Baggerspecie toepassen in andere diepe plassen dan bedoeld onder 4.9.1	Bepalingsgrens = 0,1

- (1) Voor gebieden met een hoge grondwaterstand geldt in plaats van 'boven grondwaterniveau': tot ten hoogste 1 meter onder het maaiveld. Indien de grond als gevolg van zetting op termijn in de verzadigde zone terechtkomt wordt de grond geacht boven grondwater te zijn toegepast.
- (2) Voor gebieden met een hoge grondwaterstand geldt in plaats van 'onder grondwaterniveau': op een diepte van 1 meter en meer onder het maaiveld. Indien de grond als gevolg van zetting op termijn in de verzadigde zone terechtkomt wordt de grond geacht boven grondwater te zijn toegepast.
- (3) Onder 'diepe plas' wordt verstaan: oppervlaktewaterlichaam, ontstaan als gevolg van zandwinning, grindwinning of kleiwinning of een dijkdoorbraak.
Onder 'vrijliggende diepe plas' wordt verstaan: diepe plas, die niet is gelegen in een oppervlaktewaterlichaam in beheer bij het Rijk en die bovendien boven de spronglaag nauwelijks wordt gevoed door oppervlaktewater van elders (de verblijftijd van het water is voor 90% van het jaar langer dan een maand). Als de diepe plas is gelegen in een groter oppervlaktewaterlichaam wordt de rest van het oppervlaktewaterlichaam beschouwd als oppervlaktewater van elders. Deze plassen zijn aangegeven op de kaart die als bijlage bij dit tijdelijk handelingskader is gevoegd.
Onder 'niet-vrijliggende diepe plas' wordt verstaan: diepe plas, gelegen in een oppervlaktewaterlichaam in beheer bij het Rijk, of diepe plas die niet aan de definitie van vrijliggende plas voldoet.
- (4) Op de waarden uit deze tabel hoeft geen bodemtypecorrectie te worden toegepast als het gehalte van organische stof minder dan 10% bedraagt.
- (5) Tenzij een lokale maximale waarde is vastgesteld.

4.2.2 Analyseresultaten PFAS-verbindingen

De analysecertificaten van de PFAS-verbindingen zijn opgenomen in bijlage 4. Een samenvatting hiervan is opgenomen in navolgende tabel 4.2.

Tabel 4.2 Analyseresultaten PFAS (samenvatting)

Monster-nummer	Traject (m-wb)	Boring	Grond-soort	Org. stof (%)	PFOA gemeten (µg/kg)	PFOS gemeten (µg/kg)	Overige PFAS boven de 3 µg/kg?
OZ-01-1	0,00 - 0,50	OZ-01	Klei	3.8	0.69	0.45	Nee
OZ-01-2	0,50 - 1,00	OZ-01	Zand	<2	< 0.1	< 0.1	Nee
OZ-02-1	0,00 - 0,50	OZ-02	Klei	4.0	0.49	0.44	Nee
OZ-02-2	0,50 - 0,90	OZ-02	Klei	2.1	< 0.1	< 0.1	Nee
OZ-03-1	0,00 - 0,50	OZ-03	Klei	11.5	0.75	0.76	Nee
OZ-03-2	0,50 - 1,00	OZ-03	Klei	5.1	0.13	< 0.1	Nee
OZ-04-1	0,00 - 0,40	OZ-04	Klei	5.8	0.55	0.26	Nee
OZ-04-2	0,40 - 0,90	OZ-04	Klei	2.8	< 0.1	< 0.1	Nee
OZ-05-1	0,00 - 0,40	OZ-05	Klei	7.2	0.76	0.67	Nee
OZ-05-2	0,40 - 0,80	OZ-05	Klei	2.8	< 0.1	< 0.1	Nee
OZ-06-1	0,00 - 0,50	OZ-06	Klei	5.6	0.78	0.39	Nee
OZ-06-2	0,50 - 1,00	OZ-06	Klei	2.6	< 0.1	< 0.1	Nee
OZ-07-1	0,00 - 0,50	OZ-07	Klei	4.9	0.58	0.63	Nee
OZ-07-2	0,50 - 0,95	OZ-07	Zand	<2	< 0.1	< 0.1	Nee
OZ-08-1	0,00 - 0,50	OZ-08	Klei	5.7	0.73	0.63	Nee
OZ-08-3	0,65 - 1,00	OZ-08	Zand	<2	< 0.1	< 0.1	Nee
OZ-09-1	0,00 - 0,50	OZ-09	Klei	7.8	0.86	0.72	Nee
OZ-09-2	0,50 - 0,90	OZ-09	Klei	5.0	0.23	< 0.1	Nee
OZ-10-1	0,00 - 0,50	OZ-10	Klei	5.6	1	0.63	Nee
OZ-10-2	0,50 - 0,90	OZ-10	Klei	5.1	0.27	0.11	Nee
OZ-11-1	0,00 - 0,30	OZ-11	Klei	5.5	0.63	0.55	Nee
OZ-11-3	0,80 - 1,15	OZ-11	Zand	<2	< 0.1	< 0.1	Nee
OZ-12-1	0,00 - 0,40	OZ-12	Klei	5.9	0.21	< 0.1	Nee
OZ-12-3	0,85 - 1,00	OZ-12	Zand	<2	< 0.1	< 0.1	Nee
OZ-13-1	0,00 - 0,50	OZ-13	Klei	8.2	0.23	0.12	Nee
OZ-13-2	0,50 - 1,00	OZ-13	Klei	5.6	< 0.1	< 0.1	Nee
OZ-14-1	0,00 - 0,50	OZ-14	Klei	6.6	0.4	0.12	Nee
OZ-14-2	0,50 - 1,00	OZ-14	Klei	2.5	< 0.1	< 0.1	Nee
OZ-15-1	0,00 - 0,50	OZ-15	Klei	2.5	0.71	0.64	Nee
OZ-15-2	0,50 - 1,00	OZ-15	Klei	<2	0.21	0.19	Nee
OZ-16-1	0,00 - 0,50	OZ-16	Klei	11.2	0.95	0.52	Nee
OZ-16-2	0,50 - 1,00	OZ-16	Klei	9.3	< 0.1	< 0.1	Nee
OZ-17-1	0,00 - 0,50	OZ-17	Klei	7.0	0.6	0.76	Nee
OZ-17-2	0,50 - 1,00	OZ-17	Klei	<2	< 0.1	< 0.1	Nee
OZ-18-1	0,00 - 0,50	OZ-18	Klei	8.2	< 0.1	1.9	Nee
OZ-18-2	0,50 - 1,00	OZ-18	Klei	<2	< 0.1	0.2	Nee

Monster-nummer	Traject (m-wb)	Boring	Grond-soort	Org. stof (%)	PFOA gemeten (µg/kg)	PFOS gemeten (µg/kg)	Overige PFAS boven de 3 µg/kg?
OZ-19-1	0,00 - 0,50	OZ-19	Klei	8.5	0.82	2	Nee
OZ-19-2	0,50 - 1,00	OZ-19	Klei	4.3	0.11	0.13	Nee
OZ-20-1	0,00 - 0,50	OZ-20	Klei	6.9	0.61	0.9	Nee
OZ-20-2	0,50 - 1,00	OZ-20	Klei	4.4	0.19	0.17	Nee
RV-01-1	0,00 - 0,50	RV-01	Klei	6.8	0.7	0.34	Nee
RV-01-2	0,50 - 0,90	RV-01	Klei	3.9	0.29	< 0.1	Nee
RV-02-1	0,00 - 0,50	RV-02	Klei	8.2	0.52	0.51	Nee
RV-02-2	0,50 - 1,00	RV-02	Klei	<2	0.25	< 0.1	Nee
RV-03-1	0,00 - 0,50	RV-03	Klei	6.3	0.65	0.34	Nee
RV-03-2	0,50 - 1,00	RV-03	Klei	2.4	< 0.1	< 0.1	Nee
RV-04-1	0,00 - 0,50	RV-04	Klei	8.0	0.74	0.59	Nee
RV-04-2	0,50 - 1,00	RV-04	Klei	4.6	< 0.1	< 0.1	Nee
RV-05-1	0,00 - 0,50	RV-05	Klei	7.5	0.58	0.57	Nee
RV-05-2	0,50 - 1,00	RV-05	Klei	4.8	0.17	< 0.1	Nee
RV-06-1	0,00 - 0,50	RV-06	Klei	6.5	0.74	0.56	Nee
RV-06-2	0,50 - 1,00	RV-06	Klei	3.2	< 0.1	< 0.1	Nee
RV-07-1	0,00 - 0,50	RV-07	Klei	7.1	0.42	0.5	Nee
RV-07-2	0,50 - 1,00	RV-07	Klei	4.2	0.11	< 0.1	Nee
RV-08-1	0,00 - 0,40	RV-08	Klei	5.6	< 0.1	0.7	Nee
RV-08-2	0,40 - 0,90	RV-08	Klei	2.1	0.22	< 0.1	Nee
RV-09-1	0,00 - 0,45	RV-09	Klei	6.0	0.14	0.31	Nee
RV-09-2	0,45 - 0,95	RV-09	Klei	2.2	0.21	< 0.1	Nee
RV-10-1	0,00 - 0,30	RV-10	Klei	8.7	0.78	0.46	Nee
RV-10-3	0,50 - 1,00	RV-10	Klei	4.8	< 0.1	< 0.1	Nee
RV-11-1	0,00 - 0,30	RV-11	Klei	7.9	< 0.1	< 0.1	Nee
RV-11-3	0,50 - 1,00	RV-11	Klei	4.5	< 0.1	< 0.1	Nee
RV-12-1	0,00 - 0,50	RV-12	Klei	7.1	0.52	0.26	Nee
RV-12-2	0,50 - 1,00	RV-12	Klei	2.8	< 0.1	< 0.1	Nee
RV-13-1	0,00 - 0,50	RV-13	Klei	5.6	0.14	< 0.1	Nee
RV-13-2	0,50 - 1,00	RV-13	Klei	<2	< 0.1	< 0.1	Nee
RV-14-1	0,00 - 0,50	RV-14	Klei	4.9	< 0.1	< 0.1	Nee
RV-14-2	0,50 - 1,00	RV-14	Klei	3.5	0.11	< 0.1	Nee
RV-15-1	0,00 - 0,50	RV-15	Klei	7.9	0.72	0.41	Nee
RV-15-2	0,50 - 1,00	RV-15	Klei	5.3	< 0.1	< 0.1	Nee
RV-16-1	0,00 - 0,20	RV-16	Klei	9.9	1.5	0.61	Nee
RV-16-3	0,50 - 1,00	RV-16	Klei	5.3	0.15	< 0.1	Nee
RV-17-1	0,00 - 0,50	RV-17	Klei	7.8	0.59	0.45	Nee
RV-17-2	0,50 - 1,00	RV-17	Klei	3.6	< 0.1	< 0.1	Nee
RV-18-1	0,00 - 0,50	RV-18	Klei	7.8	0.22	1.2	Nee
RV-18-2	0,50 - 1,00	RV-18	Klei	<2	0.2	0.14	Nee
RV-19-1	0,00 - 0,50	RV-19	Klei	5.1	0.8	0.46	Nee

Monster-nummer	Traject (m-wb)	Boring	Grond-soort	Org. stof (%)	PFOA gemeten (µg/kg)	PFOS gemeten (µg/kg)	Overige PFAS boven de 3 µg/kg?
RV-19-2	0,50 - 1,00	RV-19	Klei	<2	< 0.1	< 0.1	Nee
RV-20-1	0,00 - 0,50	RV-20	Klei	4.2	0.33	0.13	Nee
RV-20-2	0,50 - 1,00	RV-20	Klei	<2	< 0.1	< 0.1	Nee

Gesteld kan worden dat op de locatie tot 1,0 m-wb PFAS aangetroffen wordt. De gehalten aan PFAS nemen af met de diepte. In de ondergrond (0,5-1,0 m-wb) is ter plaatse van 24 van de 40 boringen analytisch geen PFAS aangetroffen.

In de bovengrond (0,0-0,5 m-wb) zijn gehalten aan PFOA tussen < 0,1 en 1,5 µg/kg aangetroffen en gehalten aan PFOS tussen < 0,1 en 2,0 µg/kg.

In de ondergrond (0,5-1,0 m-wb) zijn gehalten aan PFOA tussen 0,1 en 0,29 µg/kg aangetroffen en gehalten aan PFOS tussen < 0,1 en 0,2 µg/kg.

Geconcludeerd kan worden dat de resultaten van onderhavig onderzoek gebruikt kunnen worden als aanvulling op de waterbodembodemkwaliteitskaart.

5 Actualisatie waterbodempkwaliteitskaart voor PFAS-verbindingen

5.1 Doelstelling actualiseren waterbodempkwaliteitskaart

Het doel van het actualiseren van de eerder opgestelde waterbodempkwaliteitskaart is om een actueel en dekkend beeld te krijgen van de te verwachten diffuse chemische waterbodempkwaliteit voor PFAS-verbindingen in de Maasuitewaarden Demen-Dieden.

De achterliggende doelstelling is de wens van de K3Delta om met de geactualiseerde bodempkwaliteitskaart gebruik te kunnen maken van de mogelijkheden die het Besluit biedt:

- als bewijsmiddel voor de chemische kwaliteit van vrijkomende waterbodem en van de ontvangende waterbodem (hierdoor hoeven minder onderzoeken te worden uitgevoerd wat een kosten- en tijdbesparende factor is bij grondverzet (waterbodem));
- bij het toepassen van grond en baggerspecie op en in de waterbodem.
- om achtergrondwaarden voor PFAS-verbindingen te kunnen definiëren.

5.2 Actualisatie waterbodempkwaliteitskaart voor PFAS-verbindingen

5.2.1 Actualisatie waterbodempkwaliteitskaart

De eerder opgestelde waterbodempkwaliteitskaart is geactualiseerd voor PFAS-verbindingen volgens de Richtlijn bodempkwaliteitskaarten. Hierin zijn verschillende stappen onderscheiden:

- Stap 1: Opstellen programma van eisen.
- Stap 2: Vaststellen onderscheidende kenmerken.
- Stap 3: Gegevensverzameling en gegevensbewerking.
- Stap 4: Indelen beheergebied in deelgebieden.
- Stap 5: Controle indeling van het beheergebied.
- Stap 6: Verzamelen aanvullende informatie.
- Stap 7: Vaststellen bodempkwaliteitszones.
- Stap 8: Opstellen ontgravings- en toepassingskaart.

In de Richtlijn bodempkwaliteitskaarten is aangegeven dat het niet noodzakelijk is de stappen chronologisch te volgen. Het is wel noodzakelijk dat de elementen van de benoemde stappen in de bodempkwaliteitskaart terugkomen. Hierna worden deze stappen kort nader toegelicht.

Bij **Stap 1** zijn in principe hetzelfde programma van eisen gehanteerd als dat van de eerder opgestelde waterbodempkwaliteitskaart. De wijzigingen op dat programma zijn als volgt:

- De waterbodempkwaliteitskaart wordt geactualiseerd voor de waterbodemplaat vanaf de bovenzijde van de waterbodem tot en met 7,0 meter diepte. Er worden 3 bodemplaten onderscheiden:
 - o Vanaf de bovenzijde van de waterbodem tot en met 0,5 meter diepte (de waterbodempkwaliteitskaart wordt voor deze bodemplaat ook vastgesteld voor PFAS-verbindingen; zie ook de stappen 2 en 4).
 - o Vanaf 0,5 meter tot en met 1,0 meter diepte (de waterbodempkwaliteitskaart wordt voor deze bodemplaat specifiek vastgesteld voor PFAS-verbindingen; zie ook de stappen 2 en 4).
 - o Vanaf 1,0 meter tot en met 7,0 meter diepte (de waterbodempkwaliteitskaart wordt voor deze bodemplaat niet vastgesteld voor PFAS-verbindingen). De bodemplaat dieper dan 1 meter is niet verdacht voor verhoogde gehalten aan PFAS-verbindingen.
- Voor de tussenlaag (0,5-1,0 m-wb) en de ondergrond (1,0-7,0 m-wb) is de kwaliteit voor de stoffen arseen, barium, cadmium, chroom, kobalt, koper, kwik, molybdeen, lood, nikkel, zink, minerale olie, PCB, PAK en OCB gelijk gesteld.
- De bodempkwaliteitskaart is gebaseerd op de dataset van de eerder opgestelde bodempkwaliteitskaarten en de gegevens van de in dit rapport gepresenteerde meetgegevens van PFAS-verbindingen.

De gedefinieerde waterbodempkwaliteitszones in de eerder opgestelde bodempkwaliteitskaarten zijn de deelgebieden van de te actualiseren bodempkwaliteitskaarten voor PFAS-verbindingen (**Stappen 2 en 4**). In de Maasuitwaarden Demen-Dieden worden geen ruimtelijke clusterings verwacht. Om deze reden is het deelgebied in het horizontale vlak niet gesplitst. Hierdoor is er per onderscheiden bodemplaat sprake van 1 PFAS-deelgebied. In het verticale vlak worden voor de PFAS-verbindingen 2 bodemplaten onderscheiden: (1) vanaf de bovenzijde van de waterbodem tot 0,5 meter diepte en (2) vanaf 0,5 meter tot 1,0 meter diepte onderscheiden. Deze lagen zijn vanwege atmosferische depositie, uitspoeling van de toplaag naar de tussenlaag en eventuele grondroering verdacht op het voorkomen van PFAS-verbindingen.

De in dit waterbodemonderzoek verkregen meetgegevens voor PFAS-verbindingen zijn aan de dataset van de eerder opgestelde waterbodempkwaliteitskaart toegevoegd (**Stap 3**).

Op de PFAS-verbindingen voeren wij de volgende gegevensbewerkingen uit:

1. Analysewaarden beneden de detectiegrens zijn vervangen door een rekenkundige waarde; én
2. Er heeft een controle plaatsgevonden op extra hoge waarden. Deze ontstaan bijvoorbeeld door een meetfout of een lokale bron die niet als zodanig bekend is. De zogenaamde uitbijteranalyse. In de dataset van de PFAS-gegevens zijn geen uitbijters vastgesteld.

Vervolgens heeft een controle plaatsgevonden op de indeling van de PFAS-deelgebieden (**Stap 5**). Omdat geen uitbijters bij de PFAS-gegevens zijn aangetoond, voldoen de deelgebieden aan de minimumeisen (aantal en spreiding) voor PFAS-verbindingen vanuit de Richtlijn bodempkwaliteitskaarten (zie § 2.4). Ook is gecontroleerd of sprake is van ruimtelijke clustering

van lage of juist hoge gehalten. Dit is op stofniveau gecontroleerd. Een hoge variatiecoëfficiënt is een indicatie van een mogelijke ruimtelijke clustering dat kan leiden tot het splitsen van een deelgebied. Voor PFAS-verbindingen heeft Lievense de ruimtelijke clustering onderzocht vanaf een relatief lage variatiecoëfficiënt: 1,5. In de Maasuitewaarden Demen-Dieden is geen ruimtelijke clustering van hoge of lage gehalten met PFAS-verbindingen vastgesteld. In de Maasuitewaarden Demen-Dieden zijn voor PFAS-verbindingen voldoende meetgegevens beschikbaar om de waterbodempkwaliteitskaart te actualiseren. Er zijn daarom geen extra meetgegevens verzameld (**Stap 6**).

Alle PFAS-deelgebieden voldoen aan de minimumeisen van de Richtlijn bodempkwaliteitskaarten en worden daarom definitief vastgesteld.

De definitieve PFAS-deelgebieden worden toegevoegd aan de waterbodempkwaliteitszones in de Maasuitewaarden Demen-Dieden. Er is hierbij een scheiding gemaakt tussen de Toplaag (traject vanaf de bovenzijde van de waterbodem tot en met 0,5 meter diepte) en de tussenlaag (traject vanaf 0,5 meter diepte tot en met 1,0 meter diepte).

De volgende waterbodempkwaliteitszones zijn onderscheiden:

- Toplaag Riviervlakte (0,0-0,5 m-wb): stoffen van het standaard stoffenpakket voor waterbodems in Rijkswateren (C2-pakket) én PFAS-verbindingen.
- Toplaag Oevergebied (0,0-0,5 m-wb): stoffen van het standaard stoffenpakket voor waterbodems in Rijkswateren (C2-pakket) én PFAS-verbindingen.
- Tussenlaag klei (0,5-1,0 m-wb): stoffen van het standaard stoffenpakket voor waterbodems in Rijkswateren (C2-pakket) én PFAS-verbindingen.
- Tussenlaag zand (0,5-1,0 m-wb): stoffen van het standaard stoffenpakket voor waterbodems in Rijkswateren (C2-pakket) én PFAS-verbindingen.
- Ondergrond klei (1,0-7,0 m-wb): stoffen van het standaard stoffenpakket voor waterbodems in Rijkswateren (C2-pakket).
- Ondergrond zand (1,0-7,0 m-wb): stoffen van het standaard stoffenpakket voor waterbodems in Rijkswateren (C2-pakket).

5.2.2 Stap 7: Vaststellen en karakteriseren bodempkwaliteitszones

De gemiddelde gehalten van de waterbodempkwaliteitszones (zie bijlage 6, kolom 'Gem') zijn getoetst aan de normen uit de Regeling bodempkwaliteit⁵ én de toepassingsnormen die zijn benoemd in het 'tijdelijke handelingskader hergebruik van PFAS-houdende grond en baggerspecie'. De bodempkwaliteitszones kunnen vallen in de waterbodempkwaliteitsklasse Vrij Toepasbaar, Klasse A, Klasse B of Nooit toepasbaar.

In tabel 5.1 is aangegeven in welke waterbodempkwaliteitsklasse iedere zone valt. In bijlage 6 zijn de gespecificeerde beoordelingen weergegeven. De waterbodempkwaliteitsklasse wordt gebruikt voor het bepalen van de toepassingseis.

⁵ Regeling bodempkwaliteit, publicatie Staatscourant nr. 247, 21 december 2007 en latere wijzigingen.

Controle saneringscriterium

In de Richtlijn staat vermeld, dat voor elke (water)bodemkwaliteitszone met een 95-percentielwaarde boven de interventiewaarde een controle op het saneringscriterium nodig is. Echter met de inwerkingtreding van de Waterwet is voor waterbodembodem de Wbb (Wet bodembescherming) vervallen en dus ook het saneringscriterium. Er is diffuus verspreid wel een overschrijding van de interventiewaarde aangetroffen in de Oeverzone (toplaag 0-0,5 m-wb).

Heterogeniteit

Naast de percentielwaarden en variatiecoëfficiënt is ook de heterogeniteit van de analysegegevens berekend, volgens de methodiek zoals beschreven onder het kopje 'Heterogeniteit' in bijlage 5. Een overzicht van de heterogeniteitsindex per stof en per zone is in bijlage 6 opgenomen (kolom 'Heterogeniteit'). Binnen de Maasuitwaarden Demen-Dieden is voor enkele stoffen sprake van sterke heterogeniteit. Wanneer de diffuse kwaliteit in een (water)bodemkwaliteitszone sterk heterogeen is verdeeld, is de betrouwbaarheid van het gemiddelde gehalte in de zone kleiner. In de betreffende (water)bodemkwaliteitszones zijn voldoende meetgegevens aanwezig om het gemiddelde gehalte goed te beschrijven.

5.2.3 Stap 8: Waterbodembodemkwaliteitskaart

De waterbodembodemkwaliteitskaart bestaat uit twee hoofdkaarten:

1. Een kaart met de indeling in gebieden.
2. De ontgravingskaart / toepassingskaart

In de volgende paragrafen is nader ingegaan op de hoofdkaarten.

5.2.3.1 Kaart met indeling in gebieden

De waterbodembodemkwaliteitskaart is opgesteld voor de waterbodembodem.

De uitgesloten gebieden (zie rapportage eerder opgestelde waterbodembodemkwaliteitskaart) zijn, voor zover mogelijk afgebeeld op de kaartbijlage. Desondanks zal bij uitvoering van ontgraven en toepassen van waterbodembodem altijd gekeken moeten worden naar de aanwezigheid van uitgesloten locaties en puntbronnen.

Deze waterbodembodemkwaliteitskaart mag op de uitgesloten locaties en gebieden niet worden gebruikt als bewijsmiddel voor waterbodembodem die wordt ontgraven vanuit deze gebieden. Ook mag deze waterbodembodemkwaliteitskaart niet worden gebruikt om de toepassingseis te bepalen als grond of waterbodembodem op deze locaties/gebieden wordt toegepast.

5.2.3.2 Ontgravings- en toepassingskaart

De ontgravingskaart geeft de te verwachten kwaliteit aan van de eventueel te ontgraven waterbodembodem op een voor verontreiniging niet-verdachte locatie. Deze kaart mag onder bepaalde voorwaarden worden gebruikt als bewijsmiddel voor de chemische kwaliteit van de te ontgraven waterbodembodem, als deze elders nuttig wordt toegepast. De kaart doet alleen een uitspraak over welke kwaliteit in het algemeen verwacht mag worden. De kwaliteit van een individuele partij kan daarvan afwijken.

De ontgravingskwaliteit is gebaseerd op het gemiddelde gehalte van een zone (zie bijlage 6, kolom 'Gem') en getoetst aan de toetsingswaarden uit de Regeling bodemkwaliteit én de toepassingsnormen die zijn benoemd in het 'tijdelijke handelingskader hergebruik van PFAS-houdende grond en baggerspecie'. In tabel 5.1 is de te verwachten ontgravingsklasse per zone aangegeven. De ontgravingskaart per waterbodemplaat is opgenomen in de kaartbijlagen 8 t/m 10. De kleuren in de tabel komen overeen met de gebruikte kleuren op de kaartbijlagen 8 t/m 10.

Uit tabel 5.1 blijkt dat zonder het definiëren en vaststellen van (gebieds)achtergrondwaarden voor PFAS-verbindingen gebiedseigen waterbodemplaat niet mag worden hergebruikt.

Tabel 5.1 Verwachte ontgravingsklasse en toepassingseis per waterbodemplaatkwaliteitszone

Waterbodemplaatkwaliteitszone	Verwachte ontgravingsklasse	Toepassingseis
Toplaag		
Rivierlakte (0-0,5 m-wb)	Klasse B *	Klasse B, Klasse A of Altijd toepasbaar **
Oevergebied (0-0,5 m-wb)	Klasse B *	Klasse B, Klasse A of Altijd toepasbaar **
Tussenlaag		
Tussenlaag klei (0,5-1,0 m-wb)	Klasse A *	Klasse A of Altijd toepasbaar **
Tussenlaag zand (0,5-1,0 m-wb)	Altijd toepasbaar *	Altijd toepasbaar **
Ondergrond		
Ondergrond klei (1,0-7,0 m-wb)	Klasse A	Klasse A of Altijd toepasbaar **
Ondergrond zand (1,0-7,0 m-wb)	Altijd toepasbaar	Altijd toepasbaar

* Het gemiddelde voor meerdere PFAS-verbindingen is boven de bepalingsgrens vastgesteld. Hierdoor gelden mogelijk aanvullende toepassingseisen.

** Zie § 5.3.

5.3 Voorstel beleid bij het voorgenomen grondverzet (waterbodemplaat)

Bij het grondverzet (waterbodemplaat) binnen de plangebiedsgrenzen wordt voor de PFAS-verbindingen voorgesteld aan te sluiten bij categorie 4.8.1 van het 'geactualiseerde tijdelijke handelingskader hergebruik van PFAS-houdende grond en baggerspecie' (zie ook tabel 4.1 van deze rapportage). Met het uitgevoerde onderzoek naar PFAS-verbindingen en de geactualiseerde waterbodemplaatkwaliteitskaart is een meer dan representatief aantal meetgegevens van PFAS-gehalten verzameld. Hierbij zijn geen uitbijters vastgesteld. Met deze gegevens kan het grondverzet (waterbodemplaat) binnen de plangebiedsgrenzen plaatsvinden zoals voorgenomen en zonder aanvullende kwaliteitseisen voor PFAS-verbindingen.

Hetzelfde geldt als waterbodemplaat wordt toegepast van buiten het plangebied maar binnen hetzelfde oppervlaktewaterlichaam (categorie 4.7, zie ook tabel 4.1 van deze rapportage).

Als grond (vanuit binnendijs gebied) wordt toegepast binnen het plangebied, geldt voor PFAS de bepalingsgrens (0,1 µg/kg d.s.) als toepassingseis (categorie 4.6 geactualiseerd tijdelijk

handelingskader, zie ook tabel 4.1 van deze rapportage). Verder moet de grond van een vergelijkbare of betere kwaliteitsklasse zijn als de ontvangende bodem.

Als grondverzet vanuit het plangebied naar elders plaatsvindt moet worden aangesloten bij het Besluit bodemkwaliteit en de 'geactualiseerde tijdelijke handelingskader hergebruik van PFAS-houdende grond en baggerspecie'.

5.4 Toekomstige bijstelling van de landelijke (toepassings)normen voor PFAS-houdende waterbodem

Tot en met 2020 wordt er nog veel onderzoek gedaan naar PFAS-verbindingen (bijvoorbeeld naar mobiliteit, uitloging, bioaccumulatie en gedrag in grondwater) en worden er landelijke veel meetgegevens door het RIVM verzameld. Op basis van deze onderzoeken en meetgegevens worden interventiewaarden gedefinieerd en worden mogelijk de toepassingsnormen voor PFAS-verbindingen aangepast.

Als interventiewaarden worden gedefinieerd, worden de landelijke normen gevolgd.

Als de landelijke toepassingsnormen voor PFAS-houdende grond en/of waterbodem worden gewijzigd, worden de gewijzigde normen geëvalueerd met de in deze rapportage gepresenteerde PFAS-gehalten en statistische parameters. Indien van toepassing worden de achtergrondwaarden gewijzigd en bestuurlijk vastgesteld.

Overzicht bijlagen

Bijlage 1	Regionale ligging van de onderzoekslocatie
Bijlage 2	Situatietekening onderzoekslocatie
Bijlage 3	Profielbeschrijvingen en veldverslag
Bijlage 4	Analysecertificaten PFAS
Bijlage 5	Begrippenlijst
Bijlage 6	Statistische parameters waterbodempkwaliteitszones
Kaartbijlage 7	Beheergebied en uitgesloten locaties
Kaartbijlage 8	Ontgravings- en toepassingskaart toplaag (0-0,5 m-wb)
Kaartbijlage 9	Ontgravings- en toepassingskaart tussenlaag (0,5-1,0 m-wb)
Kaartbijlage 10	Ontgravings- en toepassingskaart ondergrond (1,0-7,0 m-wb)

Bijlage 1 Regionale ligging van de onderzoekslocatie



LEGENDA



Locatie

Titel: Regionale ligging

Subtitel: -

Opdrachtgever: K3Delta

Projectnummer: SOB010398

Locatie: Angerense Waarden

Veldwerker: J. ten Klooster

Datum veldwerk: 28+29-10-2019

Bijlage:

1



Naam tekening:
SOB010398

LIEVENSE
adviseurs ingenieurs

Lievense Milieu B.V.
Kantoor Nieuwegein
Ringwade 41, 3439 LM Nieuwegein
www.Lievense.com
Info@Lievense.com
Tel: +31 88 910 2000


Tekenaar: B. Ebben

Datum tekening: 11-12-2019

Schaal: 1:50.000 Formaat: A4

0 500 1.000 1.500m

Bijlage 2 Situatietekening onderzoekslocatie



LEGENDA


- Boring tot 1,5 m-mv

Titel:	Overzicht	Bijlage:	2
Subtitel:	Demen-Dieren		
Opdrachtgever:	K3Delta		
Projectnummer:	SOB010398		
Locatie:	Demen-Dieren		
Veldwerker:	J. ten Klooster		
Datum veldwerk: 28+29-10-2019		Tekenaar: B. Ebben	
		Datum tekening: 11-12-2019	
		Schaal	1:12.500
		Formaat:	A3
		0125250375m	


Bijlage 3 Profielbeschrijvingen en veldverslag

Boring: OZ-01


Datum: 28-10-2019

**Boring: OZ-02**


Datum: 28-10-2019

**Boring: OZ-03**

Datum: 28-10-2019

**Boring: OZ-04**

Datum: 28-10-2019


**Projectcode: SOB010398-A**

getekend volgens NEN 5104


Projectnaam: Uiterwaarden Demen-Dieden
LIEVENSE
 adviseurs ingenieurs

Boring: OZ-05


Datum: 28-10-2019

**Boring: OZ-06**


Datum: 28-10-2019

**Boring: OZ-07**

Datum: 28-10-2019

**Boring: OZ-08**

Datum: 29-10-2019


**Projectcode: SOB010398-A**

getekend volgens NEN 5104


Projectnaam: Uiterwaarden Demen-Dieden
LIEVENSE
 adviseurs ingenieurs

Boring: OZ-09


Datum: 29-10-2019

**Boring: OZ-10**


Datum: 29-10-2019

**Boring: OZ-11**

Datum: 29-10-2019

**Boring: OZ-12**

Datum: 29-10-2019


**Projectcode: SOB010398-A**

getekend volgens NEN 5104


Projectnaam: Uiterwaarden Demen-Dieden
LIEVENSE
 adviseurs ingenieurs

Boring: OZ-13


Datum: 29-10-2019

**Boring: OZ-14**


Datum: 29-10-2019

**Boring: OZ-15**

Datum: 29-10-2019

**Boring: OZ-16**

Datum: 29-10-2019


**Projectcode: SOB010398-A**

getekend volgens NEN 5104


Projectnaam: Uiterwaarden Demen-Dieden
LIEVENSE
 adviseurs ingenieurs

Boring: OZ-17


Datum: 29-10-2019

**Boring: OZ-18**


Datum: 29-10-2019

**Boring: OZ-19**

Datum: 29-10-2019

**Boring: OZ-20**

Datum: 29-10-2019


**Projectcode: SOB010398-A**

getekend volgens NEN 5104


Projectnaam: Uiterwaarden Demen-Dieden
LIEVENSE
 adviseurs ingenieurs

Boring: RV-01


Datum: 28-10-2019

**Boring: RV-02**


Datum: 28-10-2019

**Boring: RV-03**

Datum: 28-10-2019

**Boring: RV-04**

Datum: 28-10-2019


**Projectcode: SOB010398-A**

getekend volgens NEN 5104


Projectnaam: Uiterwaarden Demen-Dieden
LIEVENSE
 adviseurs ingenieurs

Boring: RV-05


Datum: 28-10-2019

**Boring: RV-06**


Datum: 28-10-2019

**Boring: RV-07**

Datum: 28-10-2019

**Boring: RV-08**

Datum: 28-10-2019


**Projectcode: SOB010398-A**

getekend volgens NEN 5104


Projectnaam: Uiterwaarden Demen-Dieden
LIEVENSE
 adviseurs ingenieurs

Boring: RV-09


Datum: 28-10-2019

**Boring: RV-10**


Datum: 28-10-2019

**Boring: RV-11**

Datum: 29-10-2019

**Boring: RV-12**

Datum: 29-10-2019


**Projectcode: SOB010398-A**

getekend volgens NEN 5104


Projectnaam: Uiterwaarden Demen-Dieden
LIEVENSE
 adviseurs ingenieurs

Boring: RV-13


Datum: 29-10-2019

**Boring: RV-14**


Datum: 29-10-2019

**Boring: RV-15**

Datum: 29-10-2019

**Boring: RV-16**

Datum: 29-10-2019


**Projectcode: SOB010398-A**

getekend volgens NEN 5104


Projectnaam: Uiterwaarden Demen-Dieden
LIEVENSE
 adviseurs ingenieurs

Boring: RV-17


Datum: 29-10-2019

**Boring: RV-18**


Datum: 29-10-2019

**Boring: RV-19**

Datum: 29-10-2019

**Boring: RV-20**

Datum: 29-10-2019


**Projectcode: SOB010398-A**

getekend volgens NEN 5104


Projectnaam: Uiterwaarden Demen-Dieden
LIEVENSE
 adviseurs ingenieurs

Legenda (conform NEN 5104)


grind




Grind, siltig




Grind, zwak zandig



Grind, matig zandig




Grind, sterk zandig




Grind, uiterst zandig


zand




Zand, kleiig




Zand, zwak siltig



Zand, matig siltig



Zand, sterk siltig




Zand, uiterst siltig


veen




Veen, mineraalarm




Veen, zwak kleiig



Veen, sterk kleiig



Veen, zwak zandig



Veen, sterk zandig

klei



Klei, zwak siltig



Klei, matig siltig



Klei, sterk siltig



Klei, uiterst siltig



Klei, zwak zandig



Klei, matig zandig



Klei, sterk zandig

leem



Leem, zwak zandig




Leem, sterk zandig

overige toevoegingen



zwak humeus




matig humeus



sterk humeus



zwak grindig



matig grindig



sterk grindig

geur

- geen geur
- ◐ zwakke geur
- ◑ matige geur
- ◒ sterke geur
- ◓ uiterste geur

olie

- geen olie-water reactie
- ◻ zwakke olie-water reactie
- ◼ matige olie-water reactie
- ◽ sterke olie-water reactie
- ◾ uiterste olie-water reactie

p.i.d.-waarde

- ◊ >0
- ◈ >1
- ◉ >10
- ◊ >100
- ◈ >1000
- ◉ >10000

monsters


- ◻ geroerd monster
- ◻ ongeroerd monster
- ◊ volumering

overig

- ▲ bijzonder bestanddeel
- ◀ Gemiddeld hoogste grondwaterstand
- ≡ grondwaterstand
- ◆ Gemiddeld laagste grondwaterstand



slib



water

Projectcode: SOB010398-A

getekend volgens NEN 5104

Projectnaam: Uiterwaarden Demen-Dieden

LIEVENSE
 adviseurs ingenieurs

Bijlage 4 Analysecertificaten PFAS

Lievense Milieu B.V.
Robin van Rijnsoever
Ringwade 41
3439 LM NIEUWEGEIN

Blad 1 van 195

Uw projectnaam : Uiterwaarden Demen-Dieden (PFAS)
Uw projectnummer : SOB010398-A
SYNLAB rapportnummer : 13136554, versienummer: 1
Rapport-verificatienummer : FHHEIPUH

Rotterdam, 18-11-2019

Geachte heer/mevrouw,

Hierbij ontvangt u de analyse resultaten van het laboratoriumonderzoek ten behoeve van uw project SOB010398-A. Het onderzoek werd uitgevoerd conform uw opdracht. De gerapporteerde resultaten hebben uitsluitend betrekking op de geteste monsters. De door u aangegeven omschrijvingen voor de monsters, het project en de monsternamedatum (indien aangeleverd) zijn overgenomen in dit analyserapport.

Het onderzoek is uitgevoerd door SYNLAB Analytics & Services B.V., gevestigd aan de Steenhouwerstraat 15 in Rotterdam (NL). Indien het onderzoek is uitgevoerd door derden of het SYNLAB laboratorium in Frankrijk (99-101 Avenue Louis Roche, Gennevilliers) is dit in het rapport aangegeven.

Dit analyserapport bestaat inclusief bijlagen uit 195 pagina's. In geval van een versienummer van '2' of hoger vervallen de voorgaande versies. Alle bijlagen maken onlosmakelijk onderdeel uit van het rapport. Alleen vermenigvuldiging van het hele rapport is toegestaan.

Mocht u vragen en/of opmerkingen hebben naar aanleiding van dit rapport, bijvoorbeeld als u nadere informatie nodig heeft over de meetonzekerheid van de analyseresultaten in dit rapport, dan verzoeken wij u vriendelijk contact op te nemen met de afdeling Customer Support.

Wij vertrouwen er op u met deze informatie van dienst te zijn.

Hoogachtend,



Jaap-Willem Hutter
Technical Director

Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Nummer	Monstersoort	Monsterspecificatie
001	Waterbodem (AS3000)	OZ-01-1 OZ-01-1 OZ-01 (0-50)
002	Waterbodem (AS3000)	OZ-01-2 OZ-01-2 OZ-01 (50-100)
003	Waterbodem (AS3000)	OZ-02-1 OZ-02-1 OZ-02 (0-50)
004	Waterbodem (AS3000)	OZ-02-2 OZ-02-2 OZ-02 (50-90)
005	Waterbodem (AS3000)	OZ-03-1 OZ-03-1 OZ-03 (0-50)

Analyse	Eenheid	Q	001	002	003	004	005
droge stof	gew.-%	S	84.0	92.9	83.0	82.1	75.1
gewicht artefacten	g	S	0	0	0	0	0
aard van de artefacten	-	S	geen	geen	geen	geen	geen
organische stof (gloeiverlies)	% vd DS	S	3.8	<2	4.0	2.1	11.5
gloeirest	% vd DS		95.8	99.1	95.6	97.5	88.1
ANALYSES UITGEVOERD DOOR DERDEN							
Adviespakket PFAS 30 componenten			zie bijlage	zie bijlage	zie bijlage	zie bijlage	zie bijlage

De met S gemerkte analyses zijn geaccrediteerd en vallen onder de AS3000-erkenning.

Paraaf :

Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Monster beschrijvingen

- | | | |
|-----|---|--|
| 001 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 002 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 003 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 004 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 005 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |

Paraaf :



Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Nummer	Monstersoort	Monsterspecificatie					
006	Waterbodem (AS3000)	OZ-03-2 OZ-03-2 OZ-03 (50-100)					
007	Waterbodem (AS3000)	OZ-04-1 OZ-04-1 OZ-04 (0-40)					
008	Waterbodem (AS3000)	OZ-04-2 OZ-04-2 OZ-04 (40-90)					
009	Waterbodem (AS3000)	OZ-05-1 OZ-05-1 OZ-05 (0-40)					
010	Waterbodem (AS3000)	OZ-05-2 OZ-05-2 OZ-05 (40-80)					

Analyse	Eenheid	Q	006	007	008	009	010
droge stof	gew.-%	S	79.9	80.9	81.1	79.6	84.9
gewicht artefacten	g	S	0	0	0	0	0
aard van de artefacten	-	S	geen	geen	geen	geen	geen
organische stof (gloeiverlies)	% vd DS	S	5.1	5.8	2.8	7.2	2.8
gloeirest	% vd DS		94.5	93.8	96.8	92.4	96.8
ANALYSES UITGEVOERD DOOR DERDEN							
Adviespakket PFAS 30 componenten			zie bijlage	zie bijlage	zie bijlage	zie bijlage	zie bijlage

De met S gemerkte analyses zijn geaccrediteerd en vallen onder de AS3000-erkenning.

Paraaf :

Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Monster beschrijvingen

- | | | |
|-----|---|--|
| 006 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 007 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 008 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 009 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 010 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |

Paraaf :



Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Nummer	Monstersoort	Monsterspecificatie
011	Waterbodem (AS3000)	OZ-06-1 OZ-06-1 OZ-06 (0-50)
012	Waterbodem (AS3000)	OZ-06-2 OZ-06-2 OZ-06 (50-100)
013	Waterbodem (AS3000)	OZ-07-1 OZ-07-1 OZ-07 (0-50)
014	Waterbodem (AS3000)	OZ-07-2 OZ-07-2 OZ-07 (50-95)
015	Waterbodem (AS3000)	OZ-08-1 OZ-08-1 OZ-08 (0-50)

Analyse	Eenheid	Q	011	012	013	014	015
droge stof	gew.-%	S	82.8	90.2	83.7	95.2	81.1
gewicht artefacten	g	S	0	0	0	38.3	0
aard van de artefacten	-	S	geen	geen	geen	stenen	geen
organische stof (gloeiverlies)	% vd DS	S	5.6	2.6	4.9	<2	5.7
gloeirest	% vd DS		94.0	97.0	94.7	99.4	94.0
ANALYSES UITGEVOERD DOOR DERDEN							
Adviespakket PFAS 30 componenten			zie bijlage	zie bijlage	zie bijlage	zie bijlage	zie bijlage

De met S gemerkte analyses zijn geaccrediteerd en vallen onder de AS3000-erkenning.

Paraaf :

Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Monster beschrijvingen

- | | | |
|-----|---|--|
| 011 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 012 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 013 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 014 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 015 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |

Paraaf :



Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Nummer	Monstersoort	Monsterspecificatie
016	Waterbodem (AS3000)	OZ-08-3 OZ-08-3 OZ-08 (65-100)
017	Waterbodem (AS3000)	OZ-09-1 OZ-09-1 OZ-09 (0-50)
018	Waterbodem (AS3000)	OZ-09-2 OZ-09-2 OZ-09 (50-90)
019	Waterbodem (AS3000)	OZ-10-1 OZ-10-1 OZ-10 (0-50)
020	Waterbodem (AS3000)	OZ-10-2 OZ-10-2 OZ-10 (50-90)

Analyse	Eenheid	Q	016	017	018	019	020
droge stof	gew.-%	S	96.7	77.7	81.6	78.7	78.6
gewicht artefacten	g	S	0	0	0	0	0
aard van de artefacten	-	S	geen	geen	geen	geen	geen
organische stof (gloeiverlies)	% vd DS	S	<2	7.8	5.0	5.6	5.1
gloeirest	% vd DS		99.2	91.8	94.6	94.0	94.5
ANALYSES UITGEVOERD DOOR DERDEN							
Adviespakket PFAS 30 componenten			zie bijlage	zie bijlage	zie bijlage	zie bijlage	zie bijlage

De met S gemerkte analyses zijn geaccrediteerd en vallen onder de AS3000-erkenning.

Paraaf :

Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Monster beschrijvingen

- | | | |
|-----|---|--|
| 016 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 017 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 018 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 019 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 020 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |

Paraaf :



Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Nummer	Monstersoort	Monsterspecificatie
021	Waterbodem (AS3000)	OZ-11-1 OZ-11-1 OZ-11 (0-30)
022	Waterbodem (AS3000)	OZ-11-3 OZ-11-3 OZ-11 (80-115)
023	Waterbodem (AS3000)	OZ-12-1 OZ-12-1 OZ-12 (0-40)
024	Waterbodem (AS3000)	OZ-12-3 OZ-12-3 OZ-12 (85-100)
025	Waterbodem (AS3000)	OZ-13-1 OZ-13-1 OZ-13 (0-50)

Analyse	Eenheid	Q	021	022	023	024	025
droge stof	gew.-%	S	80.4	85.1	79.7	93.1	76.5
gewicht artefacten	g	S	8.43	0	0	8.17	0
aard van de artefacten	-	S	stenen	geen	geen	stenen	geen
organische stof (gloeiverlies)	% vd DS	S	5.5	<2	5.9	<2	8.2
gloeirest	% vd DS		94.1	98.7	93.7	98.4	91.4
ANALYSES UITGEVOERD DOOR DERDEN							
Adviespakket PFAS 30 componenten			zie bijlage	zie bijlage	zie bijlage	zie bijlage	zie bijlage

De met S gemerkte analyses zijn geaccrediteerd en vallen onder de AS3000-erkenning.

Paraaf :

Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Monster beschrijvingen

- | | | |
|-----|---|--|
| 021 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 022 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 023 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 024 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 025 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |

Paraaf :



Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Nummer	Monstersoort	Monsterspecificatie
026	Waterbodem (AS3000)	OZ-13-2 OZ-13-2 OZ-13 (50-100)
027	Waterbodem (AS3000)	OZ-14-1 OZ-14-1 OZ-14 (0-50)
028	Waterbodem (AS3000)	OZ-14-2 OZ-14-2 OZ-14 (50-100)
029	Waterbodem (AS3000)	OZ-15-1 OZ-15-1 OZ-15 (0-50)
030	Waterbodem (AS3000)	OZ-15-2 OZ-15-2 OZ-15 (50-100)

Analyse	Eenheid	Q	026	027	028	029	030
droge stof	gew.-%	S	82.6	80.0	84.3	86.0	91.5
gewicht artefacten	g	S	0	0	0	0	0
aard van de artefacten	-	S	geen	geen	geen	geen	geen
organische stof (gloeiverlies)	% vd DS	S	5.6	6.6	2.5	2.5	<2
gloeirest	% vd DS		94.0	93.0	97.1	97.1	98.2
ANALYSES UITGEVOERD DOOR DERDEN							
Adviespakket PFAS 30 componenten			zie bijlage	zie bijlage	zie bijlage	zie bijlage	zie bijlage

De met S gemerkte analyses zijn geaccrediteerd en vallen onder de AS3000-erkenning.

Paraaf :

Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Monster beschrijvingen

- | | | |
|-----|---|--|
| 026 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 027 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 028 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 029 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 030 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |

Paraaf :



Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Nummer	Monstersoort	Monsterspecificatie
031	Waterbodem (AS3000)	OZ-16-1 OZ-16-1 OZ-16 (0-50)
032	Waterbodem (AS3000)	OZ-16-2 OZ-16-2 OZ-16 (50-100)
033	Waterbodem (AS3000)	OZ-17-1 OZ-17-1 OZ-17 (0-50)
034	Waterbodem (AS3000)	OZ-17-2 OZ-17-2 OZ-17 (50-100)
035	Waterbodem (AS3000)	OZ-18-1 OZ-18-1 OZ-18 (0-50)

Analyse	Eenheid	Q	031	032	033	034	035
droge stof	gew.-%	S	76.3	75.0	74.3	89.2	76.9
gewicht artefacten	g	S	0	0	0	0	0
aard van de artefacten	-	S	geen	geen	geen	geen	geen
organische stof (gloeiverlies)	% vd DS	S	11.2	9.3	7.0	<2	8.2
gloeirest	% vd DS		88.5	90.3	92.7	98.5	91.4
ANALYSES UITGEVOERD DOOR DERDEN							
Adviespakket PFAS 30 componenten			zie bijlage	zie bijlage	zie bijlage	zie bijlage	zie bijlage

De met S gemerkte analyses zijn geaccrediteerd en vallen onder de AS3000-erkenning.

Paraaf :

Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Monster beschrijvingen

- | | | |
|-----|---|--|
| 031 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 032 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 033 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 034 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 035 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |

Paraaf :



Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Nummer	Monstersoort	Monsterspecificatie
036	Waterbodem (AS3000)	OZ-18-2 OZ-18-2 OZ-18 (50-100)
037	Waterbodem (AS3000)	OZ-19-1 OZ-19-1 OZ-19 (0-50)
038	Waterbodem (AS3000)	OZ-19-2 OZ-19-2 OZ-19 (50-100)
039	Waterbodem (AS3000)	OZ-20-1 OZ-20-1 OZ-20 (0-50)
040	Waterbodem (AS3000)	OZ-20-2 OZ-20-2 OZ-20 (50-100)

Analyse	Eenheid	Q	036	037	038	039	040
droge stof	gew.-%	S	87.6	77.5	79.9	80.5	86.0
gewicht artefacten	g	S	0	0	0	0	0
aard van de artefacten	-	S	geen	geen	geen	geen	geen
organische stof (gloeiverlies)	% vd DS	S	<2	8.5	4.3	6.9	4.4
gloeirest	% vd DS		97.6	91.1	95.3	92.7	95.2
ANALYSES UITGEVOERD DOOR DERDEN							
Adviespakket PFAS 30 componenten			zie bijlage	zie bijlage	zie bijlage	zie bijlage	zie bijlage

De met S gemerkte analyses zijn geaccrediteerd en vallen onder de AS3000-erkenning.

Paraaf :

Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Monster beschrijvingen

- | | | |
|-----|---|--|
| 036 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 037 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 038 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 039 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 040 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |

Paraaf :



Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Nummer	Monstersoort	Monsterspecificatie
041	Waterbodem (AS3000)	RV-01-1 RV-01-1 RV-01 (0-50)
042	Waterbodem (AS3000)	RV-01-2 RV-01-2 RV-01 (50-90)
043	Waterbodem (AS3000)	RV-02-1 RV-02-1 RV-02 (0-50)
044	Waterbodem (AS3000)	RV-02-2 RV-02-2 RV-02 (50-100)
045	Waterbodem (AS3000)	RV-03-1 RV-03-1 RV-03 (0-50)

Analyse	Eenheid	Q	041	042	043	044	045
droge stof	gew.-%	S	77.8	81.9	75.4	84.5	77.5
gewicht artefacten	g	S	0	0	0	0	0
aard van de artefacten	-	S	geen	geen	geen	geen	geen
organische stof (gloeiverlies)	% vd DS	S	6.8	3.9	8.2	<2	6.3
gloeirest	% vd DS		92.8	95.7	91.4	97.7	93.3
ANALYSES UITGEVOERD DOOR DERDEN							
Adviespakket PFAS 30 componenten			zie bijlage	zie bijlage	zie bijlage	zie bijlage	zie bijlage

De met S gemerkte analyses zijn geaccrediteerd en vallen onder de AS3000-erkenning.

Paraaf :

Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Monster beschrijvingen

- | | | |
|-----|---|--|
| 041 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 042 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 043 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 044 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 045 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |

Paraaf :



Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Nummer	Monstersoort	Monsterspecificatie
046	Waterbodem (AS3000)	RV-03-2 RV-03-2 RV-03 (50-100)
047	Waterbodem (AS3000)	RV-04-1 RV-04-1 RV-04 (0-50)
048	Waterbodem (AS3000)	RV-04-2 RV-04-2 RV-04 (50-100)
049	Waterbodem (AS3000)	RV-05-1 RV-05-1 RV-05 (0-50)
050	Waterbodem (AS3000)	RV-05-2 RV-05-2 RV-05 (50-100)

Analyse	Eenheid	Q	046	047	048	049	050
droge stof	gew.-%	S	82.2	77.3	79.8	78.3	82.5
gewicht artefacten	g	S	0	0	0	0	0
aard van de artefacten	-	S	geen	geen	geen	geen	geen
organische stof (gloeiverlies)	% vd DS	S	2.4	8.0	4.6	7.5	4.8
gloeirest	% vd DS		97.2	91.6	95.0	92.2	94.8
ANALYSES UITGEVOERD DOOR DERDEN							
Adviespakket PFAS 30 componenten			zie bijlage	zie bijlage	zie bijlage	zie bijlage	zie bijlage

De met S gemerkte analyses zijn geaccrediteerd en vallen onder de AS3000-erkenning.

Paraaf :

Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Monster beschrijvingen

- | | | |
|-----|---|--|
| 046 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 047 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 048 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 049 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 050 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |

Paraaf :



Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Nummer	Monstersoort	Monsterspecificatie
051	Waterbodem (AS3000)	RV-06-1 RV-06-1 RV-06 (0-50)
052	Waterbodem (AS3000)	RV-06-2 RV-06-2 RV-06 (50-100)
053	Waterbodem (AS3000)	RV-07-1 RV-07-1 RV-07 (0-50)
054	Waterbodem (AS3000)	RV-07-2 RV-07-2 RV-07 (50-100)
055	Waterbodem (AS3000)	RV-08-1 RV-08-1 RV-08 (0-40)

Analyse	Eenheid	Q	051	052	053	054	055
droge stof	gew.-%	S	78.3	79.4	77.5	79.5	79.2
gewicht artefacten	g	S	0	0	0	0	0
aard van de artefacten	-	S	geen	geen	geen	geen	geen
organische stof (gloeiverlies)	% vd DS	S	6.5	3.2	7.1	4.2	5.6
gloeirest	% vd DS		93.1	96.4	92.5	95.4	94.0
ANALYSES UITGEVOERD DOOR DERDEN							
Adviespakket PFAS 30 componenten			zie bijlage	zie bijlage	zie bijlage	zie bijlage	zie bijlage

De met S gemerkte analyses zijn geaccrediteerd en vallen onder de AS3000-erkenning.

Paraaf :

Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Monster beschrijvingen

- | | | |
|-----|---|--|
| 051 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 052 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 053 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 054 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 055 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |

Paraaf :



Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Nummer	Monstersoort	Monsterspecificatie
056	Waterbodem (AS3000)	RV-08-2 RV-08-2 RV-08 (40-90)
057	Waterbodem (AS3000)	RV-09-1 RV-09-1 RV-09 (0-45)
058	Waterbodem (AS3000)	RV-09-2 RV-09-2 RV-09 (45-95)
059	Waterbodem (AS3000)	RV-10-1 RV-10-1 RV-10 (0-30)
060	Waterbodem (AS3000)	RV-10-3 RV-10-3 RV-10 (50-100)

Analyse	Eenheid	Q	056	057	058	059	060
droge stof	gew.-%	S	85.9	77.1	82.8	80.3	77.8
gewicht artefacten	g	S	0	0	0	0	0
aard van de artefacten	-	S	geen	geen	geen	geen	geen
organische stof (gloeiverlies)	% vd DS	S	2.1	6.0	2.2	8.7	4.8
gloeirest	% vd DS		97.5	93.6	97.5	90.9	94.8
ANALYSES UITGEVOERD DOOR DERDEN							
Adviespakket PFAS 30 componenten			zie bijlage	zie bijlage	zie bijlage	zie bijlage	zie bijlage

De met S gemerkte analyses zijn geaccrediteerd en vallen onder de AS3000-erkenning.

Paraaf :

Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Monster beschrijvingen

- | | | |
|-----|---|--|
| 056 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 057 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 058 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 059 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 060 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |

Paraaf :



Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Nummer	Monstersoort	Monsterspecificatie
061	Waterbodem (AS3000)	RV-11-1 RV-11-1 RV-11 (0-30)
062	Waterbodem (AS3000)	RV-11-3 RV-11-3 RV-11 (50-100)
063	Waterbodem (AS3000)	RV-12-1 RV-12-1 RV-12 (0-50)
064	Waterbodem (AS3000)	RV-12-2 RV-12-2 RV-12 (50-100)
065	Waterbodem (AS3000)	RV-13-1 RV-13-1 RV-13 (0-50)

Analyse	Eenheid	Q	061	062	063	064	065
droge stof	gew.-%	S	80.7	79.3	73.3	81.7	78.8
gewicht artefacten	g	S	0	0	0	0	0
aard van de artefacten	-	S	geen	geen	geen	geen	geen
organische stof (gloeiverlies)	% vd DS	S	7.9	4.5	7.1	2.8	5.6
gloeirest	% vd DS		91.7	95.1	92.6	96.8	94.0
ANALYSES UITGEVOERD DOOR DERDEN							
Adviespakket PFAS 30 componenten			zie bijlage	zie bijlage	zie bijlage	zie bijlage	zie bijlage

De met S gemerkte analyses zijn geaccrediteerd en vallen onder de AS3000-erkenning.

Paraaf :

Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Monster beschrijvingen

- | | | |
|-----|---|--|
| 061 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 062 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 063 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 064 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 065 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |

Paraaf :



Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Nummer	Monstersoort	Monsterspecificatie
066	Waterbodem (AS3000)	RV-13-2 RV-13-2 RV-13 (50-100)
067	Waterbodem (AS3000)	RV-14-1 RV-14-1 RV-14 (0-50)
068	Waterbodem (AS3000)	RV-14-2 RV-14-2 RV-14 (50-100)
069	Waterbodem (AS3000)	RV-15-1 RV-15-1 RV-15 (0-50)
070	Waterbodem (AS3000)	RV-15-2 RV-15-2 RV-15 (50-100)

Analyse	Eenheid	Q	066	067	068	069	070
droge stof	gew.-%	S	88.3	79.5	82.3	79.5	80.5
gewicht artefacten	g	S	0	0	0	0	0
aard van de artefacten	-	S	geen	geen	geen	geen	geen
organische stof (gloeiverlies)	% vd DS	S	<2	4.9	3.5	7.9	5.3
gloeirest	% vd DS		98.2	94.7	96.1	91.7	94.3
ANALYSES UITGEVOERD DOOR DERDEN							
Adviespakket PFAS 30 componenten			zie bijlage	zie bijlage	zie bijlage	zie bijlage	zie bijlage

De met S gemerkte analyses zijn geaccrediteerd en vallen onder de AS3000-erkenning.

Paraaf :

Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Monster beschrijvingen

- | | | |
|-----|---|--|
| 066 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 067 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 068 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 069 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 070 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |

Paraaf :



Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Nummer	Monstersoort	Monsterspecificatie
071	Waterbodem (AS3000)	RV-16-1 RV-16-1 RV-16 (0-20)
072	Waterbodem (AS3000)	RV-16-3 RV-16-3 RV-16 (50-100)
073	Waterbodem (AS3000)	RV-17-1 RV-17-1 RV-17 (0-50)
074	Waterbodem (AS3000)	RV-17-2 RV-17-2 RV-17 (50-100)
075	Waterbodem (AS3000)	RV-18-1 RV-18-1 RV-18 (0-50)

Analyse	Eenheid	Q	071	072	073	074	075
droge stof	gew.-%	S	73.8	78.1	79.2	81.2	81.2
gewicht artefacten	g	S	0	0	0	0	0
aard van de artefacten	-	S	geen	geen	geen	geen	geen
organische stof (gloeiverlies)	% vd DS	S	9.9	5.3	7.8	3.6	7.8
gloeirest	% vd DS		89.7	94.3	91.9	96.0	91.8
ANALYSES UITGEVOERD DOOR DERDEN							
Adviespakket PFAS 30 componenten			zie bijlage	zie bijlage	zie bijlage	zie bijlage	zie bijlage

De met S gemerkte analyses zijn geaccrediteerd en vallen onder de AS3000-erkenning.

Paraaf :

Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Monster beschrijvingen

- | | | |
|-----|---|--|
| 071 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 072 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 073 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 074 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 075 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |

Paraaf :



Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Nummer	Monstersoort	Monsterspecificatie
076	Waterbodem (AS3000)	RV-18-2 RV-18-2 RV-18 (50-100)
077	Waterbodem (AS3000)	RV-19-1 RV-19-1 RV-19 (0-50)
078	Waterbodem (AS3000)	RV-19-2 RV-19-2 RV-19 (50-100)
079	Waterbodem (AS3000)	RV-20-1 RV-20-1 RV-20 (0-50)
080	Waterbodem (AS3000)	RV-20-2 RV-20-2 RV-20 (50-100)

Analyse	Eenheid	Q	076	077	078	079	080
droge stof	gew.-%	S	85.3	80.1	87.2	81.8	85.8
gewicht artefacten	g	S	0	0	0	0	0
aard van de artefacten	-	S	geen	geen	geen	geen	geen
organische stof (gloeiverlies)	% vd DS	S	<2	5.1	<2	4.2	<2
gloeirest	% vd DS		97.7	94.5	98.2	95.4	98.1
ANALYSES UITGEVOERD DOOR DERDEN							
Adviespakket PFAS 30 componenten			zie bijlage	zie bijlage	zie bijlage	zie bijlage	zie bijlage

De met S gemerkte analyses zijn geaccrediteerd en vallen onder de AS3000-erkenning.

Paraaf :

Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Monster beschrijvingen

- | | | |
|-----|---|--|
| 076 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 077 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 078 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 079 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |
| 080 | * | De monstervoorbehandeling en analyses zijn uitgevoerd conform Accreditatieschema AS3000, dit geldt alleen voor de analyses die worden gerapporteerd met het "S" kenmerk. |

Paraaf :



Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Analyse	Monstersoort	Relatie tot norm
droge stof	Waterbodem (AS3000)	Waterbodem: Eigen methode (analyse gelijkwaardig aan ISO-11465 en gelijkwaardig aan NEN-EN 15934). AS3000-waterbodem: conform AS3210-1 en conform NEN-EN 15934
gewicht artefacten	Waterbodem (AS3000)	Conform AS3000 en conform NEN-EN 16179
aard van de artefacten	Waterbodem (AS3000)	Idem
organische stof (gloeiverlies)	Waterbodem (AS3000)	Conform AS3210-2 (org. stof gecorrigeerd voor 5,4 % lutum) en gelijkwaardig aan NEN 5754.
gloeirest	Waterbodem (AS3000)	Gloeirest bepaling is gelijkwaardig aan NEN-EN 12879
Adviespakket PFAS 30 componenten	Waterbodem (AS3000)	Analyse uitbesteed

Monster	Barcode	Aanlevering	Monstername	Verpakking
001	U9091082	30-10-2019	28-10-2019	ALC382
002	U9091074	30-10-2019	28-10-2019	ALC382
003	U9091073	30-10-2019	28-10-2019	ALC382
004	U9096555	30-10-2019	28-10-2019	ALC382
005	U9091064	30-10-2019	28-10-2019	ALC382
006	U9091051	30-10-2019	28-10-2019	ALC382
007	U9096543	30-10-2019	28-10-2019	ALC382
008	U9096207	30-10-2019	28-10-2019	ALC382
009	U9091199	30-10-2019	28-10-2019	ALC382
010	U9091182	30-10-2019	28-10-2019	ALC382
011	U9091069	30-10-2019	28-10-2019	ALC382
012	U9091070	30-10-2019	29-10-2019	ALC382
013	U9091245	30-10-2019	28-10-2019	ALC382
014	U9091195	30-10-2019	28-10-2019	ALC382
015	U9096573	30-10-2019	29-10-2019	ALC382
016	U9092586	30-10-2019	29-10-2019	ALC382
017	U9096559	30-10-2019	29-10-2019	ALC382
018	U9092592	30-10-2019	29-10-2019	ALC382
019	U9091075	30-10-2019	29-10-2019	ALC382
020	U9091234	30-10-2019	29-10-2019	ALC382
021	U9096548	30-10-2019	29-10-2019	ALC382
022	U9091246	30-10-2019	29-10-2019	ALC382
023	U9091242	30-10-2019	29-10-2019	ALC382
024	U9091201	30-10-2019	29-10-2019	ALC382
025	U9096218	30-10-2019	29-10-2019	ALC382
026	U9091147	30-10-2019	29-10-2019	ALC382
027	U9096577	30-10-2019	29-10-2019	ALC382
028	U9091189	30-10-2019	29-10-2019	ALC382
029	U9096489	30-10-2019	29-10-2019	ALC382
030	U9091200	30-10-2019	29-10-2019	ALC382
031	U9092597	30-10-2019	29-10-2019	ALC382
032	U9091146	30-10-2019	29-10-2019	ALC382
033	U9091258	30-10-2019	29-10-2019	ALC382
034	U9096210	30-10-2019	29-10-2019	ALC382

Paraaf :

Projectnaam Uiterwaarden Demen-Dieden (PFAS)
Projectnummer SOB010398-A
Rapportnummer 13136554 - 1

Orderdatum 30-10-2019
Startdatum 30-10-2019
Rapportagedatum 18-11-2019

Monster	Barcode	Aanlevering	Monstername	Verpakking
035	U9091250	30-10-2019	29-10-2019	ALC382
036	U9092593	30-10-2019	29-10-2019	ALC382
037	U9092596	30-10-2019	29-10-2019	ALC382
038	U9092585	30-10-2019	29-10-2019	ALC382
039	U9096571	30-10-2019	29-10-2019	ALC382
040	U9091184	30-10-2019	29-10-2019	ALC382
041	U9091079	30-10-2019	28-10-2019	ALC382
042	U9096554	30-10-2019	28-10-2019	ALC382
043	U9096201	30-10-2019	28-10-2019	ALC382
044	U9091196	30-10-2019	28-10-2019	ALC382
045	U9091067	30-10-2019	28-10-2019	ALC382
046	U9091080	30-10-2019	28-10-2019	ALC382
047	U9096553	30-10-2019	28-10-2019	ALC382
048	U9096550	30-10-2019	28-10-2019	ALC382
049	U9096204	30-10-2019	28-10-2019	ALC382
050	U9096212	30-10-2019	28-10-2019	ALC382
051	U9096541	30-10-2019	28-10-2019	ALC382
052	U9096545	30-10-2019	28-10-2019	ALC382
053	U9091066	30-10-2019	28-10-2019	ALC382
054	U9096544	30-10-2019	28-10-2019	ALC382
055	U9096551	30-10-2019	28-10-2019	ALC382
056	U9096557	30-10-2019	28-10-2019	ALC382
057	U9091257	30-10-2019	28-10-2019	ALC382
058	U9091239	30-10-2019	28-10-2019	ALC382
059	U9091071	30-10-2019	28-10-2019	ALC382
060	U9091253	30-10-2019	28-10-2019	ALC382
061	U9091187	30-10-2019	29-10-2019	ALC382
062	U9096479	30-10-2019	29-10-2019	ALC382
063	U9096199	30-10-2019	29-10-2019	ALC382
064	U9096564	30-10-2019	29-10-2019	ALC382
065	U9096556	30-10-2019	29-10-2019	ALC382
066	U9096200	30-10-2019	29-10-2019	ALC382
067	U9091191	30-10-2019	29-10-2019	ALC382
068	U9096574	30-10-2019	29-10-2019	ALC382
069	U9096206	30-10-2019	29-10-2019	ALC382
070	U9096560	30-10-2019	29-10-2019	ALC382
071	U9096216	30-10-2019	29-10-2019	ALC382
072	U9096567	30-10-2019	29-10-2019	ALC382
073	U9091197	30-10-2019	29-10-2019	ALC382
074	U9091194	30-10-2019	29-10-2019	ALC382
075	U9091251	30-10-2019	29-10-2019	ALC382
076	U9091142	30-10-2019	29-10-2019	ALC382
077	U9091252	30-10-2019	29-10-2019	ALC382
078	U9091261	30-10-2019	29-10-2019	ALC382
079	U9091256	30-10-2019	29-10-2019	ALC382
080	U9096497	30-10-2019	29-10-2019	ALC382

Paraaf :



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485367

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-001) OZ-01-1 OZ-01-1 OZ-01 (0-50)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834045

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.12	± 0.10	ug/kg TS
Calculated	PFOS, total	0.45	± 0.14	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluotelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluotelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluotelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluotelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 3282 1603 5613 4268

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485368

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-002) OZ-01-2 OZ-01-2 OZ-01 (50-100)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832409

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	92.5	± 9.25	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradecacid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden

Accred. nr 1006
Proving
ISO/IEC 17025


REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485368

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-002) OZ-01-2 OZ-01-2 OZ-01 (50-100)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832409

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.5		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Comment

Increased reporting limit for N-MeFOSAA due to disturbances from other substances in the sample.

Linköping 2019-11-13

The report has been reviewed and approved by

Emil Johansson
Responsible reviewer

Control numbers 3188 1600 5912 4064

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485369

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-003) OZ-02-1 OZ-02-1 OZ-02 (0-50)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834494

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.12	± 0.10	ug/kg TS
Calculated	PFOS, total	0.44	± 0.13	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 3086 1602 5016 4366

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden


Ackred. nr 1006
Provning
ISO/IEC 17025


REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485370

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-004) OZ-02-2 OZ-02-2 OZ-02 (50-90)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832299

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	81.7	± 8.17	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485370

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-004) OZ-02-2 OZ-02-2 OZ-02 (50-90)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832299

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluoroceta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 2981 6104 5219 4765

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485371

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-005) OZ-03-1 OZ-03-1 OZ-03 (0-50)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834467

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	79.3	± 7.93	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	0.20	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	0.10	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.75	± 0.23	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	0.75	± 0.23	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	0.61	± 0.18	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485371

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-005) OZ-03-1 OZ-03-1 OZ-03 (0-50)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834467

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.15	± 0.10	ug/kg TS
Calculated	PFOS, total	0.76	± 0.23	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 2881 6801 5416 4366

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485372

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-006) OZ-03-2 OZ-03-2 OZ-03 (50-100)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834464

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	79.1	± 7.91	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.13	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	0.13	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorononanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485372

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-006) OZ-03-2 OZ-03-2 OZ-03 (50-100)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834464

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 2781 6106 5918 4661

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485373

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-007) OZ-04-1 OZ-04-1 OZ-04 (0-40)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834475

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	80.9	± 8.09	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	0.16	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.55	± 0.17	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	0.55	± 0.17	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	0.26	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485373

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-007) OZ-04-1 OZ-04-1 OZ-04 (0-40)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834475

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	0.26	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 2681 6206 5610 4863

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485374

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-008) OZ-04-2 OZ-04-2 OZ-04 (40-90)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87833438

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	81.4	± 8.14	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorononanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage k = 2. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485374

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-008) OZ-04-2 OZ-04-2 OZ-04 (40-90)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87833438

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 2581 6702 5610 4764

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485376

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-009) OZ-05-1 OZ-05-1 OZ-05 (0-40)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832228

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.11	± 0.10	ug/kg TS
Calculated	PFOS, total	0.67	± 0.20	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulfo. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 2381 6400 5912 4761

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 · Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485377

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-010) OZ-05-2 OZ-05-2 OZ-05 (40-80)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832225

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	85.1	± 8.51	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485377

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-010) OZ-05-2 OZ-05-2 OZ-05 (40-80)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832225

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 2281 6902 5819 4565

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden


Ackred. nr 1006
Provning
ISO/IEC 17025


REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485378

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-011) OZ-06-1 OZ-06-1 OZ-06 (0-50)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832000

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	82.7	± 8.27	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	0.15	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.78	± 0.23	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	0.78	± 0.23	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	0.39	± 0.12	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485378

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-011) OZ-06-1 OZ-06-1 OZ-06 (0-50)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832000

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	0.39	± 0.12	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.5		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Comment

Increased reporting limit for N-MeFOSAA due to disturbances from other substances in the sample.

Linköping 2019-11-13

The report has been reviewed and approved by

Emil Johansson
Responsible reviewer

Control numbers 2181 6007 5213 4868

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485379

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-012) OZ-06-2 OZ-06-2 OZ-06 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87833345

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	89.8	± 8.98	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradecacid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485379

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-012) OZ-06-2 OZ-06-2 OZ-06 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87833345

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 2081 6001 5617 4264

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485380

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-013) OZ-07-1 OZ-07-1 OZ-07 (0-50)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832115

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.11	± 0.10	ug/kg TS
Calculated	PFOS, total	0.63	± 0.19	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 1916 8909 5412 4963

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485381

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-014) OZ-07-2 OZ-07-2 OZ-07 (50-95)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832227

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	95.8	± 9.58	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485381

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-014) OZ-07-2 OZ-07-2 OZ-07 (50-95)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832227

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 1816 8803 5612 4463

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485382

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-015) OZ-08-1 OZ-08-1 OZ-08 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87833531

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.17	± 0.10	ug/kg TS
Calculated	PFOS, total	0.63	± 0.19	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 1716 8804 5817 4264

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485383

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-016) OZ-08-3 OZ-08-3 OZ-08 (65-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832590

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	96.2	± 9.62	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485383

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-016) OZ-08-3 OZ-08-3 OZ-08 (65-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832590

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 1616 8806 5310 4367

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485384

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-017) OZ-09-1 OZ-09-1 OZ-09 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87833717

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.16	± 0.10	ug/kg TS
Calculated	PFOS, total	0.72	± 0.22	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulfo. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 1516 8107 5519 4965

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485385

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-018) OZ-09-2 OZ-09-2 OZ-09 (50-90)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87831361

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	79.7	± 7.97	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.23	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	0.23	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485385

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-018) OZ-09-2 OZ-09-2 OZ-09 (50-90)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87831361

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.5		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.5		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Comment

Increased reporting limit for some PFAS due to disturbances from other substances in the sample.

Linköping 2019-11-13

The report has been reviewed and approved by

Emil Johansson
Responsible reviewer

Control numbers 1416 8704 5615 4261

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485386

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-019) OZ-10-1 OZ-10-1 OZ-10 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834154

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.18	± 0.10	ug/kg TS
Calculated	PFOS, total	0.63	± 0.19	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 1316 8707 5013 4866

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden


Ackred. nr 1006
Provning
ISO/IEC 17025


REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485387

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-020) OZ-10-2 OZ-10-2 OZ-10 (50-90)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834375

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	79.5	± 7.95	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.27	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	0.27	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	0.11	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485387

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-020) OZ-10-2 OZ-10-2 OZ-10 (50-90)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834375

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	0.11	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.5		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.5		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Comment

Increased reporting limit for some PFAS due to disturbances from other substances in the sample.

Linköping 2019-11-13

The report has been reviewed and approved by

Emil Johansson
Responsible reviewer

Control numbers 1216 8707 5718 4963

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden


Accred. nr 1006
Provning
ISO/IEC 17025


REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485388

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-021) OZ-11-1 OZ-11-1 OZ-11 (0-30)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834887

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	80.8	± 8.08	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.63	± 0.19	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	0.63	± 0.19	ug/kg TS
DIN 38414-14 mod.	Perfluorononanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	0.40	± 0.12	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage k = 2. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485388

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-021) OZ-11-1 OZ-11-1 OZ-11 (0-30)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834887

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.15	± 0.10	ug/kg TS
Calculated	PFOS, total	0.55	± 0.17	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 1116 8100 5810 4062

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485389

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-022) OZ-11-3 OZ-11-3 OZ-11 (80-115)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834835

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	86.1	± 8.61	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485389

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-022) OZ-11-3 OZ-11-3 OZ-11 (80-115)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834835

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 1016 8208 5713 4263

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485390

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-023) OZ-12-1 OZ-12-1 OZ-12 (0-40)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832262

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 0169 8604 5811 4663

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485391

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-024) OZ-12-3 OZ-12-3 OZ-12 (85-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834528

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 0168 8306 5312 4260

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485392

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-025) OZ-13-1 OZ-13-1 OZ-13 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834269

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	0.12	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 0167 8202 5910 4965

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485393

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-026) OZ-13-2 OZ-13-2 OZ-13 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834105

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	81.7	± 8.17	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	0.11	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage k = 2. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485393

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-026) OZ-13-2 OZ-13-2 OZ-13 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834105

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 0166 8903 5010 4263

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485394

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-027) OZ-14-1 OZ-14-1 OZ-14 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87831891

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	80.2	± 8.02	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	0.16	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.40	± 0.12	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	0.40	± 0.12	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	0.12	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485394

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-027) OZ-14-1 OZ-14-1 OZ-14 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87831891

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	0.12	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 0165 8403 5618 4269

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485395

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-028) OZ-14-2 OZ-14-2 OZ-14 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834714

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 0164 8007 5115 4664

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485397

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-029) OZ-15-1 OZ-15-1 OZ-15 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834864

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.22	± 0.10	ug/kg TS
Calculated	PFOS, total	0.64	± 0.19	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 0162 8308 5113 4768

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485398

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-030) OZ-15-2 OZ-15-2 OZ-15 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834806

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	0.19	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 0161 8205 5012 4464

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden


Ackred. nr 1006
Provning
ISO/IEC 17025


REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485399

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-031) OZ-16-1 OZ-16-1 OZ-16 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834465

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	74.9	± 7.49	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	0.24	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	0.30	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.84	± 0.25	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	0.11	± 0.10	ug/kg TS
Calculated	PFOA, total	0.95	± 0.29	ug/kg TS
DIN 38414-14 mod.	Perfluorononanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	0.40	± 0.12	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485399

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-031) OZ-16-1 OZ-16-1 OZ-16 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834465

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.12	± 0.10	ug/kg TS
Calculated	PFOS, total	0.52	± 0.16	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 0160 8200 5015 4060

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485400

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-032) OZ-16-2 OZ-16-2 OZ-16 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87833018

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	76.2	± 7.62	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485400

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-032) OZ-16-2 OZ-16-2 OZ-16 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87833018

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 9983 0250 1516 4256

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485401

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-033) OZ-17-1 OZ-17-1 OZ-17 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834244

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	76.3	± 7.63	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	0.28	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	0.13	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.60	± 0.18	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	0.60	± 0.18	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	0.10	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	0.65	± 0.20	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485401

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-033) OZ-17-1 OZ-17-1 OZ-17 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834244

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.11	± 0.10	ug/kg TS
Calculated	PFOS, total	0.76	± 0.23	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 9881 0852 1916 4252

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485402

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-034) OZ-17-2 OZ-17-2 OZ-17 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834473

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 9782 0255 1916 4252

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485403

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-035) OZ-18-1 OZ-18-1 OZ-18 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834470

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	78.5	± 7.85	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	0.38	± 0.11	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	0.11	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	0.22	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	0.11	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	0.96	± 0.29	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485403

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-035) OZ-18-1 OZ-18-1 OZ-18 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834470

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.96	± 0.29	ug/kg TS
Calculated	PFOS, total	1.9	± 0.57	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 9684 0850 1616 4251

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Proving

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485404

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-036) OZ-18-2 OZ-18-2 OZ-18 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834466

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	87.8	± 8.78	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	0.10	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.


SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025


REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485404
Assigner
SYNLAB Analytics & Services BV
Rotterdam
Steenhouwerstraat 15
3194AG ROTTERDAM, NL
Applies to
Sediment
Level 1 : Rotterdam Nautilus Order
Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-036) OZ-18-2 OZ-18-2 OZ-18 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834466

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.10	± 0.10	ug/kg TS
Calculated	PFOS, total	0.20	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 9581 0353 1916 4752

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485405

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-037) OZ-19-1 OZ-19-1 OZ-19 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87833158

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	78.6	± 7.86	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	0.20	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	0.11	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	0.12	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.72	± 0.22	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	0.10	± 0.10	ug/kg TS
Calculated	PFOA, total	0.82	± 0.25	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	1.5	± 0.45	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485405

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-037) OZ-19-1 OZ-19-1 OZ-19 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87833158

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.47	± 0.14	ug/kg TS
Calculated	PFOS, total	2.0	± 0.60	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 9488 0555 1716 4453

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485406

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-038) OZ-19-2 OZ-19-2 OZ-19 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834469

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	0.13	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 9385 0553 1916 4255

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485407

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-039) OZ-20-1 OZ-20-1 OZ-20 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834437

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	81.7	± 8.17	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	0.32	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.51	± 0.15	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	0.10	± 0.10	ug/kg TS
Calculated	PFOA, total	0.61	± 0.18	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	0.61	± 0.18	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage k = 2. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485407

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-039) OZ-20-1 OZ-20-1 OZ-20 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834437

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.29	± 0.10	ug/kg TS
Calculated	PFOS, total	0.90	± 0.27	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 9283 0453 1616 4558

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485408

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-040) OZ-20-2 OZ-20-2 OZ-20 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834301

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	0.17	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.5		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Comment

Increased reporting limit for N-MeFOSAA due to disturbances from other substances in the sample.

Linköping 2019-11-13

The report has been reviewed and approved by

Emil Johansson
Responsible reviewer

Control numbers 9186 0857 1816 4356

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485409

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-041) RV-01-1 RV-01-1 RV-01 (0-50)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834689

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	0.34	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulfo. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 9089 0856 1516 4452

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.


SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provnings
ISO/IEC 17025


REPORT

Page 1 (2)

issued by an Accredited Laboratory

Report No. 19485410
Assigner
**SYNLAB Analytics & Services BV
Rotterdam**
**Steenhouwerstraat 15
3194AG ROTTERDAM, NL**
Applies to
Sediment
Level 1 : Rotterdam Nautilus Order
Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-042) RV-01-2 RV-01-2 RV-01 (50-90)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834526

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	82.1	± 8.21	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	0.14	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.29	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	0.29	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorononanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTriDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) :Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB
Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 · Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

Page 2 (2)

issued by an Accredited Laboratory

Report No. 19485410

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-042) RV-01-2 RV-01-2 RV-01 (50-90)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834526

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluordecanoicsulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 8989 0557 1160 4051

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485411

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-043) RV-02-1 RV-02-1 RV-02 (0-50)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832235

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	75.6	± 7.56	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.52	± 0.16	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	0.52	± 0.16	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	0.40	± 0.12	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485411

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-043) RV-02-1 RV-02-1 RV-02 (0-50)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832235

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.11	± 0.10	ug/kg TS
Calculated	PFOS, total	0.51	± 0.15	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulfo. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.5		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.5		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Comment

Increased reporting limit for some PFAS due to disturbances from other substances in the sample.

Linköping 2019-11-13

The report has been reviewed and approved by

Emil Johansson
Responsible reviewer

Control numbers 8889 0459 1162 4459

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485412

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-044) RV-02-2 RV-02-2 RV-02 (50-100)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834722

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 8785 0459 1167 4454

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485413

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-045) RV-03-1 RV-03-1 RV-03 (0-50)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834592

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	0.34	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 8688 0755 1168 4855

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Proving

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485414

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-046) RV-03-2 RV-03-2 RV-03 (50-100)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834789

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	82.3	± 8.23	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485414

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-046) RV-03-2 RV-03-2 RV-03 (50-100)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834789

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 8582 0354 1163 4154

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485415

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-047) RV-04-1 RV-04-1 RV-04 (0-50)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834579

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	76.5	± 7.65	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	0.11	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.74	± 0.22	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	0.74	± 0.22	ug/kg TS
DIN 38414-14 mod.	Perfluorononanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	0.45	± 0.14	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage k = 2. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485415

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-047) RV-04-1 RV-04-1 RV-04 (0-50)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834579

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.14	± 0.10	ug/kg TS
Calculated	PFOS, total	0.59	± 0.18	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 8486 0958 1166 4359

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Proving

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485416

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-048) RV-04-2 RV-04-2 RV-04 (50-100)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834589

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	80.3	± 8.03	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485416

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-048) RV-04-2 RV-04-2 RV-04 (50-100)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834589

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluoroocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 8383 0752 1168 4353

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485418

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-049) RV-05-1 RV-05-1 RV-05 (0-50)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834739

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.10	± 0.10	ug/kg TS
Calculated	PFOS, total	0.57	± 0.17	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 8185 0355 1168 4258

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485419

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-050) RV-05-2 RV-05-2 RV-05 (50-100)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834606

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 8082 0856 1164 4659

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485420

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-051) RV-06-1 RV-06-1 RV-06 (0-50)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834521

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.11	± 0.10	ug/kg TS
Calculated	PFOS, total	0.56	± 0.17	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.5		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.5		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Comment

Increased reporting limit for some PFAS due to disturbances from other substances in the sample.

Linköping 2019-11-13

The report has been reviewed and approved by

Emil Johansson
Responsible reviewer

Control numbers 7986 0851 1610 4951

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485421

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-052) RV-06-2 RV-06-2 RV-06 (50-100)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834560

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	79.3	± 7.93	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage k = 2. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485421

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-052) RV-06-2 RV-06-2 RV-06 (50-100)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834560

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 7888 0950 1611 4357

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485422

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-053) RV-07-1 RV-07-1 RV-07 (0-50)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834512

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.11	± 0.10	ug/kg TS
Calculated	PFOS, total	0.50	± 0.15	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 7780 0856 1611 4551

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485423

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-054) RV-07-2 RV-07-2 RV-07 (50-100)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834556

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	-		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.5		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.5		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Comment

Increased reporting limit for some PFAS due to disturbances from other substances in the sample.

N-MeFOSAA is excluded due to disturbances from other substances in the sample.

Linköping 2019-11-13

The report has been reviewed and approved by

Emil Johansson
Responsible reviewer

Control numbers 7689 0657 1619 4857

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485424

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-055) RV-08-1 RV-08-1 RV-08 (0-40)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834300

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.35	± 0.11	ug/kg TS
Calculated	PFOS, total	0.70	± 0.21	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 7588 0558 1614 4950

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485425

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-056) RV-08-2 RV-08-2 RV-08 (40-90)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87833670

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	84.3	± 8.43	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.22	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	0.22	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradecacid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485425

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-056) RV-08-2 RV-08-2 RV-08 (40-90)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87833670

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.5		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.5		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Comment

Increased reporting limit for some PFAS due to disturbances from other substances in the sample.

Linköping 2019-11-13

The report has been reviewed and approved by

Emil Johansson
Responsible reviewer

Control numbers 7480 0657 1618 4451

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485426

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-057) RV-09-1 RV-09-1 RV-09 (0-45)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87833206

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	0.31	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulfo. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 7382 0555 1619 4250

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485427

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-058) RV-09-2 RV-09-2 RV-09 (45-95)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834450

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	83.4	± 8.34	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	0.14	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.21	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	0.21	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorononanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485427

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-058) RV-09-2 RV-09-2 RV-09 (45-95)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834450

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluoroceta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 7286 0356 1616 4558

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485428

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-059) RV-10-1 RV-10-1 RV-10 (0-30)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832224

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	0.46	± 0.14	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 7188 0353 1614 4956

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Proving

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485429

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-060) RV-10-3 RV-10-3 RV-10 (50-100)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834541

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	77.5	± 7.75	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage k = 2. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485429

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-060) RV-10-3 RV-10-3 RV-10 (50-100)
Sampling date : 2019-10-28
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834541

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 7086 0958 1611 4551

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 · Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485430

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-061) RV-11-1 RV-11-1 RV-11 (0-30)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832833

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	79.2	± 7.92	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	0.16	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485430

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-061) RV-11-1 RV-11-1 RV-11 (0-30)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87832833

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 6988 0251 6211 4754

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485431

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-062) RV-11-3 RV-11-3 RV-11 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834535

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 6885 0451 6515 4953

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Sample name : (13136554-063) RV-12-1 RV-12-1 RV-12 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834270

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485432

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-063) RV-12-1 RV-12-1 RV-12 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834270

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	0.26	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 6788 0451 6011 4759

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485433

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-064) RV-12-2 RV-12-2 RV-12 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834410

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	81.4	± 8.14	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorononanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485433

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-064) RV-12-2 RV-12-2 RV-12 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834410

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 6688 0051 6714 4054

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485434

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-065) RV-13-1 RV-13-1 RV-13 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87833856

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	79.0	± 7.90	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.14	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	0.14	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485434

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-065) RV-13-1 RV-13-1 RV-13 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87833856

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 6581 0151 6610 4558

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485435

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-066) RV-13-2 RV-13-2 RV-13 (50-100)
Sampling date : 2019-10-30
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87899161

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	88.8	± 8.88	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485435

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-066) RV-13-2 RV-13-2 RV-13 (50-100)
Sampling date : 2019-10-30
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87899161

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 6487 0651 6917 4455

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden


Ackred. nr 1006
Provning
ISO/IEC 17025


REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485436

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-067) RV-14-1 RV-14-1 RV-14 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87831188

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	78.2	± 7.82	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorononanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485436

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-067) RV-14-1 RV-14-1 RV-14 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87831188

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulfo. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 6389 0351 6813 4554

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485437

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-068) RV-14-2 RV-14-2 RV-14 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87831360

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 6289 0351 6714 4659

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485439

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-069) RV-15-1 RV-15-1 RV-15 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834468

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	80.3	± 8.03	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	0.16	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.72	± 0.22	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	0.72	± 0.22	ug/kg TS
DIN 38414-14 mod.	Perfluorononanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	0.28	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485439

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-069) RV-15-1 RV-15-1 RV-15 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834468

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.13	± 0.10	ug/kg TS
Calculated	PFOS, total	0.41	± 0.12	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 6082 0151 6614 4351

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 - Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provnings

ISO/IEC 17025



REPORT

Page 1 (2)

issued by an Accredited Laboratory

Report No. 19485440

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06

Time of Arrival : 1110

Temperature at arrival :

Sample name : (13136554-070) RV-15-2 RV-15-2 RV-15 (50-100)

Sampling date : 2019-10-29

Sampling time :

Sampler : -

Depth of sampling : -

Invoice reference : P91906

Label-id @mis : 87834451

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	80.4	± 8.04	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorononanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTriDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) :Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 · Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

Page 2 (2)

issued by an Accredited Laboratory

Report No. 19485440

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-070) RV-15-2 RV-15-2 RV-15 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834451

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluordecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulfo. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 5982 0416 5311 4053

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485441

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-071) RV-16-1 RV-16-1 RV-16 (0-20)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834911

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	74.5	± 7.45	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	0.24	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	1.3	± 0.39	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	0.21	± 0.10	ug/kg TS
Calculated	PFOA, total	1.5	± 0.45	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	0.37	± 0.11	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485441

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-071) RV-16-1 RV-16-1 RV-16 (0-20)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834911

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.24	± 0.10	ug/kg TS
Calculated	PFOS, total	0.61	± 0.18	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulfo. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 5884 0616 5315 4953

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485442

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-072) RV-16-3 RV-16-3 RV-16 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834693

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	78.4	± 7.84	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.15	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	0.15	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage k = 2. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485442

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-072) RV-16-3 RV-16-3 RV-16 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834693

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 5787 0516 5018 4254

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485443

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-073) RV-17-1 RV-17-1 RV-17 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834571

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.11	± 0.10	ug/kg TS
Calculated	PFOS, total	0.45	± 0.14	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluotelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluotelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluotelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluotelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 5684 0616 5015 4751

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 · Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485444

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-074) RV-17-2 RV-17-2 RV-17 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834822

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	80.9	± 8.09	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485444

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-074) RV-17-2 RV-17-2 RV-17 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834822

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 5588 0616 5416 4555

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485445

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-075) RV-18-1 RV-18-1 RV-18 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834538

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	81.1	± 8.11	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	0.30	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.11	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	0.11	± 0.10	ug/kg TS
Calculated	PFOA, total	0.22	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	0.62	± 0.19	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485445

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-075) RV-18-1 RV-18-1 RV-18 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834538

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.62	± 0.19	ug/kg TS
Calculated	PFOS, total	1.2	± 0.36	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluoroceta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 5489 0716 5814 4254

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485446

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-076) RV-18-2 RV-18-2 RV-18 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834696

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	0.14	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.5		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.5		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Comment

Increased reporting limit for some PFAS due to disturbances from other substances in the sample.

Linköping 2019-11-13

The report has been reviewed and approved by

Emil Johansson
Responsible reviewer

Control numbers 5381 0616 5315 4454

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.


SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akkred. nr 1006
Provnings
ISO/IEC 17025


REPORT

Page 1 (2)

issued by an Accredited Laboratory

Report No. 19485447
Assigner
**SYNLAB Analytics & Services BV
Rotterdam**
**Steenhouwerstraat 15
3194AG ROTTERDAM, NL**
Applies to
Sediment
Level 1 : Rotterdam Nautilus Order
Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-077) RV-19-1 RV-19-1 RV-19 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834718

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	80.4	± 8.04	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	0.20	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	0.13	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	0.80	± 0.24	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	0.80	± 0.24	ug/kg TS
DIN 38414-14 mod.	Perfluorononanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTrDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	0.33	± 0.10	ug/kg TS

(*) :Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB
Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 · Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

Page 2 (2)

issued by an Accredited Laboratory

Report No. 19485447

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-077) RV-19-1 RV-19-1 RV-19 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834718

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	0.13	± 0.10	ug/kg TS
Calculated	PFOS, total	0.46	± 0.14	ug/kg TS
DIN 38414-14 mod. (*)	Perfluordecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulfo. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 5288 0016 5918 4154

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Proving

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485448

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-078) RV-19-2 RV-19-2 RV-19 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834854

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	87.8	± 8.78	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485448

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-078) RV-19-2 RV-19-2 RV-19 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834854

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluoroocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 5182 0316 5017 4153

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485449

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-079) RV-20-1 RV-20-1 RV-20 (0-50)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834374

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	0.13	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 5087 0316 5011 4654

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden

Tel: + 46 13 254 900 · Fax: + 46 13 121 728

Registered 556152-0916 Registered office: Linköping, Sweden



Ackred. nr 1006

Provning

ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 1 (2)

Report No. 19485450

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-080) RV-20-2 RV-20-2 RV-20 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834449

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
SS-EN 12880	Dry substance	87.9	± 8.79	%
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, linear	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOA, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOA, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluornonanoic acid, PFNA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordecanoic acid, PFDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorundec. acid, PFUnDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluordodec. acid, PFDoDA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluortridec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluortetradec. acid, PFTeDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluorhexadec. acid, PFHxDA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	Perfluoroctadec. acid, PFODA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorbutanoic acid, PFBS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorpentanoic acid, PFPeS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorhexanoic acid, PFHxS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Perfluorheptanoic acid, PFHpS	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	PFOS, linear	< 0.1	± 0.10	ug/kg TS

(*) : Method not accredited by Swedac

PFOA = Perfluorooctane acid PFOS = Perfluorooctane sulfonate

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

(continued)

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.



SYNLAB Analytics & Services Sweden AB

Box 1083, 581 10 Linköping, Sweden
Tel: + 46 13 254 900 - Fax: + 46 13 121 728
Registered 556152-0916 Registered office: Linköping, Sweden



Akred. nr 1006
Provning
ISO/IEC 17025



REPORT

issued by an Accredited Laboratory

Page 2 (2)

Report No. 19485450

Assigner

SYNLAB Analytics & Services BV
Rotterdam

Steenhouwerstraat 15
3194AG ROTTERDAM, NL

Applies to

Sediment

Level 1 : Rotterdam Nautilus Order

Information about sample and sampling

Date of Arrival : 2019-11-06
Time of Arrival : 1110
Temperature at arrival :

Sample name : (13136554-080) RV-20-2 RV-20-2 RV-20 (50-100)
Sampling date : 2019-10-29
Sampling time :
Sampler : -
Depth of sampling : -
Invoice reference : P91906
Label-id @mis : 87834449

Results

Test method	Analysis / Investigation of	Result	Uncertainty	Unit
DIN 38414-14 mod.	PFOS, branched	< 0.1	± 0.10	ug/kg TS
Calculated	PFOS, total	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Perfluorodecanoic sulpho. PFDS	< 0.1		ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (4:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (6:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod.	Fluortelomersulfo. (8:2 FTS)	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	Fluortelomersulf. (10:2 FTS)	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	N-EtFOSAA	< 0.1		ug/kg TS
DIN 38414-14 mod.	Perfluorocta.sulp.amid,PFOSA	< 0.1	± 0.10	ug/kg TS
DIN 38414-14 mod. (*)	N-MeFOSA	< 0.1		ug/kg TS
DIN 38414-14 mod. (*)	8:2 diPAP	< 0.1		ug/kg TS

(*) :Method not accredited by Swedac

The stated uncertainty of measurement is calculated using a coverage $k = 2$. Measurement uncertainty for accredited microbiological analyses are available from the laboratory upon request.

Linköping 2019-11-12

The report has been reviewed and approved by

Patric Eklundh
Responsible reviewer

Control numbers 4985 0161 5714 4857

Results refer only to the submitted sample. Unless the laboratory has written otherwise, the report may only be reproduced in its entirety.

Bijlage 5 Begrippenlijst

Bagger(specie)

Baggerspecie is materiaal dat is vrijgekomen uit de bodem via het oppervlaktewater of de voor dat water bestemde ruimte en bestaat uit minerale delen met een maximale korrelgrootte van 2 millimeter en organisch stof in een verhouding en met een structuur zoals deze in de bodem van nature wordt aangetroffen, alsmede van nature in de bodem voorkomende schelpen en grind met een korrelgrootte van 2 tot 63 millimeter.

Baggerspecie die in het kader van het Besluit bodemkwaliteit nuttig wordt toegepast mag maximaal 20 gewichtsprocent aan bodemvreemd materiaal bevatten. De gemeente heeft voor het toepassen op of in de landbodem hiervoor strenger beleid vastgesteld.

Barium

Voor barium bestaat op dit moment geen norm. De destijds voor deze stof geldende normen zijn per 4 april 2009 (Staatscourant nr. 67, publicatie 7 april 2009) ingetrokken omdat de interventiewaarde lager was dan het gehalte dat van nature in de bodem voorkomt. Dit blijft gehandhaafd. De onderzoeksgegevens over barium moeten wel in de bodemkwaliteitskaarten worden meegenomen, aangezien barium onderdeel uitmaakt van het stoffenpakket, met dien verstande dat geen eisen worden gesteld aan het aantal waarnemingen. Deze gegevens kunnen namelijk een indicatie zijn voor de aanwezigheid van antropogene bronnen die ook andere verontreinigingen met zich mee kunnen brengen.

Als verhoogde bariumgehalten ten opzichte van de natuurlijke achtergrondwaarden worden aangetroffen als gevolg van een menselijke activiteit, kan dit gehalte worden beoordeeld op basis van de voormalige interventiewaarde voor barium: 920 mg/kg d.s. (bij standaardbodempluut 25%, organisch stof 10%).

Bodembeheergebied

Een aaneengesloten, door het bestuursorgaan (bijvoorbeeld een gemeente, waterschap of Rijkswaterstaat) afgebakend deel van de oppervlakte van een of meer gemeenten of het beheergebied van een of meer beheerders.

Bodemkwaliteitszone

Een deel van een bodembeheergebied waarvoor geldt dat er sprake is van een zelfde gebiedseigen bodemkwaliteit, waarbij zowel de verwachtingswaarde als de mate van variabiliteit van belang zijn. De spreiding van gehalten binnen een bodemkwaliteitszone is relatief laag. Een bodemkwaliteitszone is begrensd in het horizontale vlak én het verticale vlak (diepte). Wanneer een bodemkwaliteitszone uit meerdere gebieden bestaat die niet aan elkaar grenzen, worden de individuele gebieden aangeduid als 'niet-aaneengesloten bodemkwaliteitszone'.

Bijzondere omstandigheden

Voor een binnen een bodemkwaliteitszone liggend gebied geldt dat er sprake is van bijzondere omstandigheden, als er voor dat gebied een afwijkende verwachtingswaarde geldt ten opzichte van de verwachtingswaarde van de betreffende bodemkwaliteitszone. Te denken valt aan voor bodemverontreiniging verdachte locaties, onderzochte locaties, locaties waar een sanering


heeft plaatsgevonden of locaties met onvoorziene visuele waarnemingen (bodenvreemde materialen, kleur, geur). Ook beschermde gebieden zoals bijvoorbeeld voor de ecologie, archeologie, aardkundige waarden en cultuurhistorie vallen onder de bijzondere omstandigheden. In gebieden met bijzondere omstandigheden kunnen vanuit andere wet- en regelgeving aanvullende eisen worden gesteld.

Deelgebied

Deel van een bodembeheergebied waarvoor geldt dat dit op eenduidige wijze kan worden gekarakteriseerd door middel van de voor het bodembeheergebied geldende onderscheidende gebiedskenmerken. In tegenstelling tot de bodemkwaliteitszone is er voor het deelgebied nog geen toetsing uitgevoerd of het daadwerkelijk een bodemkwaliteitszone is. Wanneer een deelgebied uit meerdere terreinen bestaat die niet aan elkaar grenzen, worden de individuele gebieden aangeduid als 'niet-aaneengesloten deelgebieden'.

Diffuse chemische bodemkwaliteit

De diffuse chemische bodemkwaliteit in een bepaald gebied is de verdeling van gehalten van stoffen in dat gebied waarvoor de bodemkwaliteitskaart is vastgesteld. Deze verdeling kan worden gekwantificeerd door statistische parameters (gemiddelde, percentielwaarden).



Heterogeniteit

Wanneer de diffuse bodemverontreiniging in een zone zeer heterogeen is verdeeld, is de betrouwbaarheid van het gemiddelde gehalte in de zone ook kleiner. Bij zones met een hoge heterogeniteit kan de gemeente besluiten dat de bodemkwaliteitskaart in bepaalde situaties niet gebruikt mag worden als bewijsmiddel. Het vastgestelde gemiddelde gehalte heeft naar mening van de gemeente dan een te lage betrouwbaarheid. Een zekere heterogeniteit op zich hoeft overigens geen probleem te zijn zolang er geen sprake is van een gebruiksrisico. De heterogeniteit van een stof in een zone wordt bepaald door een index die volgt uit de volgende formule:

$$\text{heterogeniteit} = \frac{(P95 - P5)}{(\text{maximale waarde industrie} - \text{Achtergrondwaarde})}$$

De beoordeling van de heterogeniteitsindex is als volgt:

Index < 0,2	: weinig heterogeniteit
0,2 < Index < 0,5	: beperkte heterogeniteit
0,5 < Index < 0,7	: er is sprake van heterogeniteit
Index > 0,7	: sterke heterogeniteit

Interventiewaarde

Wanneer een gemeten gehalte hoger is dan de interventiewaarde uit de Wet bodembescherming wordt gesproken over een sterke verontreiniging of een sterk verhoogd gehalte. De interventiewaarden zijn vastgelegd in de Circulaire bodemsanering 2009, zoals gewijzigd op 1 juli 2013 (gepubliceerd in de Staatscourant nr. 16675, d.d. 27 juni 2013).

Lokale bron (puntbron)

Duidelijk aanwijsbare bron voor een eventuele bodemverontreiniging zoals bijvoorbeeld een ondergrondse tank voor de opslag van olie, een ontvettingsbad of een afleverzuil voor brandstof(fen).

PFAS-gehalten en effect op de kwaliteitsklassen

(Bron: <https://www.bodemplus.nl/onderwerpen/wet-regelgeving/bbk/vragen/grond-baggerspecie-pfas-veldwerk-analyse-toetsing/faq/resultaten-pfas-onderzoek-toetsen-aanvulling/>)

Op dit moment is de toetsing aan de PFAS-verbindingen een aanvullende (losse) toets ten opzichte van de toetsing op de reguliere parameters en indeling in kwaliteitsklassen. Dat betekent dat eerst de toetsing plaatsvindt op basis van de reguliere parameters en op basis daarvan een indeling in kwaliteitsklasse plaatsvindt.

Vervolgens vindt de toetsing aan de toepassingsnormen uit geactualiseerde tijdelijk handelingskader van 29 november 2019 voor de PFAS-verbindingen plaats. Aan de hand van de aanvullende toetsing stel je vervolgens vast in hoeverre beperkingen aan de toepassing gelden, bijvoorbeeld een verbod op het toepassen onder grondwatervlakte of in oppervlaktewater. Voor PFAS zijn de bijzondere toetsregels voor het toetsen aan de Achtergrondwaarde of maximale waarde wonen niet van toepassing, omdat nog geen normen zijn opgenomen in bijlage B van de Regeling bodemkwaliteit. Ook tellen de gemeten PFAS niet mee als gemeten stoffen bij de bijzondere toetsregels voor het toetsen aan de achtergrondwaarde of maximale waarde wonen.

Bij de inbouw van het handelingskader in de Regeling bodemkwaliteit wordt de wijze van toetsen aan normwaarden nader ingevuld.

Voorbeeld

Als een partij baggerspecie op basis van de overige stoffen is gekwalificeerd in de bodemkwaliteitsklasse A, dan moet aanvullend de PFAS-gehalten worden bepaald. Voldoen alle PFAS-gehalten aan de bepalingsgrens (0,1 µg/kg d.s.), dan blijft de indeling in de bodemkwaliteitsklasse A staan en gelden geen toepassingsvoorwaarden. Worden hogere PFAS-gehalten aangetoond, dan kan het zijn dat er toepassingsbeperkingen zijn afhankelijk van de locatie van toepassing en het gekozen toepassingskader. Bij het onder voorwaarden

toepassen van baggerspecie in niet-vrijliggende diepe plassen die in verbinding staan met een Rijkswater geldt het voorlopige herverontreinigingsniveau als toepassingsnorm voor PFAS (3,7 µg/kg ds voor PFOS en 0,8 µg/kg ds voor PFOA en de andere (individuele) PFAS).

Percentiel/percentielwaarde

Waarde waar beneden een bepaald percentage van de analyseresultaten gelegen is.

Bijvoorbeeld 80-percentiel: 80% van de analyseresultaten ligt beneden deze waarde.

Uitbijters

Een uitbijter is een gehalte in het gegevensbestand dat niet representatief is voor de diffuse chemische bodemkwaliteit in een deelgebied. De (potentiële) uitbijters worden met een visuele methode (scatterplots) inzichtelijk gemaakt. Het niet representatieve gehalte is het gevolg van duidelijk aantoonbare menselijke activiteiten: puntverontreinigingen, verdachte locaties, typfouten tijdens invoer.

Variatiecoëfficiënt

Maat voor de spreiding in gehalten (standaarddeviatie gedeeld door het gemiddelde).

Bijlage 6 Statistische parameters waterbodemkwaliteitszones

Statistische parameters, toetsing aan Besluit Bodemkwaliteit (Waterbodems)

* De norm voor Barium geldt alleen voor die situaties waarbij duidelijke sprake is van antropogene bodemverontreiniging. Voor overige situaties is de norm voor Barium tijdelijk buitenwerking gesteld.

** In verband met 1 of meer gemiddelde gehalten PFAS > 0,0001 mg/kg gelden mogelijk aanvullende toepassingseisen.

	waarde > max. waarde klasse B
	max. waarde klasse A < waarde < max. waarde klasse B
	achtergrondwaarde < waarde < max. waarde klasse A
	waarde < achtergrondwaarde (minimaal 1x >d gemeten)
	waarde < achtergrondwaarde (alleen <d gemeten)
	waarde > hergebruiksnorm conform § 4.8.2 en 4.9.2 uit het Tijdelijk Handelingskader PFAS (versie 29 november 2019) **
	waarde > hergebruiksnorm conform § 4.9.1 uit het Tijdelijk Handelingskader PFAS (versie 29 november 2019) **

Zone	Statistische parameters																Waterbodemkwaliteitsklasse:			Klasse B		Lut = 25,0 % OS = 10,0 %	
Gezoned:	ja																						
Stoffen	N	Min	5P	25P	50P	75P	80P	90P	95P	Max	80% MIN	Gem	80% MAX	VC	Hetero- geniteit	P95>I	achtergrond waarde	klasse A	klasse B / interventie- waarde				
Arseen	24	7,9	12,7	15,6	18,8	22,8	22,8	26,3	35,0	54,6	18,2	20,4	22,5	0,40	0,34	nee	20,00	29,00	85,0				
Barium*	24	67,8	87,9	125,7	134,4	152,0	156,6	195,2	288,1	526,0	135,2	155,6	175,9	0,50	n.v.t.	n.v.t.	190,00	n.v.t.	n.v.t.				
Cadmium	24	1,04	1,49	2,25	2,49	3,61	4,07	6,80	10,60	20,12	3,08	3,98	4,88	0,87	0,68	nee	0,60	4,00	14,0				
Chroom	24	23,1	26,5	36,8	44,5	49,7	51,8	56,0	57,9	73,6	41,0	43,7	46,5	0,24	0,10	nee	55,0	120,0	380,0				
Kobalt	24	9,2	11,4	15,1	16,8	20,0	20,9	21,7	23,1	23,2	16,5	17,3	18,2	0,19	0,05	nee	15,0	25,0	240,0				
Koper	24	22,3	26,3	37,5	46,9	51,5	57,6	98,9	154,3	234,3	49,0	59,7	70,4	0,68	0,85	nee	40,0	96,0	190,0				
Kwik	24	0,15	0,24	0,30	0,35	0,50	0,56	1,26	1,66	2,81	0,44	0,58	0,73	0,96	0,14	nee	0,15	1,20	10,0				
Lood	24	85,9	90,9	133,8	167,3	203,5	247,6	433,8	608,9	892,1	186,1	230,5	274,9	0,74	0,98	ja	50,0	138,0	580,0				
Molybdeen	24	1,05	1,05	1,05	1,05	1,05	1,05	1,05	1,05	1,05	n.v.t.	1,05	n.v.t.	0,00	0,00	nee	1,5	5,0	200,0				
Nikkel	24	19,5	23,3	33,0	37,8	42,4	43,8	47,8	50,1	51,6	35,4	37,3	39,2	0,20	0,15	nee	35,0	50,0	210,0				
Zink	24	244,8	262,3	431,3	495,4	644,0	787,9	1247,2	1777,5	2913,9	575,3	708,6	841,8	0,72	0,81	nee	140,0	563,0	2000,0				
PCB28	24	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0018	0,0024	0,0037	0,0013	0,0014	0,0015	0,23	n.v.t.	nee	0,0015	0,0140	n.v.t.				
PCB52	24	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	n.v.t.	0,0012	n.v.t.	0,00	n.v.t.	nee	0,0020	0,0150	n.v.t.				
PCB101	24	0,0012	0,0012	0,0012	0,0012	0,0020	0,0022	0,0034	0,0041	0,0047	0,0016	0,0018	0,0019	0,34	n.v.t.	nee	0,0015	0,0230	n.v.t.				
PCB118	24	0,0012	0,0012	0,0012	0,0012	0,0014	0,0019	0,0028	0,0035	0,0040	0,0015	0,0016	0,0017	0,29	n.v.t.	nee	0,0045	0,0160	n.v.t.				
PCB138	24	0,0012	0,0012	0,0012	0,0032	0,0050	0,0068	0,0101	0,0110	0,0139	0,0037	0,0042	0,0048	0,49	n.v.t.	nee	0,0040	0,0270	n.v.t.				
PCB153	24	0,0012	0,0013	0,0024	0,0035	0,0057	0,0066	0,0116	0,0141	0,0156	0,0045	0,0051	0,0057	0,45	n.v.t.	nee	0,0035	0,0330	n.v.t.				
PCB180	24	0,0012	0,0012	0,0021	0,0033	0,0053	0,0058	0,0105	0,0115	0,0121	0,0039	0,0044	0,0049	0,44	n.v.t.	nee	0,0025	0,0180	n.v.t.				
PCB (som 7)	24	0,0086	0,0088	0,0105	0,0147	0,0213	0,0256	0,0407	0,0474	0,0553	0,0177	0,0196	0,0216	0,38	0,04	nee	0,0200	0,1390	1,0				
PAK (som 10)	24	0,3	0,9	1,3	1,5	2,9	3,4	4,3	9,2	12,7	1,9	2,7	3,5	1,07	0,22	nee	1,5	9,0	40,0				
Minerale olie	24	43,0	43,0	43,0	43,0	43,0	50,4	75,6	159,2	386,0	55,2	66,1	77,1	0,63	0,02	nee	190,0	1250,0	5000,0				
Pentachloorbenzeen	24	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0018	0,0012	0,0012	0,0012	0,05	n.v.t.	n.v.t.	0,0025	0,0070	n.v.t.				
Hexachloorbenzeen	24	0,0012	0,0012	0,0012	0,0025	0,0039	0,0042	0,0059	0,0063	0,0068	0,0027	0,0030	0,0032	0,33	n.v.t.	n.v.t.	0,0085	0,0440	n.v.t.				
Pentachloorfenol	23	0,0037	0,0037	0,0037	0,0037	0,0037	0,0037	0,0037	0,0037	0,0037	n.v.t.	0,0037	n.v.t.	0,00	0,00	nee	0,0030	0,0160	5,0				
Chloordaan	24	0,0025	0,0025	0,0025	0,0025	0,0025	0,0025	0,0025	0,0025	0,0025	n.v.t.	0,0025	n.v.t.	0,00	0,00	nee	0,0020	n.v.t.	4,0				
DDT	24	0,0025	0,0025	0,0025	0,0025	0,0025	0,0025	0,0025	0,0025	0,0025	n.v.t.	0,0025	n.v.t.	0,00	n.v.t.	n.v.t.	0,2000	n.v.t.	n.v.t.				
DDD	24	0,0025	0,0025	0,0025	0,0025	0,0025	0,0025	0,0025	0,0025	0,0025	n.v.t.	0,0025	n.v.t.	0,00	n.v.t.	n.v.t.	0,0200	n.v.t.	n.v.t.				
DDE	24	0,0025	0,0025	0,0025	0,0025	0,0032	0,0033	0,0040	0,0042	0,0051	0,0029	0,0030	0,0031	0,14	n.v.t.	n.v.t.	0,1000	n.v.t.	n.v.t.				
DDT/DDD/DDE	24	0,0074	0,0074	0,0074	0,0074	0,0081	0,0082	0,0089	0,0091	0,0100	0,0078	0,0079	0,0080	0,05	n.v.t.	nee	0,3000	0,3000	4,0				
Aldrin	24	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	n.v.t.	0,0012	n.v.t.	0,00	n.v.t.	n.v.t.	0,0008	0,0013	n.v.t.				
Dieldrin	24	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	n.v.t.	0,0012	n.v.t.	0,00	n.v.t.	n.v.t.	0,0080	0,0080	n.v.t.				
Endrin	24	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	n.v.t.	0,0012	n.v.t.	0,00	n.v.t.	n.v.t.	0,0035	0,0035	n.v.t.				
Drins (som 3)	24	0,0037	0,0037	0,0037	0,0037	0,0037	0,0037	0,0037	0,0037	0,0037	n.v.t.	0,0037	n.v.t.	0,00	0,00	nee	0,0150	0,0150	4,0				
Isodrin	24	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	n.v.t.	0,0012	n.v.t.	0,00	n.v.t.	n.v.t.	0,0010	n.v.t.	n.v.t.				
Telodrin	24	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	n.v.t.	0,0012	n.v.t.	0,00	n.v.t.	n.v.t.	0,0005	n.v.t.	n.v.t.				
α-Endosulfan	24	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	n.v.t.	0,0012	n.v.t.	0,00	0,00	nee	0,0009	0,0021	4,0				
Endosulfansulfaat	24	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	n.v.t.	0,0012	n.v.t.	0,00	n.v.t.	n.v.t.	n.v.t.	n.v.t.	n.v.t.				
α-HCH	24	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	n.v.t.	0,0012	n.v.t.	0,00	n.v.t.	n.v.t.	0,0010	0,0012	n.v.t.				
β-HCH	24	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	n.v.t.	0,0012	n.v.t.	0,00	n.v.t.	n.v.t.	0,0020	0,0065	n.v.t.				
γ-HCH	24	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0039	0,0081	0,0421	0,0021	0,0033	0,0046	1,44	n.v.t.	n.v.t.	0,0030	0,0030	n.v.t.				
δ-HCH	24	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	n.v.t.	0,0012	n.v.t.	0,00	n.v.t.	n.v.t.	n.v.t.	n.v.t.	n.v.t.				
HCH (som 4)	24	0,0049	0,0049	0,0049	0,0049	0,0049	0,0049	0,0076	0,0118	0,0458	0,0058	0,0070	0,0083	0,68	0,00	nee	0,0100	0,0100	2,0				
Heptachloor	24	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	n.v.t.	0,0012	n.v.t.	0,00	0,00	nee	0,0007	0,0040	4,0				
Heptachloorepoxide	24	0,0025	0,0025	0,0025	0,0025	0,0025	0,0025	0,0025	0,0025	0,0025	n.v.t.	0,0025	n.v.t.	0,00	0,00	nee	0,0020	0,0040	4,0				
Hexachloorbutadieën	24	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0012	0,0018	0,0021	0,0012	0,0012	0,0013	0,10	n.v.t.	n.v.t.	0,0030	0,0075	n.v.t.				
OCB's (som)	24	0,0282	0,0282	0,0282	0,0285	0,0301	0,0305	0,0322	0,0352	0,0691	0,0298	0,0311	0,0323	0,15	n.v.t.	nee	0,4000	n.v.t.	n.v.t.				
Beoordeling PFAS																	Hergebruiksnormen						
																	Beperving type 1	Beperving type 2					
PFOA som lineair + vertakt	40	0,00010	0,00010	0,00038	0,00061	0,00074	0,00076	0,00082	0,00095	0,00150	0,00005	0,00057	0,00000	0,52	n.v.t.	n.v.t.	0,0001	0,0008					
PFOS som lineair + vertakt	40	0,00010	0,00010	0,00033	0,00051	0,00063	0,00068	0,00077	0,00124	0,00200	0,00005	0,00055	0,00000	0,74	n.v.t.	nee	0,0001	0,0037					
perfluoroctaanzuur (PFOA) lineair	40	0,00007	0,00007	0,00038	0,00060	0,00074	0,00075	0,00080	0,00086	0,00130	0,00005	0,00055	0,00000	0,51	n.v.t.	n.v.t.	0,0001	0,0008					
perfluoroctaanzuur (PFOA) vertakt	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00010	0,00011	0,00021	0,0001	0,00008	0,00000	0,31	n.v.t.	n.v.t.	0,0001	0,0008					
perfluorctaansulfonzuur (PFOS) lineair	40	0,00007	0,00007	0,00030	0,00039	0,00046	0,00053	0,00061	0,00067	0,00150	0,0004	0,00041	0,00000	0,63	n.v.t.	nee	0,0001	0,0037					
perfluorctaansulfonzuur (PFOS) vertakt	40	0,00007	0,00007	0,00007	0,00011	0,00015	0,00017	0,00030	0,00048	0,00096	0,0001	0,00016	0,00000	1,07	n.v.t.	nee	0,0001	0,0037					
perfluorbutaanzuur (PFBA)	40	0,00007	0,00007	0,00007	0,00016	0,00023	0,00024	0,00028	0,00030	0,00038	0,0001	0,00016	0,00000	0,53	n.v.t.	n.v.t.	0,0001	0,0008					
perfluorpentaanzuur (PFPeA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00011	0,0001	0,00007	0,00000	0,13	n.v.t.	n.v.t.	0,0001	0,0008					
perfluorhexaanzuur (PFHxA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00008	0,00013	0,00016	0,00030	0,0001	0,00009	0,00000	0,52	n.v.t.	n.v.t.	0,0001	0,0008					
perfluorheptaanzuur (PFHpA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00011	0,0001	0,00007	0,00000	0,09	n.v.t.	nee	0,0001	0,0008					
perfluornonaanzuur (PFNA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	n.v.t.	0,00007	n.v.t.	0,00	n.v.t.	n.v.t.	0,0001	0,0008					
perfluordecaanzuur (PFDeA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00010	0,0001	0,00007	0,00000	0,07	n.v.t.	n.v.t.	0,0001	0,0008					
perfluorundecaanzuur (PFUnDA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	n.v.t.	0,00007	n.v.t.	0,00	n.v.t.	n.v.t.	0,0001	0,0008					
perfluordodecaanzuur (PFDoDA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	n.v.t.	0,00007	n.v.t.	0,00	n.v.t.	nee	0,0001	0,0008					
perfluortridecaanzuur (PFTrDA)	40	0,00007	0,00007	0,00007	0,00007</																		

Statistische parameters, toetsing aan Besluit Bodemkwaliteit (Waterbodems)

* De norm voor Barium geldt alleen voor die situaties waarbij duidelijke sprake is van antropogene bodemverontreiniging. Voor overige situaties is de norm voor Barium tijdelijk buitenwerking gesteld.

** In verband met 1 of meer gemiddelde gehalten PFAS > 0,0001 mg/kg gelden mogelijk aanvullende toepassingseisen.

	waarde > max. waarde klasse B
	max. waarde klasse A < waarde < max. waarde klasse B
	achtergrondwaarde < waarde < max. waarde klasse A
	waarde < achtergrondwaarde (minimaal 1x >d gemeten)
	waarde < achtergrondwaarde (alleen <d gemeten)
	waarde > hergebruiksnorm conform § 4.8.2 en 4.9.2 uit het Tijdelijk Handelingskader PFAS (versie 29 november 2019) **
	waarde > hergebruiksnorm conform § 4.9.1 uit het Tijdelijk Handelingskader PFAS (versie 29 november 2019) **

Zone	Statistische parameters																Lut = 25,0 %					
Rivierlakte, toplaag (0 - 0,5 m-wb)	Waterbodembodemkwaliteitsklasse:																Klasse B			OS = 10,0 %		
Gezoneerd:	ja																					
Stoffen	N	Min	5P	25P	50P	75P	80P	90P	95P	Max	80% MIN	Gem	80% MAX	VC	Hetero- geniteit	P95>I	achtergrond waarde	klasse A	klasse B / interventie- waarde			
Arseen	27	9,5	11,6	15,8	18,9	23,6	24,2	27,9	31,9	36,8	18,5	20,1	21,6	0,31	0,31	nee	20,0	29,0	85,0			
Barium*	27	68,6	76,1	101,5	116,0	145,0	152,7	158,5	198,1	251,3	113,3	123,7	134,1	0,34	n.v.t.	n.v.t.	190,00	n.v.t.	n.v.t.			
Cadmium	27	0,38	1,10	1,75	2,03	4,17	5,00	6,42	8,48	10,59	2,61	3,17	3,72	0,71	0,55	nee	0,60	4,00	14,0			
Chroom	27	25,5	27,6	38,2	43,1	49,4	50,7	54,6	55,8	57,8	40,5	42,8	45,0	0,21	0,09	nee	55,0	120,0	380,0			
Kobalt	27	10,6	10,9	14,5	15,5	17,9	18,4	20,1	21,3	22,3	15,4	16,2	16,9	0,19	0,05	nee	15,0	25,0	240,0			
Koper	27	18,0	23,7	34,5	38,2	61,0	76,0	91,7	111,4	159,3	45,3	52,9	60,4	0,58	0,58	nee	40,0	96,0	190,0			
Kwik	27	0,04	0,14	0,21	0,29	0,58	0,63	0,95	1,26	1,42	0,36	0,45	0,53	0,79	0,11	nee	0,15	1,20	10,0			
Lood	27	57,4	89,9	125,1	146,0	292,0	327,4	431,7	568,3	636,1	188,5	225,4	262,2	0,66	0,90	nee	50,0	138,0	580,0			
Molybdeen	27	1,05	1,05	1,05	1,05	1,05	1,05	1,05	1,05	1,05	n.v.t.	1,05	n.v.t.	0,00	0,00	nee	1,5	5,0	200,0			
Nikkel	27	24,3	24,8	33,5	35,9	38,8	40,4	43,1	44,3	44,6	34,2	35,6	37,0	0,16	0,11	nee	35,0	50,0	210,0			
Zink	27	112,9	235,1	349,0	390,1	805,8	911,5	1147,6	1437,1	1745,1	489,9	589,6	689,4	0,69	0,65	nee	140,0	563,0	2000,0			
PCB28	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	n.v.t.	0,0013	n.v.t.	0,00	n.v.t.	nee	0,0015	0,0140	n.v.t.			
PCB52	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	n.v.t.	0,0013	n.v.t.	0,00	n.v.t.	nee	0,0020	0,0150	n.v.t.			
PCB101	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0020	0,0013	0,0013	0,0013	0,06	n.v.t.	nee	0,0015	0,0230	n.v.t.			
PCB118	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	n.v.t.	0,0013	n.v.t.	0,00	n.v.t.	nee	0,0045	0,0160	n.v.t.			
PCB138	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0023	0,0024	0,0026	0,0014	0,0015	0,0015	0,15	n.v.t.	nee	0,0040	0,0270	n.v.t.			
PCB153	27	0,0013	0,0013	0,0013	0,0013	0,0025	0,0026	0,0036	0,0041	0,0044	0,0019	0,0020	0,0022	0,28	n.v.t.	nee	0,0035	0,0330	n.v.t.			
PCB180	27	0,0013	0,0013	0,0013	0,0013	0,0020	0,0023	0,0030	0,0031	0,0039	0,0017	0,0018	0,0019	0,23	n.v.t.	nee	0,0025	0,0180	n.v.t.			
PCB (som 7)	27	0,0090	0,0090	0,0090	0,0090	0,0108	0,0113	0,0140	0,0147	0,0165	0,0102	0,0105	0,0108	0,12	0,01	nee	0,0200	0,1390	1,0			
PAK (som 10)	27	0,2	0,3	0,7	1,0	2,1	2,5	3,2	4,4	6,7	1,2	1,6	2,0	0,94	0,11	nee	1,5	9,0	40,0			
Minerale olie	27	45,0	45,0	45,0	45,0	45,0	45,0	54,2	107,9	150,7	49,4	52,8	56,1	0,26	0,01	nee	190,0	1250,0	5000,0			
Pentachloorbenzeen	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	n.v.t.	0,0013	n.v.t.	0,00	n.v.t.	n.v.t.	0,0025	0,0070	n.v.t.			
Hexachloorbenzeen	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0019	0,0024	0,0030	0,0035	0,0016	0,0017	0,0017	0,20	n.v.t.	n.v.t.	0,0085	0,0440	n.v.t.			
Pentachloorfenol	27	0,0039	0,0039	0,0039	0,0039	0,0039	0,0039	0,0039	0,0039	0,0039	n.v.t.	0,0039	n.v.t.	0,00	0,00	nee	0,0030	0,0160	5,0			
Chloordaan	27	0,0026	0,0026	0,0026	0,0026	0,0026	0,0026	0,0026	0,0026	0,0026	n.v.t.	0,0026	n.v.t.	0,00	0,00	nee	0,0020	n.v.t.	4,0			
DDT	27	0,0026	0,0026	0,0026	0,0026	0,0026	0,0026	0,0026	0,0026	0,0026	n.v.t.	0,0026	n.v.t.	0,00	n.v.t.	n.v.t.	0,2000	n.v.t.	n.v.t.			
DDD	27	0,0026	0,0026	0,0026	0,0026	0,0026	0,0026	0,0026	0,0026	0,0026	n.v.t.	0,0026	n.v.t.	0,00	n.v.t.	n.v.t.	0,0200	n.v.t.	n.v.t.			
DDE	27	0,0026	0,0026	0,0026	0,0026	0,0026	0,0026	0,0035	0,0039	0,0050	0,0027	0,0028	0,0028	0,11	n.v.t.	n.v.t.	0,1000	n.v.t.	n.v.t.			
DDT/DDD/DDE	27	0,0077	0,0077	0,0077	0,0077	0,0077	0,0077	0,0086	0,0091	0,0101	0,0078	0,0079	0,0080	0,04	n.v.t.	nee	0,3000	0,3000	4,0			
Aldrin	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	n.v.t.	0,0013	n.v.t.	0,00	n.v.t.	n.v.t.	0,0008	0,0013	n.v.t.			
Dieldrin	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	n.v.t.	0,0013	n.v.t.	0,00	n.v.t.	n.v.t.	0,0080	0,0080	n.v.t.			
Endrin	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	n.v.t.	0,0013	n.v.t.	0,00	n.v.t.	n.v.t.	0,0035	0,0035	n.v.t.			
Drins (som 3)	27	0,0039	0,0039	0,0039	0,0039	0,0039	0,0039	0,0039	0,0039	0,0039	n.v.t.	0,0039	n.v.t.	0,00	0,00	nee	0,0150	0,0150	4,0			
Isodrin	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	n.v.t.	0,0013	n.v.t.	0,00	n.v.t.	n.v.t.	0,0010	n.v.t.	n.v.t.			
Telodrin	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	n.v.t.	0,0013	n.v.t.	0,00	n.v.t.	n.v.t.	0,0005	n.v.t.	n.v.t.			
α-Endosulfan	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	n.v.t.	0,0013	n.v.t.	0,00	0,00	nee	0,0009	0,0021	4,0			
Endosulfansulfaat	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	n.v.t.	0,0013	n.v.t.	0,00	n.v.t.	n.v.t.	n.v.t.	n.v.t.	n.v.t.			
α-HCH	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	n.v.t.	0,0013	n.v.t.	0,00	n.v.t.	n.v.t.	0,0010	0,0012	n.v.t.			
β-HCH	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	n.v.t.	0,0013	n.v.t.	0,00	n.v.t.	n.v.t.	0,0020	0,0065	n.v.t.			
γ-HCH	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0036	0,0049	0,0064	0,0081	0,0019	0,0022	0,0025	0,48	n.v.t.	n.v.t.	0,0030	0,0030	n.v.t.			
δ-HCH	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	n.v.t.	0,0013	n.v.t.	0,00	n.v.t.	n.v.t.	n.v.t.	n.v.t.	n.v.t.			
HCH (som 4)	27	0,0051	0,0051	0,0051	0,0051	0,0051	0,0075	0,0087	0,0102	0,0119	0,0058	0,0061	0,0063	0,17	0,00	nee	0,0100	0,0100	2,0			
Heptachloor	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	n.v.t.	0,0013	n.v.t.	0,00	0,00	nee	0,0007	0,0040	4,0			
Heptachloorepoxide	27	0,0026	0,0026	0,0026	0,0026	0,0026	0,0026	0,0026	0,0026	0,0026	n.v.t.	0,0026	n.v.t.	0,00	0,00	nee	0,0020	0,0040	4,0			
Hexachloorbutadieën	27	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	0,0013	n.v.t.	0,0013	n.v.t.	0,00	n.v.t.	n.v.t.	0,0030	0,0075	n.v.t.			
OCB's (som)	27	0,0296	0,0296	0,0296	0,0296	0,0303	0,0322	0,0341	0,0359	0,0375	0,0304	0,0307	0,0310	0,04	n.v.t.	nee	0,4000	n.v.t.	n.v.t.			
Beoordeling PFAS																	Hergebruiksnormen					
																	Beperking type 1	Beperking type 2				
PFOA som lineair + vertakt	40	0,00010	0,00010	0,00038	0,00061	0,00074	0,00076	0,00082	0,00095	0,00150	0,00005	0,00057	0,00000	0,52	n.v.t.	n.v.t.	0,0001	0,0008				
PFOS som lineair + vertakt	40	0,00010	0,00010	0,00033	0,00051	0,00063	0,00068	0,00077	0,00124	0,00200	0,00005	0,00055	0,00000	0,74	n.v.t.	nee	0,0001	0,0037				
perfluoroctaanzuur (PFOA) lineair	40	0,00007	0,00007	0,00038	0,00060	0,00074	0,00075	0,00080	0,00086	0,00130	0,00005	0,00055	0,00000	0,51	n.v.t.	n.v.t.	0,0001	0,0008				
perfluoroctaanzuur (PFOA) vertakt	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00010	0,00011	0,00021	0,0001	0,00008	0,00000	0,31	n.v.t.	n.v.t.	0,0001	0,0008				
perfluorctaansulfonzuur (PFOS) lineair	40	0,00007	0,00007	0,00030	0,00039	0,00046	0,00053	0,00061	0,00067	0,00150	0,0004	0,00041	0,00000	0,63	n.v.t.	nee	0,0001	0,0037				
perfluorctaansulfonzuur (PFOS) vertakt	40	0,00007	0,00007	0,00007	0,00011	0,00015	0,00017	0,00030	0,00048	0,00096	0,0001	0,00016	0,00000	1,07	n.v.t.	nee	0,0001	0,0037				
perfluorbutaanzuur (PFBA)	40	0,00007	0,00007	0,00007	0,00016	0,00023	0,00024	0,00028	0,00030	0,00038	0,0001	0,00016	0,00000	0,53	n.v.t.	n.v.t.	0,0001	0,0008				
perfluorpentaanzuur (PFPeA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00011	0,0001	0,00007	0,00000	0,13	n.v.t.	n.v.t.	0,0001	0,0008				
perfluorhexaanzuur (PFHxA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00008	0,00013	0,00016	0,00030	0,0001	0,00009	0,00000	0,52	n.v.t.	n.v.t.	0,0001	0,0008				
perfluorheptaanzuur (PFHpA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00011	0,0001	0,00007	0,00000	0,09	n.v.t.	nee	0,0001	0,0008				
perfluorononaanzuur (PFNA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	n.v.t.	0,00007	n.v.t.	0,00	n.v.t.	n.v.t.	0,0001	0,0008				
perfluordecaanzuur (PFDeA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00010	0,0001	0,00007	0,00000	0,07	n.v.t.	n.v.t.	0,0001	0,0008				
perfluorundecaanzuur (PFUnDA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	n.v.t.	0,00007	n.v.t.	0,00	n.v.t.	n.v.t.	0,0001	0,0008				
perfluordodecaanzuur (PFDoDA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	n.v.t.	0,00007	n.v.t.	0,00	n.v.t.	nee	0,0001	0,0008				
perfluortridecaanzuur (PFTrDA)																						

Statistische parameters, toetsing aan Besluit Bodemkwaliteit (Waterbodems)

* De norm voor Barium geldt alleen voor die situaties waarbij duidelijke sprake is van antropogene bodemverontreiniging. Voor overige situaties is de norm voor Barium tijdelijk buitenwerking gesteld.

** In verband met 1 of meer gemiddelde gehalten PFAS > 0,0001 mg/kg gelden mogelijk aanvullende toepassingseisen.

	waarde > max. waarde klasse B
	max. waarde klasse A < waarde < max. waarde klasse B
	achtergrondwaarde < waarde < max. waarde klasse A
	waarde < achtergrondwaarde (minimaal 1x >d gemeten)
	waarde < achtergrondwaarde (alleen <d gemeten)
	waarde > hergebruiksnorm conform § 4.8.2 en 4.9.2 uit het Tijdelijk Handelingskader PFAS (versie 29 november 2019) **
	waarde > hergebruiksnorm conform § 4.9.1 uit het Tijdelijk Handelingskader PFAS (versie 29 november 2019) **

Zone	Statistische parameters																Lut = 25,0 %					
Klei, tussenlaag (0,5 - 1,0 m-wb)	Waterbodemkwaliteitsklasse:																Klasse A			OS = 10,0 %		
Gezoneerd:	ja																					
Stoffen	N	Min	5P	25P	50P	75P	80P	90P	95P	Max	80% MIN	Gem	80% MAX	VC	Hetero- geniteit	P95> I	achtergrond waarde	klasse A	klasse B / interventie- waarde			
Arseen	27	5,7	7,5	9,9	11,7	14,8	14,8	19,5	21,9	35,9	12,0	13,2	14,4	0,37	0,22	nee	20,0	29,0	85,0			
Barium*	27	57,9	70,9	84,4	100,7	115,8	119,1	138,5	147,3	327,4	99,2	108,8	118,4	0,36	n.v.t.	n.v.t.	190,00	n.v.t.	n.v.t.			
Cadmium	27	0,19	0,22	0,39	0,63	0,94	1,04	1,21	2,17	9,82	0,72	1,05	1,38	1,29	0,15	nee	0,60	4,00	14,0			
Chroom	27	20,6	23,3	29,8	34,4	41,8	43,3	47,7	52,0	59,6	34,0	36,0	38,0	0,23	0,09	nee	55,0	120,0	380,0			
Kobalt	27	10,4	11,4	13,7	15,0	18,1	18,7	21,2	22,1	23,7	15,4	16,1	16,8	0,17	0,05	nee	15,0	25,0	240,0			
Koper	27	9,8	13,4	19,5	20,8	24,1	24,7	28,9	36,7	156,0	21,2	26,3	31,3	0,78	0,16	nee	40,0	96,0	190,0			
Kwik	27	0,04	0,04	0,04	0,07	0,11	0,11	0,14	0,32	1,81	0,07	0,15	0,22	0,04	0,03	nee	0,15	1,20	10,0			
Lood	27	27,5	35,0	49,0	63,3	72,3	80,5	95,3	349,0	669,1	69,8	98,3	126,8	1,17	0,59	nee	50,0	138,0	580,0			
Molybdeen	27	1,05	1,05	1,05	1,05	1,05	1,05	1,05	1,05	n.v.t.	n.v.t.	1,05	n.v.t.	0,00	0,00	nee	1,5	5,0	200,0			
Nikkel	27	20,8	24,3	31,2	34,2	40,4	40,4	47,5	51,5	52,6	34,2	35,8	37,4	0,18	0,16	nee	35,0	50,0	210,0			
Zink	27	80,4	84,7	124,5	166,0	242,6	265,6	301,4	618,0	2043,1	192,6	265,6	338,6	1,11	0,29	nee	140,0	563,0	2000,0			
PCB28	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	nee	0,0015	0,0140	n.v.t.			
PCB52	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	nee	0,0020	0,0150	n.v.t.			
PCB101	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	nee	0,0015	0,0230	n.v.t.			
PCB118	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	nee	0,0045	0,0160	n.v.t.			
PCB138	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	nee	0,0040	0,0270	n.v.t.			
PCB153	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	nee	0,0035	0,0330	n.v.t.			
PCB180	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	nee	0,0025	0,0180	n.v.t.			
PCB (som 7)	27	0,0194	0,0194	0,0194	0,0194	0,0194	0,0194	0,0194	0,0194	0,0194	n.v.t.	0,0194	n.v.t.	0,00	0,00	nee	0,0200	0,1390	1,0			
PAK (som 10)	27	0,2	0,2	0,2	0,2	0,2	0,2	0,3	0,9	10,0	0,1	0,6	1,1	3,14	0,02	nee	1,5	9,0	40,0			
Minerale olie	27	97,1	97,1	97,1	97,1	97,1	97,1	97,1	97,1	475,8	106,5	111,0	115,5	0,17	0,00	nee	190,0	1250,0	5000,0			
Pentachloorbenzeen	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0025	0,0070	n.v.t.			
Hexachloorbenzeen	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0052	0,0027	0,0028	0,0028	0,04	n.v.t.	n.v.t.	0,0085	0,0440	n.v.t.			
Pentachloorfenol	27	0,0083	0,0083	0,0083	0,0083	0,0083	0,0083	0,0083	0,0083	0,0083	n.v.t.	0,0083	n.v.t.	0,00	0,00	nee	0,0030	0,0160	5,0			
Chlooraan	27	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	n.v.t.	0,0056	n.v.t.	0,00	0,00	nee	0,0020	n.v.t.	4,0			
DDT	27	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	n.v.t.	0,0056	n.v.t.	0,00	n.v.t.	n.v.t.	0,2000	n.v.t.	n.v.t.			
DDD	27	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	n.v.t.	0,0056	n.v.t.	0,00	n.v.t.	n.v.t.	0,0200	n.v.t.	n.v.t.			
DDE	27	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	n.v.t.	0,0056	n.v.t.	0,00	n.v.t.	n.v.t.	0,1000	n.v.t.	n.v.t.			
DDT/DDD/DDE	27	0,0167	0,0167	0,0167	0,0167	0,0167	0,0167	0,0167	0,0167	0,0167	n.v.t.	0,0167	n.v.t.	0,00	n.v.t.	nee	0,3000	0,3000	4,0			
Aldrin	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0008	0,0013	n.v.t.			
Dieldrin	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0080	0,0080	n.v.t.			
Endrin	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0035	0,0035	n.v.t.			
Drins (som 3)	27	0,0083	0,0083	0,0083	0,0083	0,0083	0,0083	0,0083	0,0083	0,0083	n.v.t.	0,0083	n.v.t.	0,00	0,00	nee	0,0150	0,0150	4,0			
Isodrin	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0010	n.v.t.	n.v.t.			
Telodrin	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0005	n.v.t.	n.v.t.			
α-Endosulfan	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	0,00	nee	0,0009	0,0021	4,0			
Endosulfansulfaat	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	n.v.t.	n.v.t.	n.v.t.			
α-HCH	26	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0010	0,0012	n.v.t.			
β-HCH	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0020	0,0065	n.v.t.			
γ-HCH	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0030	0,0030	n.v.t.			
δ-HCH	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	n.v.t.	n.v.t.	n.v.t.			
HCH (som 4)	26	0,0111	0,0111	0,0111	0,0111	0,0111	0,0111	0,0111	0,0111	0,0111	n.v.t.	0,0111	n.v.t.	0,00	0,00	nee	0,0100	0,0100	2,0			
Heptachloor	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	0,00	nee	0,0007	0,0040	4,0			
Heptachloorepoxide	27	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	n.v.t.	0,0056	n.v.t.	0,00	0,00	nee	0,0020	0,0040	4,0			
Hexachloorbutadieën	27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0030	0,0075	n.v.t.			
OCB's (som)	27	0,0638	0,0638	0,0638	0,0638	0,0638	0,0638	0,0638	0,0638	0,0793	0,0640	0,0642	0,0644	0,01	n.v.t.	nee	0,4000	n.v.t.	n.v.t.			
Beoordeling PFAS																	Hergebruiksnormen					
																	Beperving type 1	Beperving type 2				
PFOA som lineair + vertakt	40	0,00010	0,00010	0,00010	0,00010	0,00016	0,00019	0,00022	0,00025	0,00029	0,0001	0,00013	0,0000	0,43	n.v.t.	n.v.t.	0,0001	0,0008				
PFOS som lineair + vertakt	40	0,00010	0,00010	0,00010	0,00010	0,00010	0,00010	0,00013	0,00017	0,00020	0,0001	0,00011	0,0000	0,57	n.v.t.	nee	0,0001	0,0037				
perfluoroctaanzuur (PFOA) lineair	40	0,00007	0,00007	0,00007	0,00007	0,00016	0,00019	0,00022	0,00025	0,00029	0,0001	0,00012	0,0000	0,22	n.v.t.	n.v.t.	0,0001	0,0008				
perfluoroctaanzuur (PFOA) vertakt	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	n.v.t.	0,00007	n.v.t.	0,00	n.v.t.	n.v.t.	0,0001	0,0008				
perfluorctaansulfonzuur (PFOS) lineair	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00011	0,00014	0,00019	0,0001	0,00008	0,0000	0,35	n.v.t.	nee	0,0001	0,0037				
perfluorctaansulfonzuur (PFOS) vertakt	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00010	0,00010	0,0001	0,00007	0,0000	0,07	n.v.t.	nee	0,0001	0,0037				
perfluorbutaanzuur (PFBA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00013	0,00014	0,0001	0,00008	0,0000	0,23	n.v.t.	n.v.t.	0,0001	0,0008				
perfluorpentaanzuur (PFPeA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	n.v.t.	0,00007	n.v.t.	0,00	n.v.t.	n.v.t.	0,0001	0,0008				
perfluorhexaanzuur (PFHxA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	n.v.t.	0,00007	n.v.t.	0,00	n.v.t.	n.v.t.	0,0001	0,0008				
perfluorheptaanzuur (PFHpA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	n.v.t.	0,00007	n.v.t.	0,00	n.v.t.	nee	0,0001	0,0008				
perfluornonaanzuur (PFNA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	n.v.t.	0,00007	n.v.t.	0,00	n.v.t.	n.v.t.	0,0001	0,0008				
perfluordecaanzuur (PFDeA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	n.v.t.	0,00007	n.v.t.	0,00	n.v.t.	n.v.t.	0,0001	0,0008				
perfluorundecaanzuur (PFUnDA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	n.v.t.	0,00007	n.v.t.	0,00	n.v.t.	n.v.t.	0,0001	0,0008				
perfluordodecaanzuur (PFDoDA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	n.v.t.	0,00007	n.v.t.	0,00	n.v.t.	nee	0,0001	0,0008				
perfluortridecaanzuur (PFTrDA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	n.v.t.	0,00007	n.v.t.	0,00	n.v.t.	n.v.t.	0,00					

Statistische parameters, toetsing aan Besluit Bodemkwaliteit (Waterbodems)

* De norm voor Barium geldt alleen voor die situaties waarbij duidelijke sprake is van antropogene bodemverontreiniging. Voor overige situaties is de norm voor Barium tijdelijk buitenwerking gesteld.
 ** In verband met 1 of meer gemiddelde gehalten PFAS > 0,0001 mg/kg gelden mogelijk aanvullende toepassingseisen.

	waarde > max. waarde klasse B
	max. waarde klasse A < waarde < max. waarde klasse B
	achtergrondwaarde < waarde < max. waarde klasse A
	waarde < achtergrondwaarde (minimaal 1x >d gemeten)
	waarde < achtergrondwaarde (alleen <d gemeten)
	waarde > hergebruiksnorm conform § 4.8.2 en 4.9.2 uit het Tijdelijk Handelingskader PFAS (versie 29 november 2019) **
	waarde > hergebruiksnorm conform § 4.9.1 uit het Tijdelijk Handelingskader PFAS (versie 29 november 2019) **

Statistische parameters																		
Zand, tussenlaag (0,5 - 1,0 m-wb)																		
Gezoneerd: ja																		
	N	Min	5P	25P	50P	75P	80P	90P	95P	Max	80% MIN	Gem	80% MAX	VC	Hetero- geniteit	P95> I		
Stoffen	N	Min	5P	25P	50P	75P	80P	90P	95P	Max	80% MIN	Gem	80% MAX	VC	Hetero- geniteit	P95> I	achtergrond waarde	
Arseen	31	4,7	4,7	4,7	4,7	8,2	8,6	12,2	14,9	33,8	6,6	7,4	8,2	0,46	0,16	nee	20,0	
Barium*	31	46,3	46,3	46,3	46,3	56,2	86,0	109,1	163,7	529,1	70,5	76,7	83,0	0,35	n.v.t.	n.v.t.	190,00	
Cadmium	31	0,24	0,24	0,24	0,24	0,24	0,24	0,24	0,62	2,35	8,41	0,45	0,66	0,87	1,39	0,16	0,60	
Chroom	31	12,3	12,3	12,3	12,3	19,4	22,9	28,2	30,0	67,0	15,8	17,3	18,7	0,36	0,05	nee	55,0	
Kobalt	31	6,1	7,0	10,4	11,9	17,3	19,3	22,0	24,1	33,6	13,6	14,1	14,5	0,14	0,08	nee	15,0	
Koper	31	6,9	6,9	6,9	6,9	9,9	9,9	14,6	34,5	236,6	11,9	16,8	21,6	1,25	0,18	nee	40,0	
Kwik	31	0,05	0,05	0,05	0,05	0,05	0,05	0,05	0,22	1,83	0,06	0,11	0,16	2,03	0,02	nee	0,15	
Lood	31	10,7	10,7	10,7	10,7	14,6	19,9	47,5	124,2	552,0	23,2	38,3	53,3	1,71	0,21	nee	50,0	
Molybdeen	31	1,05	1,05	1,05	1,05	1,05	1,05	1,05	1,05	n.v.t.	1,05	n.v.t.	n.v.t.	0,00	0,00	nee	1,5	
Nikkel	31	12,6	14,4	18,3	24,3	31,4	34,0	39,3	43,2	55,0	25,0	25,9	26,8	0,15	0,16	nee	35,0	
Zink	31	31,0	31,0	37,6	59,8	89,7	97,4	194,9	708,7	2214,7	132,1	175,6	219,2	1,08	0,36	nee	140,0	
PCB28	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	nee	0,0015	
PCB52	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	nee	0,0020	
PCB101	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	nee	0,0015	
PCB118	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	nee	0,0045	
PCB138	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	nee	0,0040	
PCB153	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	nee	0,0035	
PCB180	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	nee	0,0025	
PCB (som 7)	31	0,0238	0,0238	0,0238	0,0238	0,0238	0,0238	0,0238	0,0238	0,0238	n.v.t.	0,0238	n.v.t.	0,00	0,00	nee	0,0200	
PAK (som 10)	31	0,2	0,2	0,2	0,2	0,2	0,2	0,2	1,1	4,4	0,2	0,4	0,6	1,95	0,02	nee	1,5	
Minerale olie	31	118,9	118,9	118,9	118,9	118,9	118,9	118,9	118,9	441,5	126,3	129,0	131,8	0,09	0,00	nee	190,0	
Pentachloorbenzeen	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0025	
Hexachloorbenzeen	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0085	
Pentachloorfenol	31	0,0102	0,0102	0,0102	0,0102	0,0102	0,0102	0,0102	0,0102	0,0102	n.v.t.	0,0102	n.v.t.	0,00	0,00	nee	0,0030	
Chloordaan	31	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	n.v.t.	0,0068	n.v.t.	0,00	0,00	nee	0,0020	
DDT	31	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	n.v.t.	0,0068	n.v.t.	0,00	n.v.t.	n.v.t.	0,2000	
DDD	31	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	n.v.t.	0,0068	n.v.t.	0,00	n.v.t.	n.v.t.	0,0200	
DDE	31	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	n.v.t.	0,0068	n.v.t.	0,00	n.v.t.	n.v.t.	0,1000	
DDT/DDD/DDE	31	0,0204	0,0204	0,0204	0,0204	0,0204	0,0204	0,0204	0,0204	0,0204	n.v.t.	0,0204	n.v.t.	0,00	n.v.t.	nee	0,3000	
Aldrin	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0008	
Dieldrin	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0080	
Endrin	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0035	
Drins (som 3)	31	0,0102	0,0102	0,0102	0,0102	0,0102	0,0102	0,0102	0,0102	0,0102	n.v.t.	0,0102	n.v.t.	0,00	0,00	nee	0,0150	
Isodrin	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0010	
Telodrin	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0005	
α-Endosulfan	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	0,00	nee	0,0009	
Endosulfansulfaat	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	n.v.t.	
α-HCH	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0010	
β-HCH	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0020	
γ-HCH	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0030	
δ-HCH	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	n.v.t.	
HCH (som 4)	31	0,0136	0,0136	0,0136	0,0136	0,0136	0,0136	0,0136	0,0136	0,0136	n.v.t.	0,0136	n.v.t.	0,00	0,00	nee	0,0100	
Heptachloor	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	0,00	nee	0,0007	
Heptachloorepoxide	31	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	n.v.t.	0,0068	n.v.t.	0,00	0,00	nee	0,0020	
Hexachloorbutadieën	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0030	
OCB's (som)	31	0,0781	0,0781	0,0781	0,0781	0,0781	0,0781	0,0781	0,0781	0,0781	n.v.t.	0,0781	n.v.t.	0,00	n.v.t.	nee	0,4000	
Beoordeling PFAS																	Hergebruiksnormen	
																	Beperking type 1	Beperking type 2
PFOA som lineair + vertakt	40	0,00010	0,00010	0,00010	0,00010	0,00016	0,00019	0,00022	0,00025	0,00029	0,00001	0,00013	0,0000	0,43	n.v.t.	n.v.t.	0,0001	
PFOS som lineair + vertakt	40	0,00010	0,00010	0,00010	0,00010	0,00010	0,00010	0,00013	0,00017	0,00020	0,00001	0,00011	0,0000	0,22	n.v.t.	nee	0,0001	
perfluorocetaanzuur (PFOA) lineair	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00016	0,00019	0,00022	0,00025	0,00029	0,00001	0,00012	0,0000	0,57	n.v.t.	n.v.t.	
perfluorocetaanzuur (PFOA) vertakt	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	n.v.t.	0,00007	n.v.t.	0,00	n.v.t.	n.v.t.	0,0001	
perfluorocetaansulfonzuur (PFOS) lineair	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00011	0,00014	0,00019	0,00001	0,00008	0,0000	0,35	n.v.t.	nee	
perfluorocetaansulfonzuur (PFOS) vertakt	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00010	0,00001	0,00007	0,0000	0,07	n.v.t.	nee	
perfluorbutaanzuur (PFBA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00013	0,00014	0,00001	0,00008	0,0000	0,23	n.v.t.	n.v.t.	
perfluorpentaanzuur (PFPeA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	n.v.t.	0,00007	n.v.t.	0,00	n.v.t.	n.v.t.	
perfluorhexaanzuur (PFHxA)	40	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,00007	0,								

Statistische parameters, toetsing aan Besluit Bodemkwaliteit (Waterbodems)

* De norm voor Barium geldt alleen voor die situaties waarbij duidelijke sprake is van antropogene bodemverontreiniging. Voor overige situaties is de norm voor Barium tijdelijk buitenwerking gesteld.
** In verband met 1 of meer gemiddelde gehalten PFAS > 0,0001 mg/kg gelden mogelijk aanvullende toepassingseisen.

	waarde > max. waarde klasse B
	max. waarde klasse A < waarde < max. waarde klasse B
	achtergrondwaarde < waarde < max. waarde klasse A
	waarde < achtergrondwaarde (minimaal 1x >d gemeten)
	waarde < achtergrondwaarde (alleen <d gemeten)
	waarde > hergebruiksnorm conform § 4.8.2 en 4.9.2 uit het Tijdelijk Handelingskader PFAS (versie 29 november 2019) **
	waarde > hergebruiksnorm conform § 4.9.1 uit het Tijdelijk Handelingskader PFAS (versie 29 november 2019) **


Klei, ondergrond (1,0 - 3,0 m-mv)		Statistische parameters															Waterbodemkwaliteitsklasse:			Klasse A		Lut = 25,0 %	
Gezoneerd:	ja																		OS = 10,0 %		25,0 %		
		N	Min	5P	25P	50P	75P	80P	90P	95P	Max	80% MIN	Gem	80% MAX	VC	Hetero- geniteit	P95> I	achtergrond waarde	klasse A	klasse B / interventie- waarde			
Arseen		27	5,7	7,5	9,9	11,7	14,8	14,8	19,5	21,9	35,9	12,0	13,2	14,4	0,37	0,22	nee	20,0	29,0	85,0			
Barium*		27	57,9	70,9	84,4	100,7	115,8	119,1	138,5	147,3	327,4	99,2	108,8	118,4	0,36	n.v.t.	n.v.t.	190,00	n.v.t.	n.v.t.			
Cadmium		27	0,19	0,22	0,39	0,63	0,94	1,04	1,21	2,17	9,82	0,72	1,05	1,38	1,29	0,15	nee	0,60	4,00	14,0			
Chroom		27	20,6	23,3	29,8	34,4	41,8	43,3	47,7	52,0	59,6	34,0	36,0	38,0	0,23	0,09	nee	55,0	120,0	380,0			
Kobalt		27	10,4	11,4	13,7	15,0	18,1	18,7	21,2	22,1	23,7	15,4	16,1	16,8	0,17	0,05	nee	15,0	25,0	240,0			
Koper		27	9,8	13,4	19,5	20,8	24,1	24,7	28,9	36,7	156,0	21,2	26,3	31,3	0,78	0,16	nee	40,0	96,0	190,0			
Kwik		27	0,04	0,04	0,04	0,07	0,11	0,11	0,14	0,32	1,81	0,07	0,15	0,22	2,04	0,03	nee	0,15	1,20	10,0			
Lood		27	27,5	35,0	49,0	63,3	72,3	80,5	95,3	349,0	669,1	69,8	98,3	126,8	1,17	0,59	nee	50,0	138,0	580,0			
Molybdeen		27	1,05	1,05	1,05	1,05	1,05	1,05	1,05	1,05	n.v.t.	n.v.t.	1,05	n.v.t.	0,00	0,00	nee	1,5	5,0	200,0			
Nikkel		27	20,8	24,3	31,2	34,2	40,4	40,4	47,5	51,5	52,6	34,2	35,8	37,4	0,18	0,16	nee	35,0	50,0	210,0			
Zink		27	80,4	84,7	124,5	166,0	242,6	265,6	301,4	618,0	2043,1	192,6	265,6	338,6	1,11	0,29	nee	140,0	563,0	2000,0			
PCB28		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	nee	0,0015	0,0140	n.v.t.				
PCB52		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	nee	0,0020	0,0150	n.v.t.				
PCB101		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	nee	0,0015	0,0230	n.v.t.				
PCB118		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	nee	0,0045	0,0160	n.v.t.				
PCB138		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	nee	0,0040	0,0270	n.v.t.				
PCB153		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	nee	0,0035	0,0330	n.v.t.				
PCB180		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	nee	0,0025	0,0180	n.v.t.				
PCB (som 7)		27	0,0194	0,0194	0,0194	0,0194	0,0194	0,0194	0,0194	0,0194	n.v.t.	0,0194	n.v.t.	0,00	0,00	nee	0,0200	0,1390	1,0				
PAK (som 10)		27	0,2	0,2	0,2	0,2	0,2	0,2	0,3	0,9	10,0	0,1	0,6	1,1	3,14	0,02	nee	1,5	9,0	40,0			
Minerale olie		27	97,1	97,1	97,1	97,1	97,1	97,1	97,1	97,1	475,8	106,5	111,0	115,5	0,17	0,00	nee	190,0	1250,0	5000,0			
Pentachloorbenzeen		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0025	0,0070	n.v.t.				
Hexachloorbenzeen		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0052	0,0027	0,0028	0,0028	0,04	n.v.t.	n.v.t.	0,0085	0,0440	n.v.t.			
Pentachloorfenol		27	0,0083	0,0083	0,0083	0,0083	0,0083	0,0083	0,0083	0,0083	0,0083	n.v.t.	0,0083	n.v.t.	0,00	0,00	nee	0,0030	0,0160	5,0			
Chloordaan		27	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	n.v.t.	0,0056	n.v.t.	0,00	0,00	nee	0,0020	n.v.t.	4,0			
DDT		27	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	n.v.t.	0,0056	n.v.t.	0,00	n.v.t.	n.v.t.	0,2000	n.v.t.	n.v.t.			
DDD		27	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	n.v.t.	0,0056	n.v.t.	0,00	n.v.t.	n.v.t.	0,0200	n.v.t.	n.v.t.			
DDE		27	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	n.v.t.	0,0056	n.v.t.	0,00	n.v.t.	n.v.t.	0,1000	n.v.t.	n.v.t.			
DDT/DDD/DDE		27	0,0167	0,0167	0,0167	0,0167	0,0167	0,0167	0,0167	0,0167	0,0167	n.v.t.	0,0167	n.v.t.	0,00	n.v.t.	nee	0,3000	0,3000	4,0			
Aldrin		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0008	0,0013	n.v.t.			
Dieldrin		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0080	0,0080	n.v.t.			
Endrin		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0035	0,0035	n.v.t.			
Drins (som 3)		27	0,0083	0,0083	0,0083	0,0083	0,0083	0,0083	0,0083	0,0083	0,0083	n.v.t.	0,0083	n.v.t.	0,00	0,00	nee	0,0150	0,0150	4,0			
Isodrin		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0010	n.v.t.	n.v.t.			
Telodrin		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0005	n.v.t.	n.v.t.			
α-Endosulfan		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	0,00	nee	0,0009	0,0021	4,0			
Endosulfansulfaat		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	n.v.t.	n.v.t.	n.v.t.			
α-HCH		26	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0010	0,0012	n.v.t.			
β-HCH		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0020	0,0065	n.v.t.			
γ-HCH		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0030	0,0030	n.v.t.			
δ-HCH		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	n.v.t.	n.v.t.	n.v.t.			
HCH (som 4)		26	0,0111	0,0111	0,0111	0,0111	0,0111	0,0111	0,0111	0,0111	0,0111	n.v.t.	0,0111	n.v.t.	0,00	0,00	nee	0,0100	0,0100	2,0			
Heptachloor		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	0,00	nee	0,0007	0,0040	4,0			
Heptachloorepoxide		27	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	0,0056	n.v.t.	0,0056	n.v.t.	0,00	0,00	nee	0,0020	0,0040	4,0			
Hexachloorbutadieën		27	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	0,0028	n.v.t.	0,0028	n.v.t.	0,00	n.v.t.	n.v.t.	0,0030	0,0075	n.v.t.			
OCB's (som)		27	0,0638	0,0638	0,0638	0,0638	0,0638	0,0638	0,0638	0,0638	0,0793	0,0640	0,0642	0,0644	0,01	n.v.t.	nee	0,4000	n.v.t.	n.v.t.			

Statistische parameters, toetsing aan Besluit Bodemkwaliteit (Waterbodems)

* De norm voor Barium geldt alleen voor die situaties waarbij duidelijke sprake is van antropogene bodemverontreiniging. Voor overige situaties is de norm voor Barium tijdelijk buitenwerking gesteld.
** In verband met 1 of meer gemiddelde gehalten PFAS > 0,0001 mg/kg gelden mogelijk aanvullende toepassingseisen.

	waarde > max. waarde klasse B
	max. waarde klasse A < waarde < max. waarde klasse B
	achtergrondwaarde < waarde < max. waarde klasse A
	waarde < achtergrondwaarde (minimaal 1x >d gemeten)
	waarde < achtergrondwaarde (alleen <d gemeten)
	waarde > hergebruiksnorm conform § 4.8.2 en 4.9.2 uit het Tijdelijk Handelingskader PFAS (versie 29 november 2019) **
	waarde > hergebruiksnorm conform § 4.9.1 uit het Tijdelijk Handelingskader PFAS (versie 29 november 2019) **

Statistische parameters																					
Zand, ondergrond (1,0 - 3,0 m-mv)										Waterbodemkwaliteitsklasse:							Vrij toepasbaar			Lut = 25,0 % OS = 10,0 %	
Gezoneerd:	ja																				
Stoffen	N	Min	5P	25P	50P	75P	80P	90P	95P	Max	80% MIN	Gem	80% MAX	VC	Hetero- geniteit	P95> I	achtergrond waarde	klasse A	klasse B / interventie- waarde		
Arseen	31	4,7	4,7	4,7	4,7	8,2	8,6	12,2	14,9	33,8	6,6	7,4	8,2	0,46	0,16	nee	20,0	29,0	85,0		
Barium*	31	46,3	46,3	46,3	46,3	56,2	86,0	109,1	163,7	529,1	70,5	76,7	83,0	0,35	n.v.t.	n.v.t.	190,00	n.v.t.	n.v.t.		
Cadmium	31	0,24	0,24	0,24	0,24	0,24	0,24	0,62	2,35	8,41	0,45	0,66	0,87	1,39	0,16	nee	0,60	4,00	14,0		
Chroom	31	12,3	12,3	12,3	12,3	19,4	22,9	28,2	30,0	67,0	15,8	17,3	18,7	0,36	0,05	nee	55,0	120,0	380,0		
Kobalt	31	6,1	7,0	10,4	11,9	17,3	19,3	22,0	24,1	33,6	13,6	14,1	14,5	0,14	0,08	nee	15,0	25,0	240,0		
Koper	31	6,9	6,9	6,9	6,9	6,9	9,9	14,6	34,5	236,6	11,9	16,8	21,6	1,25	0,18	nee	40,0	96,0	190,0		
Kwik	31	0,05	0,05	0,05	0,05	0,05	0,05	0,05	0,22	1,83	0,06	0,11	0,16	2,03	0,02	nee	0,15	1,20	10,0		
Lood	31	10,7	10,7	10,7	10,7	14,6	19,9	47,5	124,2	552,0	23,2	38,3	53,3	1,71	0,21	nee	50,0	138,0	580,0		
Molybdeen	31	1,05	1,05	1,05	1,05	1,05	1,05	1,05	1,05	1,05	n.v.t.	1,05	n.v.t.	0,00	0,00	nee	1,5	5,0	200,0		
Nikkel	31	12,6	14,4	18,3	24,3	31,4	34,0	39,3	43,2	55,0	25,0	25,9	26,8	0,15	0,16	nee	35,0	50,0	210,0		
Zink	31	31,0	31,0	37,6	59,8	89,7	97,4	194,9	708,7	2214,7	132,1	175,6	219,2	1,08	0,36	nee	140,0	563,0	2000,0		
PCB28	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	nee	0,0015	0,0140	n.v.t.		
PCB52	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	nee	0,0020	0,0150	n.v.t.		
PCB101	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	nee	0,0015	0,0230	n.v.t.		
PCB118	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	nee	0,0045	0,0160	n.v.t.		
PCB138	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	nee	0,0040	0,0270	n.v.t.		
PCB153	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	nee	0,0035	0,0330	n.v.t.		
PCB180	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	nee	0,0025	0,0180	n.v.t.		
PCB (som 7)	31	0,0238	0,0238	0,0238	0,0238	0,0238	0,0238	0,0238	0,0238	0,0238	n.v.t.	0,0238	n.v.t.	0,00	0,00	nee	0,0200	0,1390	1,0		
PAK (som 10)	31	0,2	0,2	0,2	0,2	0,2	0,2	0,2	1,1	4,4	0,2	0,4	0,6	1,95	0,02	nee	1,5	9,0	40,0		
Minerale olie	31	118,9	118,9	118,9	118,9	118,9	118,9	118,9	118,9	441,5	126,3	129,0	131,8	0,09	0,00	nee	190,0	1250,0	5000,0		
Pentachloorbenzeen	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0025	0,0070	n.v.t.		
Hexachloorbenzeen	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0085	0,0440	n.v.t.		
Pentachloorfenol	31	0,0102	0,0102	0,0102	0,0102	0,0102	0,0102	0,0102	0,0102	0,0102	n.v.t.	0,0102	n.v.t.	0,00	0,00	nee	0,0030	0,0160	5,0		
Chloordaan	31	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	n.v.t.	0,0068	n.v.t.	0,00	0,00	nee	0,0020	n.v.t.	4,0		
DDT	31	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	n.v.t.	0,0068	n.v.t.	0,00	n.v.t.	n.v.t.	0,2000	n.v.t.	n.v.t.		
DDD	31	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	n.v.t.	0,0068	n.v.t.	0,00	n.v.t.	n.v.t.	0,0200	n.v.t.	n.v.t.		
DDE	31	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	n.v.t.	0,0068	n.v.t.	0,00	n.v.t.	n.v.t.	0,1000	n.v.t.	n.v.t.		
DDT/DDD/DDE	31	0,0204	0,0204	0,0204	0,0204	0,0204	0,0204	0,0204	0,0204	0,0204	n.v.t.	0,0204	n.v.t.	0,00	n.v.t.	nee	0,3000	0,3000	4,0		
Aldrin	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0008	0,0013	n.v.t.		
Dieldrin	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0080	0,0080	n.v.t.		
Endrin	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0035	0,0035	n.v.t.		
Drins (som 3)	31	0,0102	0,0102	0,0102	0,0102	0,0102	0,0102	0,0102	0,0102	0,0102	n.v.t.	0,0102	n.v.t.	0,00	0,00	nee	0,0150	0,0150	4,0		
Isodrin	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0010	n.v.t.	n.v.t.		
Telodrin	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0005	n.v.t.	n.v.t.		
α-Endosulfan	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	0,00	nee	0,0009	0,0021	4,0		
Endosulfansulfaat	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	n.v.t.	n.v.t.	n.v.t.		
α-HCH	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0010	0,0012	n.v.t.		
β-HCH	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0020	0,0065	n.v.t.		
γ-HCH	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0030	0,0030	n.v.t.		
δ-HCH	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	n.v.t.	n.v.t.	n.v.t.		
HCH (som 4)	31	0,0136	0,0136	0,0136	0,0136	0,0136	0,0136	0,0136	0,0136	0,0136	n.v.t.	0,0136	n.v.t.	0,00	0,00	nee	0,0100	0,0100	2,0		
Heptachloor	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	0,00	nee	0,0007	0,0040	4,0		
Heptachloorepoxide	31	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	0,0068	n.v.t.	0,0068	n.v.t.	0,00	0,00	nee	0,0020	0,0040	4,0		
Hexachloorbutadieën	31	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	0,0034	n.v.t.	0,0034	n.v.t.	0,00	n.v.t.	n.v.t.	0,0030	0,0075	n.v.t.		
OCB's (som)	31	0,0781	0,0781	0,0781	0,0781	0,0781	0,0781	0,0781	0,0781	0,0781	n.v.t.	0,0781	n.v.t.	0,00	n.v.t.	nee	0,4000	n.v.t.	n.v.t.		



LEGENDA

Bodemkwaliteitszones

- Oeverzone
- Riviervlakte


Overige

- Uitgesloten gebied

Uitgezonderd van de waterbodemkwaliteitskaart zijn:

- de op de kaart aangegeven drogere oevergebieden;
- wegen en dijklichamen;
- watergangen en poelen in beheer bij Rijkswaterstaat Zuid Nederland;
- de waterbodemplaa dieper dan 3 meter minus maaiveld;
- het grondwater.

Voorafgaand aan het gebruik van deze kaart als bewijsmiddel bij grondverzet dient altijd te worden onderzocht of er sprake is van een uitgesloten gebied waar deze kaart niet van toepassing is.



Sources: Esri, HERE, Garmin, USGS, Intermap, iPC, INCREMENT P, NRCan, Esri Japan, METI, Esri China

TITEL

Beheergebied en uitgesloten gebieden

PROJECT

Actualisatie waterbodemkwaliteitskaart Demen-Dieden

OPDRACHTGEVER

K3Delta

Kaartnr:

SOB10398.D7

Versie:

Definitief

Auteur:

Paul Karels

Gecontroleerd:

Jeroen Spronk

Schaal (A3):

1:11.000


Datum:

december 2019



LIEVENSE
adviseurs ingenieurs

Ringsedijk 41, 3429 LM Nieuwegein
+31 (0)85 970 2000
www.lievense.nl



LEGENDA

Ontgraving- en toepassingsklasse (waterbodem) *

- Niet toepasbaar
- Klasse B
- Klasse A
- Vrij toepasbaar

Overige

- Uitgesloten gebied

* In verband met de aanwezigheid van 1 of meer gemiddelde gehalten PFAS > 0,0001 mg/kg gelden mogelijk aanvullende toepassingseisen als grond buiten het beheergebied wordt toegepast.

Voorafgaand aan het gebruik van deze kaart als bewijsmiddel bij grondverzet dient altijd te worden onderzocht of er sprake is van een uitgesloten gebied waar deze kaart niet van toepassing is.

TITEL

Kwaliteitskaart toplaag (0 - 0,5 m-wb)

PROJECT

Actualisatie waterbodemkwaliteitskaart Demen-Dieden

OPDRACHTGEVER

K3Delta

Kaartnr:

SOB10398.D8

Versie:

Definitief

LIEVENSE

adviseurs ingenieurs

Ringside 41, 3429 LM Nieuwegein

+31 (0) 30 2200

www.lievense.nl

Auteur:

Paul Karels

Gecontroleerd:

Jeroen Spronk

Schaal (A3):

1:11.000

Datum:

december 2019





LEGENDA

Ontgraving- en toepassingsklasse (waterbodem) *

- Niet toepasbaar
- Klasse B
- Klasse A
- Vrij toepasbaar

Overige

- Uitgesloten gebied

* In verband met de aanwezigheid van 1 of meer gemiddelde gehalten PFAS > 0,0001 mg/kg gelden mogelijk aanvullende toepassingseisen als grond buiten het beheergebied wordt toegepast.

Voorafgaand aan het gebruik van deze kaart als bewijsmiddel bij grondverzet dient altijd te worden onderzocht of er sprake is van een uitgesloten gebied waar deze kaart niet van toepassing is.

TITEL

Kwaliteitskaart tussenlaag (0,5 - 1,0 m-wb)

PROJECT

Actualisatie waterbodemkwaliteitskaart Demen-Dieden

OPDRACHTGEVER

K3Delta

Kaartnr:

SOB10398.D9

Versie:

Definitief

LIEVENSE

adviseurs ingenieurs

Ringside 41, 3429 LM Nieuwegein

+31 (0) 35 110 2000

www.lievense.nl

Auteur:

Paul Karels

Gecontroleerd:

Jeroen Spronk

Schaal (A3):

1:11.000

Datum:

december 2019





LEGENDA

Ontgraving- en toepassingsklasse (waterbodem) *

- Niet toepasbaar
- Klasse B
- Klasse A
- Vrij toepasbaar

Overige

- Uitgesloten gebied

Voorafgaand aan het gebruik van deze kaart als bewijsmiddel bij grondverzet dient altijd te worden onderzocht of er sprake is van een uitgesloten gebied waar deze kaart niet van toepassing is.

TITEL

Kwaliteitskaart ondergrond (1,0 - 3,0 m-wb)

PROJECT

Actualisatie waterbodemkwaliteitskaart Demen-Dieden

OPDRACHTGEVER

K3Delta

Kaartnr:

SOB10398.D10

Versie:

Definitief

LIEVENSE

adviseurs ingenieurs

Ringside 41, 3429 LM Nieuwegein
+31 (0) 35 910 2000
www.lievense.nl

Auteur:

Paul Karels

Gecontroleerd:

Jeroen Spronk

Schaal (A3):

1:11.000

Datum:

december 2019

